

EUROLITE Set 2x LED THA-150F + Case

2x fresnel spot with 170 W warm white/amber LED including PRO flightcase

Art. No.: 2000680

GTIN: 4026397360950



List price: 2259.81 €

incl. 19% VAT.

Features:

EUROLITE LED THA-150F Theater-Spot

Fresnel spotlight, dim to warm, 170 W warm white/amber LED, CRI >90, quiet, DMX

- New LED technology that simulates the color temperature curve of a halogen lamp when dimming
- Rugged metal housing
- 1 powerful LED 170 W COB (chip-on-board) Dim to warm (homogenous color mix)
- Zoom motor-driven
- The device is cooled by temperature-controlled fan
- Control via RDM; DMX
- Flicker-free
- With a beam angle of 8° - 55°
- Very high color rendering index (CRI)
- With Mounting bracket
- LCD display
- Exact 16 bit resolution at Dimmer
- Color blend stepless; Dimmer electronic; Dimmer speed (step response) adjustable; dimmer curves adjustable
- Strobe effect
- Preprogrammed in Light´J; Light Captain
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Trade fair and shop fitting; Installation; Stage; theater
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x barndoor, 1 x filter frame

Logistic

EAN / GTIN: 4026397360950

Weight: 40,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.45 m

Bulky product

ROADINGER Flightcase 2x LED THA-150F Theater-Spot

Trunk case, PRO version

- With accessory compartment
- With 2 Device compartments
- 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware

Technical specifications:

Weight: 31,90 kg

EUROLITE LED THA-150F Theater-Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	150 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	P-Con (gray), mounting version
LED:	1 x 170 W COB (chip-on-board) Dim to warm (homogenous color mix)
Equipment:	Zoom motor-driven
DMX channels:	2; 6; 7
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	RDM; DMX
Preprogrammed in:	Light J; Light Captain
Projection:	Flicker-free
Beam angle:	8° - 55°
Beam angle (1/2 peak):	8 - 39°
Beam angle (1/10 peak):	12 - 55°
Color rendering index (CRI):	96 Ra
Luminous flux:	5093 lm
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Transport aid:	Rubber feet

Dimensions:	Length: 45,7 cm Width: 33,6 cm Height: 39,8 cm
Weight:	9,40 kg
Noise classification:	Class 2 (slight noise)
Energy efficiency class (A - G):	G

ROADINGER Flightcase 2x LED THA-150F Theater-Spot

Maximum load:	50 kg
Aluminum profile frames:	25 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Color:	Dark brown, laminated
Device compartment:	38,5 cm x 40 cm x 23 cm
Accessory compartment:	10 cm x 48 cm x 23 cm
Inside dimensions:	87 cm x 48 cm x 23 cm
Material thickness:	7 mm
Dimensions:	Width: 92 cm Depth: 37 cm Height: 52 cm
Weight:	13,10 kg