

EUROLITE Set 4x LED THA-150F + Case

4x fresnel spot with 170 W warm white/amber LED including PRO flightcase

Art. No.: 2000681

GTIN: 4026397360974



Features:

- New LED technology that simulates the color temperature curve of a halogen lamp when dimming
- Rugged metal housing
- 1 LED 170 W COB (chip-on-board) Dim to warm (homogenous color mix)
- Exact 16 bit resolution at Dimmer
- Zoom motor driven
- Color blend stepless; Dimmer electronic; Dimmer speed (step response) adjustable; dimmer curves adjustable
- Strobe effect
- The device is cooled by temperature-controlled fan
- Control via RDM; DMX
- Fixtures available for Light´J; Light Captain
- Flicker-free
- With a beam angle of 8° - 55°
- Very high color rendering index (CRI)
- With mounting bracket
- LCD display
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; wedding/gala/events; Trade fair and shop fitting; theater; rental; video and photography
- Application possibility: Suspended; on stand
- <p>ROADINGER Flightcase 4x LED THA-150F Theater Spot
- <h2 class="featureSatz">Trunk case with castors, PRO version</h2>With accessory compartment
- With 4 device compartments

Logistic

EAN / GTIN: 4026397360974

Weight: 78,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.85 m

Bulky product

- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- Branded hardware

Technical specifications:

Weight: 66.50 kg

EUROLITE LED THA-150F Theater Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	150 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug included
Power output:	P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	1 x 170 W COB (chip-on-board) Dim to warm (homogenous color mix)
Equipment:	Zoom motor driven
DMX channels:	2; 6; 7
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	RDM; DMX
Fixtures available for:	Light J; Light Captain
Projection:	Flicker-free
Beam angle:	8° - 55°
Beam angle (1/2 peak):	8 - 39°
Beam angle (1/10 peak):	12 - 55°
Color rendering index (CRI):	96 Ra
Luminous flux:	5093 lm
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Transport aid:	Rubber feet
Material:	Aluminum casting; metal

Slot for spot length:	20 cm x 20 cm
Dimensions:	Length: 45.7 cm Width: 33.6 cm Height: 39.8 cm
Weight:	9.40 kg
Noise classification:	Class 2 (slight noise)
Energy efficiency class (A - G):	G
EPREL-Nr:	1243870
Diameter mounting holes:	5 x Ø10mm
Material:	Aluminum casting, 6.5 mm
Cable construction:	3 x 1.5 mm ² H05VV-F
Cable length:	Approx. 1.3 m
Material:	Aluminum, 1.5 mm; metal, 1 mm
Ring diameter:	Outside: 198 mm Inside: 220 mm
Dimensions:	Width: 50.5 cm Depth: 4.2 cm Height: 50.5 cm
Material:	Aluminum, 1 mm
Dimensions:	Width: 22.5 cm Height: 22.5 cm Diameter: Ø 18 cm

ROADINGER Flightcase 4x LED THA-150F Theater Spot

Maximum load:	100 kg
Aluminum profile frames:	25 mm
Case handle:	4 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Accessory compartment:	9 cm x 79 cm x 23.5 cm
Device compartment:	48 cm x 22.5 cm x 23.5 cm
Inside dimensions:	105 cm x 79 cm x 23.5 cm
Dimensions:	Width: 112 cm Depth: 50 cm Height: 84 cm
Weight:	28.90 kg

Scope of delivery:

- 1 x spotlight
- 1 x power cord
- 1 x barndoor
- 1 x filter frame

1 x user manual