eurolite®

EUROLITE Set PAR-16 Spot sil + GU-10 230V COB 5W LED 1800-3000K dim2warn2000687

PAR-16 housing with GU-10 socket including LED lamp with modern dim-to-warm-feature

GTIN: 4026397361582







List price: 35.58 €

incl. 19% VAT.

Features:

EUROLITE PAR-16 Spot GU-10 silver

PAR-16 housing with GU10 socket (with plug + cable)

- Mini-spot for GU-10 lamp
- Control via plug and play
- For PAR 16
- Package contents
- 1 x spotlight, 1 x filter frame, 1 x user manual

OMNILUX GU-10 230V COB 5W LED 1800-3000K dim2warm

LED lamp with modern dim-to-warm feature

- Dimming behavior comparable with incandescent and halogen lamps (dim-to-warm)
- Changes the light color from 3000 K (warm white) to 1800 K (extra warm white) when dimming
- Creates particularly cosy atmospheres
- Easy lamp replacement
- Energy-saving
- Dimmable
- Easy installation
- With a beam angle of 24°
- Variable color temperature 1800 K 3000 K
- Very high color rendering index (CRI)

Logistic

EAN / GTIN: 4026397361582 Weight: 0,50 kg Length: 0.17 m Width: 0.10 m Heigth: 0.10 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Technical specifications:

Weight:	0,32 kg
Energy efficiency class (A - G):	F

Power supply:230 V AC, 50 HzPower consumption:Max. 75 WIP classification:IP20Protection class:Protection class IPower connection:Fixed power supply cord with safety plugCable construction:3 x 0,75 mm² H05SS-FCable length:Approx. 0,4 mBase:GU10Lamp type:SelectableCotrol:Plug and playControl:Plug and playControl:PAR-16Housing color:SilverMaterial:Aluminum, 1 mmSlot for spot length:8 cm x 8 cmDimensions:Length: 17 cm Width: 11 cm Height: 13 cmWeight:0,28 kgMounting bracketDiameter mounting holes:Shape:Octagonal Material:Material:AluminumDimensions:Length: 7,7 cm Width: 7,7 cm Diameter: Ø 5,3 cmWeight:0,01 kg	EUROLITE PAR-16 Spot GU-10 silver	
IP classification: IP20 Protection class: Protection class I Power connection: Fixed power supply cord with safety plug Cable construction: 3 x 0,75 mm² H05SS-F Cable length: Approx. 0,4 m Base: GU10 Lamp type: Selectable Color generation: Via color filter frame Control: Plug and play Construction: PAR-16 Housing color: Silver Material: Aluminum, 1 mm Slot for spot length: 8 cm x 8 cm Dimensions: Length: 17 cm Width: 11 cm Height: 13 cm Veight: 0,28 kg Mounting bracket Diameter mounting holes: Diameter mounting holes: 2 x Ø10mm Material: Aluminum, 3 mm Filter frame Shape: Octagonal Material: Material: Aluminum Dimensions: Length: 7,7 cm Width: 7,7 cm Diameter: Ø 5,3 cm Diameter: Ø 5,3 cm	Power supply:	230 V AC, 50 Hz
Protection class:Protection class IPower connection:Fixed power supply cord with safety plugCable construction:3 x 0,75 mm² H05SS-FCable length:Approx. 0,4 mBase:GU10Lamp type:SelectableColor generation:Via color filter frameControl:Plug and playConstruction:PAR-16Housing color:SilverMaterial:Aluminum, 1 mmSlot for spot length:8 cm x 8 cmDimensions:Length: 17 cm Width: 11 cm Height: 13 cmWeight:0,28 kgMounting bracketDiameter mounting holes:2 x Ø10mmAluminum, 3 mmFilter frameOctagonalShape:OctagonalMaterial:AluminumDimensions:Length: 7,7 cm Width: 7,7 cm Diameter: Ø 5,3 cm	Power consumption:	Max. 75 W
Power connection:Fixed power supply cord with safety plugCable construction:3 x 0,75 mm² H05SS-FCable length:Approx. 0,4 mBase:GU10Lamp type:SelectableColor generation:Via color filter frameControl:Plug and playConstruction:PAR-16Housing color:SilverMaterial:Aluminum, 1 mmSlot for spot length:8 cm x 8 cmDimensions:Length: 17 cmWeight:0,28 kgMounting bracketDiameter mounting holes:Plaretail:Aluminum, 3 mmFilter frameShape:OctagonalMaterial:AluminumDimensions:Length: 7,7 cmWidth: 7,7 cmWidth: 7,7 cmDimensions:Length: 7,7 cmDimensions:Length: 7,7 cmDimensions:Length: 7,7 cmDiameter:Ø,33 cm	IP classification:	IP20
Cable construction:3 x 0,75 mm² H05SS-FCable length:Approx. 0,4 mBase:GU10Lamp type:SelectableColor generation:Via color filter frameControl:Plug and playConstruction:PAR-16Housing color:SilverMaterial:Aluminum, 1 mmSlot for spot length:8 cm x 8 cmDimensions:Length: 17 cmWidth: 11 cmHeight: 13 cmWeight:0,28 kgMounting bracketDiameter mounting holes:2 x Ø10mmAluminum, 3 mmFilter frameShape:OctagonalAluminumDimensions:Length: 7,7 cmWidth: 7,7 cmDiameter: Ø 5,3 cm	Protection class:	Protection class I
Cable length:Approx. 0,4 mBase:GU10Lamp type:SelectableColor generation:Via color filter frameControl:Plug and playConstruction:PAR-16Housing color:SilverMaterial:Aluminum, 1 mmSlot for spot length:8 cm x 8 cmDimensions:Length: 17 cmWeight:0,28 kgMounting bracketDiameter mounting holes:Pitter frame2 x Ø10mmShape:OctagonalMaterial:Aluminum, 3 mmFilter frameDimensions:Length: 7,7 cmWidth: 7,7 cmDimensions:Length: 7,7 cmWidth: 7,7 cmDiameter: Ø 5,3 cm	Power connection:	Fixed power supply cord with safety plug
Base: GU10 Lamp type: Selectable Color generation: Via color filter frame Control: Plug and play Construction: PAR-16 Housing color: Silver Material: Aluminum, 1 mm Slot for spot length: 8 cm x 8 cm Dimensions: Length: 17 cm Weight: 0,28 kg Mounting bracket Diameter mounting holes: Pitter frame Stape: Shape: Octagonal Material: Aluminum Dimensions: Length: 7,7 cm Width: 7,7 cm Diameter: Ø 5,3 cm	Cable construction:	3 x 0,75 mm ² H05SS-F
Lamp type:SelectableColor generation:Via color filter frameControl:Plug and playConstruction:PAR-16Housing color:SilverMaterial:Aluminum, 1 mmSlot for spot length:8 cm x 8 cmDimensions:Length: 17 cmWeight:0,28 kgMounting bracketDiameter mounting holes:2 x Ø10mmFilter frameShape:OctagonalMaterial:Aluminum, 3 mmFilter frameDimensions:Length: 7,7 cmWidth: 7,7 cmDimensions:Length: 7,7 cmWidth: 7,7 cmDiameter: Ø 5,3 cm	Cable length:	Approx. 0,4 m
Color generation: Via color filter frame Control: Plug and play Construction: PAR-16 Housing color: Silver Material: Aluminum, 1 mm Slot for spot length: 8 cm x 8 cm Dimensions: Length: 17 cm Weight: 0,28 kg Mounting bracket Diameter mounting holes: 2 x Ø10mm Aluminum, 3 mm Filter frame Shape: Octagonal Material: Material: Aluminum Dimensions: Length: 7,7 cm Weight: 0,28 kg	Base:	GU10
Control:Plug and playConstruction:PAR-16Housing color:SilverMaterial:Aluminum, 1 mmSlot for spot length:8 cm x 8 cmDimensions:Length: 17 cmWidth: 11 cmHeight: 13 cmWeight:0,28 kgMounting bracketDiameter mounting holes:2 x Ø10mmAluminum, 3 mmFilter frameShape:OctagonalAluminumDimensions:Length: 7,7 cmWidth: 7,7 cmDiameter: Ø 5,3 cm	Lamp type:	Selectable
Construction: PAR-16 Housing color: Silver Material: Aluminum, 1 mm Slot for spot length: 8 cm x 8 cm Dimensions: Length: 17 cm Width: 11 cm Height: 13 cm Weight: 0,28 kg Mounting bracket Diameter mounting holes: 2 x Ø10mm Material: Aluminum, 3 mm Filter frame Shape: Octagonal Material: Aluminum Dimensions: Length: 7,7 cm Width: 7,7 cm Diameter: Ø 5,3 cm	Color generation:	Via color filter frame
Housing color:SilverMaterial:Aluminum, 1 mmSlot for spot length:8 cm x 8 cmDimensions:Length: 17 cm Width: 11 cm Height: 13 cmWeight:0,28 kgMounting bracketDiameter mounting holes:2 x Ø10mmMaterial:Aluminum, 3 mmFilter frameOctagonalShape:OctagonalMaterial:AluminumDimensions:Length: 7,7 cm Width: 7,7 cm Diameter: Ø 5,3 cm	Control:	Plug and play
Material:Aluminum, 1 mmSlot for spot length:8 cm x 8 cmDimensions:Length: 17 cmWidth: 11 cmHeight: 13 cmWeight:0,28 kgMounting bracketDiameter mounting holes:2 x Ø10mmMaterial:Aluminum, 3 mmFilter frameOctagonalMaterial:AluminumDimensions:Length: 7,7 cmWidth: 7,7 cmWidth: 7,7 cmDiameter: Ø 5,3 cmDiameter: Ø 5,3 cm	Construction:	PAR-16
Slot for spot length: 8 cm x 8 cm Dimensions: Length: 17 cm Width: 11 cm Height: 13 cm Weight: 0,28 kg Mounting bracket Diameter mounting holes: Diameter mounting holes: 2 x Ø10mm Material: Aluminum, 3 mm Filter frame Octagonal Material: Aluminum Dimensions: Length: 7,7 cm Diameter: Ø 5,3 cm	Housing color:	Silver
Dimensions:Length: 17 cm Width: 11 cm Height: 13 cmWeight:0,28 kgMounting bracket0,28 kgDiameter mounting holes:2 x Ø10mmMaterial:Aluminum, 3 mmFilter frameShape:Shape:OctagonalMaterial:AluminumDimensions:Length: 7,7 cm Width: 7,7 cm Diameter: Ø 5,3 cm	Material:	Aluminum, 1 mm
Width: 11 cm Height: 13 cmWeight:0,28 kgMounting bracketDiameter mounting holes:2 x Ø10mmMaterial:Aluminum, 3 mmFilter frameShape:OctagonalMaterial:AluminumDimensions:Length: 7,7 cm Width: 7,7 cm Diameter: Ø 5,3 cm	Slot for spot length:	8 cm x 8 cm
Height: 13 cmWeight:0,28 kgMounting bracketDiameter mounting holes:2 x Ø10mmMaterial:Aluminum, 3 mmFilter frameShape:OctagonalMaterial:AluminumDimensions:Length: 7,7 cm Width: 7,7 cm Diameter: Ø 5,3 cm	Dimensions:	Length: 17 cm
Weight:0,28 kgMounting bracketDiameter mounting holes:2 x Ø10mmMaterial:Aluminum, 3 mmFilter frameShape:OctagonalMaterial:AluminumDimensions:Length: 7,7 cm Width: 7,7 cm Diameter: Ø 5,3 cm		
Mounting bracket Diameter mounting holes: 2 x Ø10mm Material: Aluminum, 3 mm Filter frame Shape: Shape: Octagonal Material: Aluminum Dimensions: Length: 7,7 cm Diameter: Ø 5,3 cm Diameter: Ø 5,3 cm		Height: 13 cm
Diameter mounting holes: 2 x Ø10mm Material: Aluminum, 3 mm Filter frame Shape: Shape: Octagonal Material: Aluminum Dimensions: Length: 7,7 cm Diameter: Ø 5,3 cm Diameter: Ø 5,3 cm	Weight:	0,28 kg
Material: Aluminum, 3 mm Filter frame Shape: Shape: Octagonal Material: Aluminum Dimensions: Length: 7,7 cm Width: 7,7 cm Diameter: Ø 5,3 cm	Mounting bracket	
Filter frame Shape: Octagonal Material: Aluminum Dimensions: Length: 7,7 cm Width: 7,7 cm Diameter: Ø 5,3 cm	Diameter mounting holes:	2 x Ø10mm
Shape: Octagonal Material: Aluminum Dimensions: Length: 7,7 cm Width: 7,7 cm Diameter: Ø 5,3 cm	Material:	Aluminum, 3 mm
Material: Aluminum Dimensions: Length: 7,7 cm Width: 7,7 cm Diameter: Ø 5,3 cm	Filter frame	
Dimensions: Width: 7,7 cm Diameter: Ø 5,3 cm	Shape:	Octagonal
Width: 7,7 cm Diameter: Ø 5,3 cm	Material:	Aluminum
Diameter: Ø 5,3 cm	Dimensions:	Length: 7,7 cm
		Width: 7,7 cm
Weight: 0,01 kg		Diameter: Ø 5,3 cm
	Weight:	0,01 kg

OMNILUX GU-10 230V COB 5W LED 1800-3000K dim2warm

Operating voltage:	230
Nominal wattage:	5 W
Base:	GU10

Lamp type:	LED lamp; reflector lamp
Lamp specification:	Dimmable
Measurand (Pst LM):	0,0
Setup:	Easy installation
Beam angle:	24°
Beam angle (1/2 peak):	24°
Beam angle (1/10 peak):	60°
Color of light:	White
Color temperature:	1800K - 3000K adjustable
Color rendering index (CRI):	90 Ra
Luminous flux maintenance:	13
MacAdam Color consistency:	3
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Lamp life:	15000 h
Luminous flux:	400 lm
Luminous flux maintenance:	0,97
Wavelength:	640 nm
Material:	Aluminum casting
Dimensions:	Width: 5 cm
	Depth: 5 cm
	Height: 5 cm
Weight:	0,04 kg
Energy efficiency class (A - G):	F
EPREL-Nr:	960770