EUROLITE Set PAR-20 Spot sil + PAR-20 230V COB 6W E-27 LED 1800-3000K dim2warm

Art.-Nr.: 51700358

PAR-20 housing with E-27 socket including PAR-20 LED lamp with modern dim-to-warm-feature

GTIN: 4026397362350

List price: 42.72 €

incl. 19% VAT.

Features:

EUROLITE PAR-20 Spot silver

PAR-20 housing with E27 socket (with plug + cable)

- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Strong clamps with extension springs for safe hold and for quick opening of the rear housing cover
- Blackened tube for precise light output
- Strong cable tension relief
- Control via plug and play
- With Mounting bracket
- Available in various colors
- For PAR 20
- For application areas such as: Advertisement/Shop window; Decoration; Clubs/dancing school

Package contents

- 1 x spotlight, 1 x mounting bracket, 1 x filter frame, 1 x user manual

OMNILUX PAR-20 230V COB 6W E-27 LED 1800k-3000k dim2warm

PAR-20 LED lamp with modern dim-to-warm feature

- Dimming behavior comparable with incandescent and halogen lamps (dim-to-warm)
- Changes the light color from 3000 K (warm white) to 1800 K (extra warm white) when dimming
- Creates particularly cosy atmospheres
- Easy lamp replacement
- Energy-saving
- Dimmable
- Variable color temperature 1800 K - 3000 K

Logistic

EAN / GTIN: 4026397362350

Weight: 0,60 kg

Length: 0.30 m

Width: 0.22 m

Heigth: 0.12 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- Easy installation
- Very high color rendering index (CRI)

Technical specifications:

Weight:	430 g
Energy efficiency class (A - G):	F

EUROLITE PAR-20 Spot silver

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 75 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable length:	Approx. 0,4 m
Base:	E27
Lamp type:	Selectable
Color generation:	Via color filter frame
Control:	Plug and play
Construction:	PAR-20
Housing color:	Silver
Attachment system:	Mounting bracket
Material:	Aluminum
Slot for spot length:	8,5 cm x 8,5 cm
Dimensions:	Width: 15 cm Depth: 18 cm Height: 11,2 cm Diameter: Ø 8 cm
Weight:	320 g
Mounting bracket	
Diameter mounting holes:	2 x Ø10mm
Material:	Aluminum, 3 mm
Filter frame	
Material:	Aluminum
Dimensions:	Length: 8,4 cm Width: 8,4 cm Diameter: Ø 6,1 cm

OMNILUX PAR-20 230V COB 6W E-27 LED 1800k-3000k dim2warm

Operating voltage:	230 V, 220 - 240 V
Nominal wattage:	6 W
Base:	E27

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Lamp specification:	Dimmable
Beam angle:	24°
Color of light:	White
Color temperature:	1800K - 3000K adjustable
Setup:	Easy installation
Color rendering index (CRI):	95 Ra
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Lamp life:	15000 h
Luminous flux:	480 lm
Wavelength:	640 nm
Material:	Aluminum casting
Color:	Black
Weight:	110 g
Energy efficiency class (A - G):	F

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.