



Features:

EUROLITE PAR-30 Spot black

PAR-30 housing with E27 socket (with plug + cable)

- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Strong clamps with extension springs for safe hold and for quick opening of the rear housing cover
- Blackened tube for precise light output
- Suitable for different spot angles
- Small lighting-systems can also be realized with a small budget
- Control via plug and play
- With mounting bracket
- For PAR 30
- For application areas such as: Clubs/dancing school; decoration; Trade fair and shop fitting; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation

OMNILUX PAR-30 230V COB 12W E-27 LED 1800k-3000k dim2warm

PAR-30 LED lamp with modern dim-to-warm feature

- Dimming behavior comparable with incandescent and halogen lamps (dim-to-warm)
- Changes the light color from 3000 K (warm white) to 1800 K (extra warm white) when dimming
- Creates particularly cosy atmospheres
- Easy lamp replacement
- Energy-saving
- Dimmable
- Easy installation

Logistic

EAN / GTIN: 4026397366600

Weight: 7,00 kg

Length: 0.61 m

Width: 0.31 m

Height: 0.42 m

- Variable color temperature 1800 K - 3000 K
- Very high color rendering index (CRI)

EUROLITE EDX-4 DMX RDM LED Dimmer Pack

4-channel dimmer for LED lights with 230 V operation

- Trailing edge dimmer with 4 channels
- Max. channel load 200 watts
- Independent DMX addressing per channel possible
- Dimmer or switch operation
- 4 channel faders for control on the device
- Note: Only suitable for LED - not for conventional light bulbs
- 16 integrated show programs
- Control via RDM; stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- With rigging points
- LCD display
- For application areas such as: Trade fair and shop fitting; theater; rental; video and photography; restaurants, bars and hotels
- Silent operation
- Application possibility: Wall mounting

Technical specifications:

Weight:	5.20 kg
---------	---------

Energy efficiency class (A - G):	F
----------------------------------	---

EUROLITE PAR-30 Spot black

Power supply:	230 V AC, 50 Hz
---------------	-----------------

Power consumption:	Max. 100 W
--------------------	------------

IP classification:	IP20
--------------------	------

Protection class:	Protection class I
-------------------	--------------------

Suitable lamp:	Max. 230 V/100 W E27
----------------	----------------------

Power connection:	Fixed power supply cord with safety plug
-------------------	--

Cable construction:	3 x 0.75 mm² H05SS-F
---------------------	----------------------

Cable length:	Approx. 0.4 m
---------------	---------------

Base:	E27
-------	-----

Lamp type:	Selectable
------------	------------

Color generation:	Via color filter frame
-------------------	------------------------

Control:	Plug and play
----------	---------------

Construction:	PAR-30
---------------	--------

Housing color:	Black matte
----------------	-------------

Attachment system:	Mounting bracket
--------------------	------------------

Material:	Aluminum
-----------	----------

Slot for spot length:	12.8 cm x 12.8 cm
-----------------------	-------------------

Dimensions:	Length: 23.5 cm
	Width: 14.5 cm
	Height: 21 cm

Weight:	0.53 kg
Noise classification:	Class 0 (no noise at all)
Diameter mounting holes:	2 x Ø10mm
Material:	Aluminum, 3 mm
Color:	Black, matte
Shape:	Octagonal
Material:	Aluminum, 0.5 mm
Color:	Black, matte
Dimensions:	Length: 12.6 cm Width: 12.6 cm Diameter: Ø 9.4 cm
Weight:	0.022 kg

OMNILUX PAR-30 230V COB 12W E-27 LED 1800k-3000k dim2warm

Operating voltage:	230
Nominal wattage:	12 W
Base:	E27
Lamp type:	LED lamp; reflector lamp
Lamp specification:	Dimmable
Beam angle:	24°
Setup:	Easy installation
Color of light:	White
Color temperature:	1800K - 3000K adjustable
Color rendering index (CRI):	96 Ra
Construction:	PAR-30
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Lamp life:	15000 h
Luminous flux:	960 lm
Wavelength:	640 nm
Weight:	0.14 kg
Photobiological safety:	Risk Group 1
Energy efficiency class (A - G):	F
EPREL-Nr:	963473

EUROLITE EDX-4 DMX RDM LED Dimmer Pack

Power supply:	230 V AC, 50 Hz
Output power:	Max. 200 W Max. 800 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	4 x safety contact (F), hinged lid mounting version fused 1 x P-Con (gray), mounting version Bypass

Device fuse:	5 x 20 mm, F 6 A fuse replaceable
Power output fuse per channel:	5 x 20 mm, T 1 A fuse replaceable
DMX channels:	1; 4; 6
DMX input:	3-pin XLR (M)
DMX output:	3-pin XLR (F)
Control:	RDM; stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Control channels:	4
Flying points:	2 x M10 thread
Display type:	LCD display
Status LED:	Channel level meter
Color:	Black
Dimensions:	Width: 21 cm Depth: 29 cm Height: 9 cm
Weight:	2.53 kg
Noise classification:	Class 0 (no noise at all)

Scope of delivery:

4 x EUROLITE PAR-30 Spot black

1 x spotlight
1 x filter frame
1 x user manual

1 x EUROLITE EDX-4 DMX RDM LED Dimmer Pack

1 x device
1 x user manual
1 x power cord