

OMNITRONIC Set WMT-2M UHF Transmitter + WMR-2M UHF Receiver

UHF Transmitter including UHF Receiver

Art. No.: 20000698

GTIN: 4026397177954





The article is no longer in our assortment.

Features:

OMNITRONIC WMT-2M UHF Transmitter, mono

Wireless mono audio transmission system, 823-832 MHz + 863-865 MHz

- Wireless audio transmission system with UHF PLL technology
- For wireless transmission of audio line and microphone signals with one transmitter and one or more receivers
- Compatible with wireless modules and microphones of the MOM and DAD series
- 16 channels selectable
- Supports operation and simultaneous charging
- Robust metal fixing clip
- WM-2M camera tripod optional
- Up to 4 transmitters can be operated in parallel without interference

transmitter

- UHF 863 865 MHz License-free and approved in Europe
- UHF 823 832 MHz License-free and approved in large parts of Europe
- Operating range up to 50m
- Battery pack tool-free replacement
- Integrated automatic charging of the battery and status indicator
- Powered by a battery/battery pack

Package contents

- 1 x transmitter, 1 x microphone, 1 x uSB cable, 1 x jack cable, 1 x adapter, 1 x user manual, 1 x declaration of conformity

OMNITRONIC WMR-2M UHF Receiver, mono

Wireless mono audio transmission system, 823-832 MHz + 863-865 MHz

Logistic

EAN / GTIN: 4026397177954

Weight: 0,50 kg Length: 0.30 m Width: 0.22 m Heigth: 0.21 m

- Wireless audio transmission system with UHF PLL technology
- For wireless transmission of audio line and microphone signals with one transmitter and one or more receivers
- Compatible with wireless modules and microphones of the MOM and DAD series
- 16 channels selectable
- Audio line output and earphone connection via 3.5 mm jack
- Supports operation and simultaneous charging
- Robust metal fixing clip
- WM-2M camera tripod optional
- UHF 823 832 MHz License-free and approved in large parts of Europe
- UHF 863 865 MHz License-free and approved in Europe
- Operating range up to 50m
- Battery pack tool-free replacement
- Integrated automatic charging of the battery and status indicator
- Powered by a battery/battery pack
- Up to 4 transmitters can be operated in parallel without interference

Package contents

- 1 x receiver, 1 x jack cable, 1 x uSB cable, 1 x adapter, 1 x user manual, 1 x declaration of conformity

Technical specifications: Weight: 290 g

OMNITRONIC WMT-2M UHF Transmitter, mono

Type:	Bodypack with microphone
Parallel mode:	Max. 4 transmitter
Control elements:	Level control
Weight:	150 g
Transmitter	
Type:	Pocket transmitter
Power supply:	Or 5 V DC 3 V DC
Power connection:	Mains input via micro USB (F) mounting version power supply cord for USB A mains connection (provided)
	Battery/battery pack
Battery:	2 x Mignon (AA) (not included)
S/N ratio:	>90 dB
Range:	Range up to 50m
Frequency band:	UHF 863 - 865 MHz; UHF 823 - 832 MHz
Frequency stability:	± 0,01 %
RF power output:	10 mW
Modulation:	FM
Frequency selection:	Switchable frequencies
Pilot frequency:	32,768 khz
Connections:	Input: Microphone via 1 x Mini XLR (M) 3-pin mounting version

	Input: line via 1 x 3.5 mm jack (stereo) mounting version
Switch:	On/off switch
Material:	Plastic
Color:	Black
Dimensions:	Width: 6,7 cm Depth: 3,0 cm Height: 11,2 cm
Weight:	80 g
Microphone	
Type:	Lavalier microphone
Power connection:	Via Mini XLR (F) 3-pin
Capsule type:	Condenser

OMNITRONIC WMR-2M UHF Receiver, mono

Type:	Audio transmission
Power supply:	3 V DC Or 5 V DC
Power connection:	Battery/battery pack Mains input via micro USB (F) mounting version power supply cord for USB A mains connection (provided)
Battery:	2 x Mignon (AA) (not included)
S/N ratio:	>80 dB
Range:	Range up to 50m
Frequency band:	UHF 823 - 832 MHz; UHF 863 - 865 MHz
Frequency stability:	± 0,01 %
Parallel mode:	Max. 4 transmitter
Modulation:	FM
Frequency selection:	16 Switchable frequencies
Pilot frequency:	32,768 khz
Control elements:	, frequency selector switch, level control
Status LED:	Power, signal
Connections:	Output: line via 1 x 3.5 mm jack (mono) mounting version 0,75 V
	Output: headphones via 1 x 3.5 mm jack (mono) mounting version 1 V
Switch:	On/off switch
Material:	Plastic
Color:	Black
Dimensions:	Width: 6,7 cm
	Depth: 3,0 cm
	Height: 11,2 cm
Weight:	130 g
Receiver	
Weight:	80 g