

EUROLITE Set LED KLS-3002 + STV-40S-WOT Steel stand

Bar with 4 powerful RGBAW/UV spots, QuickDMX, remote control and bag incl. steel stand

Art. No.: 20000719

GTIN: 4026397304305



List price: 724.71 €

incl. 19% VAT.

Features:

EUROLITE LED KLS-3002 Next Compact Light Set

Bar with 4 powerful RGBAW/UV spots, QuickDMX support, IR remote control and carrying bag

- DMX light set with four slim-line LED spots
- 7 high-power 10 W RGBAW/UVLEDs (6in1) per spot
- effect solid and pastel colors and stunning blacklight effects thanks to RGBAW/UV color mixing
- Color and brightness individually adjustable for each spot directly at the control unit
- Brand-new software design with smart programs
- Ultra-light ideally suited for mobile use
- Crossbar with integrated DMX control unit and TV spigot for tripod installation
- Quick truss installation via quick-lock omega holders
- Spots movable and tiltable, and with 19° beam angle
- Comes pre-assembled with practical transport bag
- Convenient control via included IR remote control or optional wireless foot switch
- Auto, music, color, master/slave, and DMX mode
- 20 built-in auto and music show programs
- Direct color selection for 21 preset colors
- Addressing and setting via control panel with 4-digit LED display
- Supports QuickDMX - the wireless DMX system by Eurolite
- Built-in phantom-powered USB port for QuickDMX receivers (accessories)
- Mounting points and power outlets for additional fixtures
- P-Con terminals for power linking up to 8 units
- LED: Spot 7 x high-power 10 W 6in1 HCL RGBWA/UV (homogenous color mix)
- Can be operated in 2; 4; 6; 10; 24; 28 CH mode
- The device is cooled by passive convection
- Controlling by Stand-alone; DMX; Wireless footswitch (optional); QuickDMX via USB (optional); IR remote control; Sound to light via Microphone

Logistic

EAN / GTIN: 4026397304305

Weight: 22,00 kg

Length: 1.35 m

Width: 0.21 m

Height: 0.58 m

Bulky product

- Is in EASY SHOW; Light J Software; EUROLITE LED PC-Control 512 software; LED EASY OPERATOR DELUXE already preprogrammed
- For application areas such as: Small lender; Lender; Wedding/gala

EUROLITE STV-40S-WOT Steel Stand

Steel lighting stand without crossbar, max. load 18 kg, max. height 340 cm

- Stable lighting stand for mobile use
- The telescopic tube is additionally fixed with a safety pin
- With mounting hole (d=28mm) for tv-pin

Technical specifications:

Weight: 19,34 kg

EUROLITE LED KLS-3002 Next Compact Light Set

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	225 W
IP classification:	IP20
Power connection:	Mains input P-Con (blue), mounting version Power supply cord with safety plug (provided)
Cable construction:	3 x 1,0 mm ² H05VV-F
Cable length:	3 m
Power output:	2 x IEC connector (F) mounting version fused 1 x P-Con (gray), mounting version Bypass
Device fuse:	5 x 20 mm, T 2,5 A Fuse replaceable
Power output fuse per channel:	5 x 20 mm, T 5 A Fuse replaceable
Lamp type:	LED lamp
LED:	Spot 7 x high-power 10 W 6in1 HCL RGBWA/UV (homogenous color mix)
DMX channels:	2; 4; 6; 10; 24; 28
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection
Control:	Stand-alone; DMX; Wireless footswitch (optional); QuickDMX via USB (optional); IR remote control; Sound to light via Microphone; EASY SHOW; Light J Software; EUROLITE LED PC-Control 512 software; LED EASY OPERATOR DELUXE
Beam angle:	19°
Beam angle (1/2 peak):	19°
Beam angle (1/10 peak):	35°
Housing color:	Black
Attachment system:	TV spigot Ø 28mm
Dimensions:	Width: 1,28 m Depth: 8 cm Height: 29 cm

Weight:	11,14 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese
Legal specifications	
Special product:	Not designed for household room illumination
intended use:	show effect lighting

EUROLITE STV-40S-WOT Steel Stand

Maximum carrying capacity:	18 kg
Height:	Maximum: 340 cm above 2 sections Minimum: 150 cm
Attachment system:	TV spigot Ø 28mm
Construction by:	DIN 15560-27, DIN EN ISO 12100-2
Type (general stands):	Light stand/manual
Color:	Black
Transport dimensions:	1,59 m x 18 cm x 15 cm
Base area:	Ø 1,2 m
Weight:	8,20 kg