eurolite®

EUROLITE Set 4x AKKU Bar-6 QCL + Flightcase with charging function Art. No.: 20000722

4x Battery-powered LED bar with 4in1 LEDs and remote control incl. PRO flightcase with charging function 9TIN: 4026397168273







List price: 1783.81 €

incl. 19% VAT.

Features:

EUROLITE AKKU Bar-6 QCL

Battery-powered LED bar with 4in1 LEDs and IR remote control

- Additional frost filter provides a wide, soft and homogeneous light
- 6 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
 LEDs controlled separately
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- Integrated show programs
- Direct color selection for 35 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; master/slave function; sound to light via microphone; IR remote control; W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional)
- Flicker-free
- With a beam angle of 8°
- With double bracket
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; small rental
- Mains input and output for power linking up to 8 units
- Cordless, flexible and versatile
- Integrated automatic charging of the battery and status indicator
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light´J; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Silent operation

Logistic

EAN / GTIN: 4026397168273

- Application possibility: Standing; suspended; on stand Package contents
- 1 x bar, 1 x user manual, 1 x power cord, 1 x frost filter, 1 x remote control, 1 x battery

ROADINGER Flightcase 4x AKKU BAR-6 QCL with charging function

Trunk case with castors

- With accessory compartment
- With 4 device compartments
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function
- 4 castors with 2 locking brakes
- 4 built-in stacking trays in the cover
- Package contents
- 1 x case, 1 x user manual, 1 x power cord

Technical specifications:

Weight:

34,35 kg

EUROLITE AKKU Bar-6 QCL

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Battery/battery pack
	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Battery pack type:	1 x lithium ion 11,1 V, 10400 mAh, 115,44 Wh
Lamp type:	LED lamp
LED type:	6 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
DMX channels:	4; 6; 8; 11; 12; 13; 17; 24; 29
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; master/slave function; sound to light via microphone; IR remote control; W- DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional)
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle:	8°

Beam angle (1/10 peak): 17° Housing color: Black Attachment system: Double bracket Dimensions: Length: 50,2 cm Depth: 6 cm Height: 20,1 cm Weight: 3,80 kg Noise classification: Class 0 (no noise at all) Remote control 1 x button cell 3.0 V CR2032 lithium manganese built-in Legal specifications Special product: Not designed for household room illumination Not designed for household room illumination	Beam angle (1/2 peak):	8°
Attachment system: Double bracket Dimensions: Length: 50,2 cm Depth: 6 cm Height: 20,1 cm Weight: 3,80 kg Noise classification: Class 0 (no noise at all) Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Legal specifications Special product: Not designed for household room illumination	Beam angle (1/10 peak):	17°
Dimensions: Length: 50,2 cm Depth: 6 cm Height: 20,1 cm Weight: 3,80 kg Noise classification: Class 0 (no noise at all) Remote control 1 x button cell 3.0 V CR2032 lithium manganese built-in Legal specifications Special product:	Housing color:	Black
Depth: 6 cm Height: 20,1 cm Weight: 3,80 kg Noise classification: Class 0 (no noise at all) Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Legal specifications Special product: Not designed for household room illumination	Attachment system:	Double bracket
Height: 20,1 cm Weight: 3,80 kg Noise classification: Class 0 (no noise at all) Remote control In x button cell 3.0 V CR2032 lithium manganese built-in Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Legal specifications Special product:	Dimensions:	Length: 50,2 cm
Weight: 3,80 kg Noise classification: Class 0 (no noise at all) Remote control Battery: Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Legal specifications Special product:		Depth: 6 cm
Noise classification: Class 0 (no noise at all) Remote control Image: Second control co		Height: 20,1 cm
Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Legal specifications Special product: Not designed for household room illumination	Weight:	3,80 kg
Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Legal specifications Special product: Not designed for household room illumination	Noise classification:	Class 0 (no noise at all)
built-in Legal specifications Special product: Not designed for household room illumination	Remote control	
Special product: Not designed for household room illumination	Battery:	5
	Legal specifications	
Intended use: Show effect lighting	Special product:	Not designed for household room illumination
	Intended use:	Show effect lighting

ROADINGER Flightcase 4x AKKU BAR-6 QCL with charging function

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	Max. 1150 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable length:	1,20 m
Device fuse:	5 x 20 mm, F 5 A fuse replaceable
Aluminum profile frames:	25 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs with shut-off function
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Material:	Birch multiplex
Color:	Black, laminated
Device compartment:	17 cm x 50,5 cm x 18 cm
Accessory compartment:	9 cm x 50,5 cm x 18 cm
Dimensions:	Width: 98 cm
	Depth: 56 cm
	Height: 35 cm
Weight:	19,15 kg