# FUTURELIGHT Set 4x PLB-130 + Case

4x High-power beam with OSRAM SIRIUS HRI 132 W lamp including PRO flightcase

**Art. No.: 20000725**

GTIN: 4026397607680

## The article is no longer in our assortment.

### Features:

**FUTURELIGHT PLB-130 Moving Head**

High performance beam with Osram Sirius HRI 132 W lamp

- Parallel beam
- Effect wheel with rotating 8-facet prism
- The prism rotate in both directions and at different speeds
- Motorized focus
- Strobe effect with adjustable speed
- Random strobe effect
- Electronic dimmer (0-100%)
- Exact positioning via 16-bit PAN/TILT movement resolution
- Automatic position correction
- Control panel with LC display for easy configuration
- PAN angle switchable between 630° and 540°
- Stand-alone, master/slave and DMX mode
- Number of scenes in Program Run can be changed individually
- The scenes in Program Run can be modified via the Control Board or via an external controller and loaded into the memory
- Software upload by optional accessories via DMX link
- With Osram Sirius HRI 132 W lamp
- Gobos
- Gobo effect
- Color wheel with 14 dichroic filters plus open<BR>Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 17 gobos and open<BR>shake effect
- The device is cooled by temperature-controlled fan
- Control via RDM; DMX; stand-alone; Sound to light via Microphone

### Logistic

EAN / GTIN: 4026397607680

Weight: 80,00 kg

Length: 1.20 m

Width: 0.80 m

Heigth: 1.00 m

Bulky product

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- Preprogrammed in LED PC-Control 512; Light Captain; Light´J
- With a beam angle of 2°

**Package contents**

- 1 x moving light, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x xLR cable

**ROADINGER Flightcase 4x PLB-130/DMH-80/TMH XB-130**

PRO flightcase for 4 x PLB-130

- With 4 Device compartments
- With accessory compartment
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding<BR>cover with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

| | |
|---|---|
| Weight: | 69,40 kg |

**FUTURELIGHT PLB-130 Moving Head**

| | |
|---|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 190 W |
| IP classification: | IP20 |
| Power connection: | Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x PowerCON (gray), mounting version |
| Fuse: | T 3,15 A Fuse replaceable |
| Lamp type: | Discharge lamp |
| Max. TILT movement: | 265° Positioning |
| Max. PAN movement: | 630° Positioning |
| Flash rate: | 1 - 20 Hz |
| Equipment: | Gobos |
| Color generation: | Color wheel with 14 dichroic filters plus open<br>Rainbow effect with adjustable speed in both directions |
| Gobos: | Gobo wheel with static gobos, 17 gobos and open<br>Shake effect |
| DMX channels: | 10; 12; 13; 16 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Temperature-controlled fan |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| | |
|---|---|
| Control: | RDM; DMX; stand-alone; Sound to light via Microphone |
| Preprogrammed in: | LED PC-Control 512; Light Captain; Light´J |
| Beam angle: | 2° |
| Beam angle (1/2 peak): | 2° |
| Housing color: | Black |
| Dimensions: | Width: 25 cm<br>Depth: 30 cm<br>Height: 40 cm |
| Weight: | 11,70 kg |
| Noise classification: | Class 3 (clearly perceptible sounds) |
| Legal specifications | |
| Energy efficiency class (A++ - E): | G |

**ROADINGER Flightcase 4x PLB-130/DMH-80/TMH XB-130**

| | |
|---|---|
| Maximum load: | 100 kg |
| Aluminum profile frames: | 25 mm |
| Case handle: | 4 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |
| Transport aid: | 4 x castors with 2 locking brakes |
| Use of brands: | Branded hardware |
| Material: | Birch multiplex, 7 mm |
| Color: | Dark brown, laminated |
| Accessory compartment: | 10 cm x 45 cm x 38,5 cm |
| Inside dimensions: | 77 cm x 45 cm x 40,5 cm |
| Device compartment: | 31,5 cm x 21,5 cm x 38,5 cm |
| Dimensions: | Width: 81 cm<br>Depth: 50 cm<br>Height: 43 cm |
| Weight: | 22,60 kg |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.