

EUROLITE Set LED KLS-180 white + BS-2 EU Loudspeakerstand white

Art. No.: 20000726

White bar with 4 RGBW spots and 4 white strobe LEDs with QuickDMX connector incl. speaker stand

GTIN: 4026397455564



List price: 339.15 €

incl. 19% VAT.

Features:

EUROLITE LED KLS-180 Compact Light Set wh

Bar with 4 RGBW spots and 4 white strobe LEDs, with QuickDMX connector (XLR)

- Crossbar with integrated DMX control unit and stand sleeve
- Ultra-light ideally suited for mobile use
- Ideal for bands, stages or solo entertainers
- Suited for installation on a speaker stand (not included) or truss
- Comes pre-assembled with practical transport bag
- 4 powerful 4in1 LEDs per spot provide for an exquisite RGBW color mix
- Strobe effect with 4 white 1 W LEDs
- Movable and tiltable spotlights
- Via DMX, each spot can be individually controlled
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Supports QuickDMX - the wireless DMX-system from Eurolite
- Built-in phantom fed socket for QuickDMX receiver (see accessories)
- Functions: RGBW color mixture, color presets, built-in programs, strobe effects with variable speed, dimmer, Master/Slave operation
- Addressing and setting via control panel with 4-digit LED display
- Additional controlling possibility via the EUROLITE IR-7 remote control, included in delivery
- White lacquered metal version with movable mounting bracket
- IEC terminals for power linking up to 8 units
- LED: Spot separate controlling 4 x high-power 8 W 4in1 QCL RGBW (homogenous color mix)
- LED: Strobe effect 4 x high-power 1 W CW
- Can be operated in 3; 4; 8; 21 CH mode
- The device is cooled by passive convection
- Controlling by IR remote control (provided); Stand-alone; DMX; Sound to light via Microphone; QuickDMX via USB (optional)

Logistic

EAN / GTIN: 4026397455564

Weight: 10,75 kg

Length: 1.20 m

Width: 0.60 m

Height: 0.20 m

- Is in EASY SHOW; EUROLITE LED PC-Control 512 software already preprogrammed
- Flicker-free projection
- For application areas such as: Wedding/gala

OMNITRONIC BS-2 EU Loudspeaker Stand white

High steel speaker stand, height adjustable 117-205 cm, maximum load 50 kg

- Stable steel version
- Height adjustable, with locking pin
- Height: 117-205 cm
- Tube diameter: Ø 35 mm
- Centric load: 50 kg
- Scratch-resistant white finish
- Made in Europe

Technical specifications:

Weight: 9,60 kg

EUROLITE LED KLS-180 Compact Light Set wh

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	80 W
IP classification:	IP20
Power connection:	Mains input IEC connector (M) mounting version Power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Fuse:	T 1 A
Lamp type:	LED lamp
LED:	Spot 4 x high-power 8 W 4in1 QCL RGBW (homogenous color mix) Strobe effect 4 x high-power 1 W CW
Flash rate:	1 - 20 Hz
DMX channels:	3; 4; 8; 21
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection
Control:	IR remote control (provided); Stand-alone; DMX; Sound to light via Microphone; QuickDMX via USB (optional); EASY SHOW; EUROLITE LED PC-Control 512 software
Beam angle:	9°
Beam angle (1/2 peak):	9°
Housing color:	White
Dimensions:	Width: 60,5 cm Depth: 14 cm Height: 23 cm
Weight:	5,10 kg
Noise classification:	Class 0 (no noise at all)

Remote control

Battery: 1 x Button cell 3.0 V CR2025 lithium manganese built-in

Legal specifications

Special product: Not designed for household room illumination

intended use: show effect lighting

OMNITRONIC BS-2 EU Loudspeaker Stand white

Maximum carrying capacity: 50 kg

Height: Maximum: 205 cm
Minimum: 117 cm

Attachment system: Ø 35mm

Type (general stands): Speaker stand/manual

Material: Steel

Color: White

Transport dimensions: 1,1 m x 17 cm x 14 cm

Weight: 4,50 kg
