

EUROLITE Set LED Color Curtain + BS-2 EU Loudspeaker stand white

White LED curtain with 4 RGBW LEDs and QuickDMX incl. speaker stand and 2x stand sleeve

Art. No.: 20000736

GTIN: 4026397616651



List price: 374.85 €

incl. 19% VAT.

Features:

EUROLITE LED Color Curtain

White LED curtain with 4 high-power RGBW LEDs and QuickDMX support

- Elegant white design
- Cutout for cable inlet
- 4 powerful LEDs 4in1 QCL RGB/WW
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Integrated show programs
- Direct color selection for 15 preset colors
- Control via DMX; Sound to light via Microphone; Master/slave function; stand-alone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- 3 digit 7-segment LED display
- Preprogrammed in EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; Light Captain; Light'J
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Wedding/gala/events; Installation; restaurants, bars and hotels
- Silent operation
- Application possibility: On stand; suspended

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x textile cover

OMNITRONIC BS-2 EU Loudspeaker Stand white

High steel speaker stand, height adjustable 117-205 cm, maximum load 50 kg

Logistic

EAN / GTIN: 4026397616651

Weight: 12,00 kg Length: 1.20 m Width: 0.60 m Heigth: 0.60 m Bulky product

- Height adjustable, with locking pin
- Tube diameter: Ø 35 mm
- Adjustable height
- Scratchproof and shockproof
- Made in Europe

OMNITRONIC BOB-4 Stand Adaptor white 2x

Adapter with stand sleeve for 35 mm tube, M8 threadPackage contents

- 2 x holder

Technical specifications:

Weight: 9,48 kg

EUROLITE LED Color Curtain

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	25 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version
Power output:	1 x P-Con (gray), mounting version
Lamp type:	LED lamp
LED:	4 x 4in1 QCL RGB/WW
Flash rate:	0 - 20 Hz
DMX channels:	4; 8
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; Sound to light via Microphone; Master/slave function; stand-alone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; Light Captain; Light'J
Housing color:	White
Display type:	3 digit 7-segment LED display
Dimensions:	Height: 1,3 m Diameter: Ø 40 cm
Weight:	4,60 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OMNITRONIC BS-2 EU Loudspeaker Stand white

Maximum carrying capacity:	50 kg
Height:	Maximum: 205 cm
	Minimum: 117 cm
Attachment system:	Ø 35mm
Type (general stands):	Speaker stand/manual
Material:	Steel
Color:	White, painted; , scratchproof and shockproof
Transport dimensions:	1,1 m x 17 cm x 14 cm
Weight:	4,50 kg

OMNITRONIC BOB-4 Stand Adaptor white 2x

Maximum carrying capacity:	30 kg
Type (general stands):	Accessory
Material:	Metal
Color:	White
Weight:	380 g