

OMNITRONIC PAS MK3 Party Set

Subwoofer, 2x 2-Way Top, 2x Speaker Stand, Amplifier, PRO flightcase and 3x speaker cable

Art. No.: 2000744

GTIN: 4026397682366



List price: 2140.81 €

incl. 19% VAT.

Features:

OMNITRONIC PAS-151 MK3 Subwoofer

Passive 15" bassreflex subwoofer with 700 W RMS, 8 ohms

- Rugged Pro PA subwoofer
- 38 cm (15") bass speaker
- Parallel Speaker connections
- Rugged multiplex cabinet
- Scratch-resistant lacquer surface
- Metal handlebars
- Impact-resistant steel grille with acoustic foam
- Flange for mounting top speakers
- With Wheels optional

OMNITRONIC PAS-210 MK3 2-Way Top

Passive speaker with 10" woofer, 1" driver and 250 W RMS

- Rugged full-range top speaker, qualified for suspension
- Trapezoidal, multi-functional multiplex cabinet with scratch-resistant lacquer surface
- 2-way bass-reflex system with 25 cm woofer (8 cm voice coil)
- 2.5 cm compression driver with ferrite magnet (3.8 cm voice coil with polymer diaphragm)
- Parallel Speaker connections
- Optimized for combination with PAS subwoofers
- Dual flange with 0° and 5° tilt angle enables flexible positioning
- M8 threaded inserts for suspended installation
- Rugged multiplex cabinet with protective grille and handlebars
- Applications: standing, on a subwoofer or speaker stand, suspended

Logistic

EAN / GTIN: 4026397682366

Weight: 100,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 1.50 m

Bulky product

OMNITRONIC Speaker Stand MOVE MK2 set

2 speaker stands, extendible up to 185 cm, maximum load 30 kg + carrying bag

- Set consisting of 2 x speaker stand and carry bag
- Height adjustable, with locking pin
- Height: 100-185 cm
- Tube diameter: Ø 35 mm
- Scratch-resistant black finish

OMNITRONIC A-3603 Class-D 2.1 Amplifier

3-channel PA amplifier with crossover network - 4 ohms: 1 x 2000 W, 2 x 800 W

- 3-channel PA amplifier with class D circuitry and switch mode power supply
- Adjustable crossover frequency for satellites and subwoofer
- 2.1 operation or 3-channel operation selectable
- 3 level controls
- LED VU meter and LEDs for activated protective circuit (protect) and overload (clip) per channel
- Electronically balanced inputs via XLR mounting jacks, with XLR feed-through outputs
- Speaker outputs via lockable Speaker plugs
- Rugged steel chassis with aluminum front panel
- Rack installation, 2 U
- (19") 48.3 cm rack installation 2 U

ROADINGER Rack Profi 2U 45cm

PRO flightcase for 483 mm devices (19")

- High-quality workmanship with birch multiplex 9 mm, dark brown, laminated
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 4 high-quality butterfly locks
- With wooden slide rails on the bottom
- With profile rails suitable for (19") approx. 48 cm units
- 2 U
- Made in Europe

PSSO Speaker cable Speakon 2x2.5 5m bk

High-quality speaker cable

- With Neutrik plugs from Liechtenstein
- 2-pole speaker cable
- With Neutrik Speakon cable plugs
- Cable cross-section: 2.5 mm²
- Cable diameter: 8 mm
- NEUTRIK
- Made in Germany

Technical specifications:

Weight: 82,80 kg

OMNITRONIC PAS-151 MK3 Subwoofer

Rated power: 700 W RMS

Program power: 1400 W

Frequency range: 40 - 200 Hz

Sensitivity:	97 dB (1W/1m)
Max. SPL:	127 dB
Impedance:	8 ohms
Connections:	Input: speakers via 2 x speaker built-in socket (F)
Speakers:	1 x woofer (15") approx. 38 cm with ferrit magnet Basket material: aluminum Voice coil lows (4") approx. 10 cm
Type of speaker:	Subwoofer
Type:	Vented
Transport aid:	Wheels optional
Material:	Birch multiplex
Color:	Black, painted
Dimensions:	Width: 46 cm Depth: 56 cm Height: 52 cm
Weight:	31,25 kg

OMNITRONIC PAS-210 MK3 2-Way Top

Rated power:	250 W RMS
Program power:	500 W
Frequency range:	65 - 20000 Hz
Sensitivity:	96 dB (1W/1m)
Max. SPL:	123 dB
Dispersion angle:	90° x 60°
Crossover frequency:	3200 Hz
Impedance:	8 ohms
Attachment system:	Ø 35mm variable tilt
Flying points:	5 x M8 thread; 4 x M10 thread
Connections:	Input: speakers via 2 x speaker built-in socket (F)
Speakers:	1 x compression tweeter highs (1") approx. 2,5 cm with ferrit magnet Basket material: aluminum Voice coil compression tweeter highs (1.5") approx. 4 cm Horn vent (1") approx. 2,5 cm 1 x woofer (10") approx. 25 cm Voice coil lows (2.5") approx. 6.35 cm
Type of speaker:	Compact cabinet speaker
Material:	Birch multiplex
Color:	Black, painted
Dimensions:	Width: 32 cm Depth: 52,5 cm Height: 30 cm
Weight:	12,95 kg

OMNITRONIC Speaker Stand MOVE MK2 set

Maximum carrying capacity:	30 kg
Tube diameter sector:	35
Height:	Maximum: 185 cm Minimum: 100 cm
Attachment system:	Ø 35mm
Type (general stands):	Speaker stand/manual
Material:	Steel; Steel
Color:	Black
Weight:	5,10 kg

OMNITRONIC A-3603 Class-D 2.1 Amplifier

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	685 W 1/8 power
Output power:	2 x 400 W RMS (8 ohms) 1 x 1000 W RMS (8 ohms) 2 x 800 W RMS (4 ohms) 1 x 2000 W RMS (4 ohms)
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Frequency range:	20 - 20000 Hz
S/N ratio:	>100 dB
THD:	<0,003 % at 1 kHz
Impedance:	Input 20 kOhm , bal. Input 10 kOhm , unbal.
Gain:	Chanal 1 26 dB Chanal 2 26 dB Chanal 3 32 dB
Circuitry:	Class D
Slew rate:	>10 V/µs
Damping factor:	>500
Control elements:	Power switch, level control per channel, mode switch (2/3 channels), crossover frequency
Status LED:	Protect, clip, level meter, bridged
Connections:	Input: line via 3 x 3-pin XLR Link: line via 3 x 3-pin XLR Output: speakers via 3 x speaker built-in socket (F)
Housing design:	(19") 48.3 cm rack installation 2 U
Dimensions:	Width: 48,3 cm Depth: 41 cm Height: 8,9 cm
Weight:	9,10 kg

ROADINGER Rack Profi 2U 45cm

Maximum load:	50 kg
Aluminum profile frames:	30 mm

Case handles:	2 pc/pcs
Lock:	Butterfly lock: 4 pc/pcs
Transport aid:	Wooden slide rails on the bottom
Material:	Birch multiplex, 9 mm
Color:	Dark brown, laminated
Front panel width:	(19") approx. 48 cm
Mounting height:	Approx. 9 cm (2 U)
Mounting depth:	450 mm
Housing design:	2 U
Dimensions:	Width: 55,5 cm Depth: 59,5 cm Height: 17 cm
Weight:	9,80 kg

PSSO Speaker cable Speakon 2x2.5 5m bk

Cable construction:	2 x 2,5 mm ² Loudspeaker cable
Cable length:	5 m
Plug A:	1 x 2-pin SpeakON (M)
Plug B:	1 x 2-pin SpeakON (M)
Use of brands:	NEUTRIK
Color:	Black
Weight:	550 g