

**OMNITRONIC Set MOLLY-12A Subwoofer active + 4x MOLLY-6 Top 8 Ohm, black** 20000757

Active 12" subwoofer with DSP and Bluetooth incl. 4x 6.5" satellite speakers with bracket

GTIN: 4026397684384

**List price: 969.85 €**

incl. 19% VAT.

**Features:****OMNITRONIC MOLLY-12A Subwoofer active black**

Active 12" subwoofer with DSP and Bluetooth

- 12" bassreflex subwoofer with DSP and 700 watts RMS power
- Flexibly extendable with MOLLY-6 satellites for 2.1 and 4.1 configurations
- DSP-controlled class D amplifier (500 W + 2 x 100 W)
- Integrated Bluetooth audio streaming
- 4 EQ presets with indicators
- Signal limiter and crossover
- Signal inputs via combo jacks (XLR/6.3 mm jack), RCA and 3.5 mm jack
- XLR outputs for linking further MOLLY systems or active systems
- Separate volume controls for subwoofer and satellites L/R
- Stereo/mono selection
- Phase reversal switch
- Fault, limit, signal and power indicators
- M20 metal flange for mounting top speakers
- Multiplex enclosure with scratch-resistant lacquer surface and steel grille
- Built-in handles and low weight for ease of transport
- Digital signal processor
- Controlling by Bluetooth
- For application areas such as: Mobile djs/entertainer; Trade fair and shop fitting; Installation; home entertainment; restaurants, bars and hotels; product presentations and lectures

**Package contents**

- 1 x User manual, 1 x Power cord, 1 x Declaration of conformity, 1 x Bass, 2 x Speaker cable

**Logistic**

EAN / GTIN: 4026397684384

Weight: 41,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.50 m

Bulky product

## OMNITRONIC MOLLY-6 Top black 2x

6.5" satellite speakers with bracket

- 8-ohm speaker pair with 6.5" woofer and 1" tweeter
- For use with MOLLY-12A subwoofers for 2.1 and 4.1 configurations
- Optional stand adaptor required for stand mounting
- Extension U-bracket and cable available for connecting 2 satellite speakers
- Rated power: 130 W RMS/260 W program
- Connectors: 1 x speaker and screw plug terminal
- Scratch-resistant lacquer surface and steel grille
- With Mounting bracket

### Package contents

- 2 x Top, 2 x Mounting bracket, 4 x Knurled screw, 2 x Screw terminal

## Technical specifications:

---

Weight: 39,90 kg

---

## OMNITRONIC MOLLY-12A Subwoofer active black

Power supply:	230 V AC, 50 Hz
Power consumption:	1000 W
Output power:	1 x 500 W RMS 2 x 100 W RMS (8 ohms) 2 x 200 W RMS (4 ohms)
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Frequency range:	40 - 160 Hz
Sensitivity:	103 dB
Max. SPL:	128 dB
DSP:	Digital signal processor
Control:	Bluetooth
Attachment system:	M20 thread
Circuitry:	Class D
Controls:	Softstart; short-circuit; limiter; Overvoltage; overheat
Connections:	Input: line via 2 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Input: line via 1 x 3.5 mm jack (stereo) mounting version Input: line via 1 x stereo RCA Output: line via 2 x 3-pin XLR Output: Top via 2 x speaker built-in socket (F)
Input channels:	1 x stereo via Combination socket or RCA or Bluetooth, channel control via Rotary dial
Speaker:	1 x woofer (12") approx. 30 cm Voice coil lows (3") approx. 8 cm
Type of speaker:	Subwoofer

Type:	Vented
Color:	Black, painted
Dimensions:	Width: 47 cm Depth: 57 cm Height: 40 cm
Weight:	22,10 kg

#### **OMNITRONIC MOLLY-6 Top black 2x**

Rated power:	130 W RMS
Program power:	260 W
Frequency range:	150 - 20000 Hz
Sensitivity:	95 dB (1W/1m)
Max. SPL:	119 dB
Impedance:	8 ohms
Attachment system:	2x Mounting bracket
Flying points:	2 x M8 thread
Connections:	1 x speaker built-in socket (F) 1 x screw terminal
Speaker:	1 x woofer (6.5") approx. 17 cm Voice coil lows (1") approx. 2,5 cm 1 x Tweeter (1") approx. 2,5 cm
Type of speaker:	On-ceiling/on-wall speaker
Material:	MDF (Medium-density fibreboard)
Color:	Black
Weight:	8,90 kg