

EUROLITE Set 10x LED PT-100/32 Pixel DMX Tube + MADRIX Software + KEY. No.: 20000760

10x Pixel DMX Tube incl. MADRIX 5 start licence, MADRIX 5 Key and LED controller

GTIN: 4026397684476



The article is no longer in our assortment.

Features:

EUROLITE LED PT-100/32 Pixel DMX Tube

DMX controlled pixel tube with RGB color mixing

- DMX and power terminals intelligently designed for easy wiring
- 96 powerful LEDs SMD 5050 3in1 TCL RGB (homogenous color mix)
32 segments controlled separately
- Color change adjustable; Dimmer electronic
- Strobe effect
- Integrated show programs
- Direct color selection for 17 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; master/slave function
- Preprogrammed in LED PC-Control 512; Light Captain
- With a beam angle of 120°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Trade fair and shop fitting; stage; restaurants, bars and hotels
- Silent operation
- Application possibility: Suspended; wall mounting

Package contents

- 1 x light effect, 1 x user manual, 1 x power cord

MADRIX Software 5 License start

MADRIX 5 licence "start"

Logistic

EAN / GTIN: 4026397684476

Weight: 28,00 kg Length: 0.00 m Width: 0.00 m Heigth: 0.00 m

- Includes 1x MADRIX 5 License "start"
- Requires a valid, empty, and metallic MADRIX KEY
- Can transmit up to 1024 DMX channels
- Compatible with Win 7, Win 8, Win 10,
- Made in Germany
- Engineered in Germany
- For further information about this product, please refer to the Data Sheet under "Downloads"

MADRIX KEY

MADRIX 5 KEY - without license

- Includes an empty MADRIX KEY
- Requires a proper MADRIX 5 License to activate the features or output for the MADRIX 5 Software
- The device can be connected via USB to the PC
- Made in Germany

EUROLITE Art-Net/DMX Node 1

LED controller and Art-Net/DMX converter

- Compact LED controller for controlling RGB and RGBA/RGBW LEDs via Art-Net and DMX
- Converts standard DMX512 signals and Art-Net data to PWM signals for driving LEDs
- For use with the digital LED pixel strip (item 50530200)
- Applicable as standard Art-Net/DMX converter for 1 DMX512 universe (512 channels)
- DMX input and parallel DMX output for serial connection via XLR connectors
- Ethernet port: 2 x RJ45, 10/100 Mbps
- Stand-alone operation possible with 16 built-in light programs
- 2 x 8-digit LCD screen for menu settings
- Terminals for connecting the LEDs
- Powered via included PSU
- Rugged black metal housing

Technical specifications:

- Can transmit up to 512 DMX channels
- Control via Art-Net
- The device can be connected via RJ-45 (F) mounting version to the PC

Package contents

- 1 x device, 1 x external mains adapter, 1 x adapter cable, 1 x user manual

Weight: 22,00 kg

EUROLITE LED PT-100/32 Pixel DMX Tube

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	30 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	96 x SMD 5050 3in1 TCL RGB (homogenous color mix)
Flash rate:	0,25 - 11 Hz
DMX channels:	3; 5; 8; 48; 96
	·

3-pin XLR (M) mounting version
3-pin XLR (F) mounting version
Passive convection cooling
Stand-alone; DMX; sound to light via microphone; master/slave function
LED PC-Control 512; Light Captain
120°
120°
Black
Mounting bracket
4 digit 7-segment LED display
Length: 99,9 cm Width: 5,9 cm Height: 15,3 cm
2,10 kg
Class 0 (no noise at all)
Not designed for household room illumination
Show effect lighting

MADRIX Software 5 License start

DMX channels:	Output 1024
Weight:	0,00 kg
Operating system:	Win 7, Win 8, Win 10,

MADRIX KEY

Power connection:	Mains input via USB A (M) connectable version
USB port:	Туре А
PC connect:	Via USB
Weight:	0,07 kg

EUROLITE Art-Net/DMX Node 1

100-240 V AC, 50/60 Hz 5V DC 1000 mA
5 W
Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Screw plug-in terminal
Output 512
1 x 3-pin XLR (M) mounting version
1 x 3-pin XLR (F) mounting version

Network connection:	Protocol: Art-Net 3 via 2x RJ-45 (F) mounting version
Control:	Art-Net
PC connect:	Via RJ-45 (F) mounting version
Dimensions:	Width: 15,3 cm Depth: 9 cm Height: 3,7 cm
Weight:	0,47 kg