

## PSSO Set WISE ONE + BP + Headset 518-548MHz

License-free true diversity wireless receiver incl. pocket transmitter and headset microphone

Art. No.: 20000768

GTIN: 4026397685367



**List price: 629.51 €**

incl. 19% VAT.

### Features:

#### PSSO WISE ONE 1-Channel True Diversity Receiver 518-548MHz

License-free true diversity wireless receiver with 2.4GHz iSync control management

- Professional multifrequency wireless receiver with true diversity reception for stage use
- High-grade components and intelligent features ensure best performance and high reliability
- Ideal for large multi-channel systems (parallel operation possible up to 26 systems)
- 100 preset channels in 10 channel groups
- 2.4 GHz iSync - real-time synchronization and monitoring
- Automatic frequency setup
- Pilot frequency squelch technology delete wireless RF interference
- Multifunctional jogdial for menu settings
- Lock function for prevents undesired changes to settings
- Mic/line selector switch
- 2 detachable BNC antennas allow for use with external antenna divider
- 2 receivers can share a single power adapter
- Multicolor LCD display
- UHF 518 - 548 MHz License-free and approved in large parts of Europe
- Operating range up to 60m with line-of-sight
- Desktop console housing
- (19") 48.3 cm rack installation possible 1 U
- Firmware can be updated
- For application areas such as: Mobile use; Stage; theater; Rental; sports centres/gyms; concerts/FoH's

#### Package contents

- 1 x receiver, 1 x external mains adapter, 1 x adapter, 3 x antenna, 3 x mounting bracket, 9 x screw, 4 x foot, 1 x jack cable, 1 x adapter cable, 1 x holder, 1 x windshield, 1 x user manual, 1 x declaration of conformity, 2 x battery

### Logistic

EAN / GTIN: 4026397685367

Weight: 0,29 kg

Length: 0.40 m

Width: 0.33 m

Height: 0.27 m

### **PSSO WISE Bodypack 518-548MHz**

Bodypack transmitter with PLL multifrequency transmitter

- 2.4 GHz iSync - real-time synchronization and monitoring
- Editable user name and user color
- RF output switchable
- Gain level adjustable
- Lock function for prevents undesired changes to settings
- Operating range up to 60m with line-of-sight
- UHF 518 - 548 MHz License-free and approved in large parts of Europe
- Multicolor LCD display

#### **Package contents**

- 1 x transmitter, 2 x antenna, 1 x user manual, 1 x declaration of conformity

### **PSSO WISE Headset for Bodypack**

Headset microphone for WISE bodypack transmitter

- Polar pattern: Omnidirectional

#### **Package contents**

- 1 x microphone, 2 x windshield

### **Technical specifications:**

---

Weight: 2,01 kg

---

### **PSSO WISE ONE 1-Channel True Diversity Receiver 518-548MHz**

|                      |   |
|----------------------|---|
| Type:                | Receiver  |
| Power supply:        | 100-240 V AC, 50/60 Hz<br>12-15 V DC 800 mA   |
| Power consumption:   | 4 W   |
| Power connection:    | Mains input via Coaxial power connector (M)<br>mounting version power supply cord with AC<br>adapter (provided) |
| Number of channels:  | 1   |
| Frequency range:     | 50 - 20000 Hz   |
| S/N ratio:           | >96 dB  |
| THD:                 | <0,1 % at 1 kHz   |
| Gain:                | Microphone -32 dB to +4 dB<br>Output: -32 dB to +4 dB   |
| Range:               | Range up to 60m with line-of-sight  |
| Frequency band:      | UHF 518 - 548 MHz   |
| Diversity:           | True diversity  |
| Modulation:          | FM  |
| Frequency selection: | 100 Switchable frequencies<br>In 10 groups<br>Frequencies automatically scannable                               |
| Display type:        | Multicolor LCD display  |
| Control elements:    | Power switch, groundlift selector, menu, encoder  |

|                 |  |
|-----------------|--|
| Connections:    | Antenna via 2 x BNC (F) 12-15 V<br>Antenna via 1 x SMA (F) mounting version<br>Output: mic/line via 1 x 3-pin XLR<br>Output: mic/line via 1 x 6.3 mm jack socket (mono) mounting version |
| Channels:       | Microphon chanal: 1 x mono with Mic-line switch via XLR or jack  |
| Switch:         | Low cut switch   |
| Material:       | Metal  |
| Color:          | Black  |
| PC connect:     | , firmware can be updated  |
| Housing design: | Desktop console housing<br>(19") 48.3 cm rack installation possible 1 U  |
| Dimensions:     | Width: 21 cm<br>Depth: 27 cm<br>Height: 4,3 cm   |
| Weight:         | 1,80 kg  |

### **PSSO WISE Bodypack 518-548MHz**

|                   |   |
|-------------------|---|
| Type:             | Pocket transmitter                          |
| Power supply:     | 3 V DC                                      |
| Battery:          | 2 x Mignon (AA) (not included)              |
| Frequency range:  | 50 - 18000 Hz                               |
| Gain:             | -32 dB to +4 dB                             |
| Range:            | Range up to 60m with line-of-sight          |
| Frequency band:   | UHF 518 - 548 MHz                           |
| RF power output:  | 50 mW; 30 mW; 10 mW                         |
| Modulation:       | FM  |
| Display type:     | Multicolor LCD display                      |
| Control elements: | Menu, navigation keys                       |
| Connections:      | Microphone via 1 x Mini XLR (F) 3-pin 5 V   |
| Color code:       | Color indicator and name adjustable         |
| Switch:           | On/off switch; Mute control                 |
| Material:         | Metal                                       |
| Color:            | Grey  |
| Dimensions:       | Width: 7 cm<br>Depth: 3 cm<br>Height: 13 cm |
| Weight:           | 190 g                                       |

### **PSSO WISE Headset for Bodypack**

|               |                    |
|---------------|--------------------|
| Type:         | Headset microphone |
| Power supply: | 2-10 V DC          |
| Cable length: | 1,5 m              |
| Capsule type: | Electret           |

|                  |                    |
|------------------|--------------------|
| Polar pattern:   | Omnidirectional    |
| Frequency range: | 100 - 20000 Hz     |
| S/N ratio:       | >58 dB             |
| Sensitivity:     | -45 dB             |
| Impedance:       | 1 kOhm<br>1000 Ohm |
| Connections:     | Mini XLR (F) 3-pin |
| Material:        | Metal              |
| Color:           | Skin-colored       |
| Dimensions:      | Diameter: Ø 3,5 mm |
| Weight:          | 20 g               |