

EUROLITE Set LED CBB-2 COB WW + Stand

LED light effect bar with WW COB LEDs including speaker stand and knob

Art. No.: 20000795

GTIN: 4026397687385



List price: 172.55 €

incl. 19% VAT.

Features:

EUROLITE LED CBB-2 COB WW Bar

LED light effect bar with WW COB LEDs, incl. IR remote control

- 2 powerful LEDs 35 W COB (chip-on-board) warm white (WW)
- Dimmer electronic
- Strobe effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via IR remote control; sound to light via microphone; DMX; stand-alone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 37°
- Very high color rendering index (CRI)
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- Preprogrammed in LED PC-Control 512; Light Captain; Light´J; Colorchief
- For application areas such as: Trade fair and shop fitting; stage; theater; video and photography
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

Logistic

EAN / GTIN: 4026397687385

Weight: 6,00 kg

Length: 1.20 m

Width: 0.60 m

Height: 0.60 m

Bulky product

OMNITRONIC Speaker Stand BOB System

Speaker stand for BOB speakers, extendable up to 170 cm

- Tube diameter: Ø 30 mm
- Adjustable height
- Scratchproof and shockproof

Package contents

- 1 x stand, 1 x user manual

Technical specifications:

Weight:	4,61 kg
---------	---------

EUROLITE LED CBB-2 COB WW Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
IP classification:	IP20
Lamp type:	LED lamp
LED type:	2 x 35 W COB (chip-on-board) warm white (WW)
Flash rate:	0 - 20 Hz
DMX channels:	2; 3; 5
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	IR remote control; sound to light via microphone; DMX; stand-alone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	LED PC-Control 512; Light Captain; Light´J; Colorchief
Projection:	Flicker-free
Beam angle:	37°
Beam angle (1/2 peak):	37°
Beam angle (1/10 peak):	70°
Color temperature:	2700K
Color rendering index (CRI):	91 Ra
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 15,5 cm Depth: 24 cm Height: 17,5 cm
Weight:	2,45 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0
Remote control	

Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OMNITRONIC Speaker Stand BOB System

Maximum carrying capacity:	14 kg
Height:	Maximum: 195 cm Minimum: 107 cm Adjustable in 6 steps with locking pin
Attachment system:	M10 thread
Type (general stands):	Speaker stand/manual
Material:	Steel
Color:	Black, painted; , scratchproof and shockproof
Main pipe diameter:	Ø 3 cm
Extension tube diameter:	Ø 2,5 cm
Weight:	2,15 kg