

EUROLITE Set AKKU THA-20PC TRC + Stand + Bag

Battery powered LED theater spot incl. speaker stand and matching transport bag

Art. No.: 20000796 GTIN: 4026397687392



List price: 315.35 €

incl. 19% VAT.

Features:

EUROLITE AKKU THA-20PC TRC Theater-Spot bk

Battery powered LED theater spotlight with manual brightness regulation

- Two additional frost filters provide a soft, homogeneous light
- New LED technology that simulates the color temperature curve of a halogen lamp when dimming
- Rugged metal housing
- Battery operation up to 2h
- 1 powerful LED 17 W COB (chip-on-board) Dim to warm (homogenous color mix)
- Dimmer electronic
- The device is cooled by passive convection cooling
- Control via stand-alone
- Flicker-free
- With a beam angle of 17°
- Very high color rendering index (CRI)
- With Mounting bracket
- Silent operation
- For application areas such as: Trade fair and shop fitting; Wedding/gala/events; video and photography; restaurants, bars and hotels
- Cordless, flexible and versatile
- Integrated automatic charging of the battery and status indicator
- Rubber feet
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x external mains adapter, 1 x filter frame, 1 x barndoor, 2 x diffusor cover

Logistic

EAN / GTIN: 4026397687392

Weight: 6,00 kg Length: 1.20 m Width: 0.60 m Heigth: 0.60 m Bulky product

OMNITRONIC Speaker Stand BOB System

Speaker stand for BOB speakers, extendable up to 170 cm

- Tube diameter: Ø 30 mm
- Adjustable height
- Scratchproof and shockproof

Package contents

- 1 x stand, 1 x user manual

OMNITRONIC BOB Transport Bag for Tripod/Distance Tube

Accessory for the BOB series

- Suitable for stands and distance tubes
- Made of easy-care artificial black textile
- High-quality workmanship with textile , black

Package contents

- 1 x bag

Technical specifications:

Weight: 4,75 kg

EUROLITE AKKU THA-20PC TRC Theater-Spot bk

100-240 V AC, 50/60 Hz
IP20
Mains input via Coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
1 x lithium ion 11,1 V, 2600 mAh, 28,86 Wh
Battery operation up to 2h Recharging time 3h
1 x 17 W COB (chip-on-board) Dim to warm (homogenous color mix)
3000K
Passive convection cooling
Stand-alone
Flicker-free
17°
17° Frost filter 19° Frost filter 26°
92 Ra
Black
Mounting bracket
Rubber feet
Length: 21 cm Width: 14,5 cm Height: 21 cm

Weight:	2,38 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OMNITRONIC Speaker Stand BOB System

Maximum carrying capacity:	14 kg
Height:	Maximum: 195 cm
	Minimum: 107 cm
	Adjustable in 6 steps with locking pin
Attachment system:	M10 thread
Type (general stands):	Speaker stand/manual
Material:	Steel
Color:	Black, painted; , scratchproof and shockproof
Main pipe diameter:	Ø 3 cm
Extension tube diameter:	Ø 2,5 cm
Weight:	2,15 kg

Locking screw M10 for STW

Weight: 30 g

OMNITRONIC BOB Transport Bag for Tripod/Distance Tube

Material:	Textile	
Color:	Black	
Dimensions:	Width: 1,06 m	
	Depth: 9 cm	
	Height: 7 cm	
Weight:	190 g	