

EUROLITE Set LED THA-20PC TRC + Stand

Fanless PC spot with 17 W white light LED incl. speaker stand

Art. No.: 20000797

GTIN: 4026397687408



List price: 220.15 €

incl. 19% VAT.

Features:

EUROLITE LED THA-20PC TRC Theater-Spot bk

Fanless PC spot with 17 W white light LED, color rendering index (CRI) >90

- New LED technology that simulates the color temperature curve of a halogen lamp when dimming
- Two additional frost filters provide a soft, homogeneous light
- 1 powerful LED 17 W COB (chip-on-board) Dim to warm (homogenous color mix)
- The device is cooled by passive convection cooling
- Control via stand-alone
- Flicker-free
- With a beam angle of 17°
- Very high color rendering index (CRI)
- With Mounting bracket
- Silent operation
- For application areas such as: Trade fair and shop fitting; Wedding/gala/events; video and photography; mobile use
- Dimmer electronic
- Rubber feet
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x barndoor, 1 x filter frame, 2 x diffusor cover, 1 x ring, 2 x lamp clamping ring, 1 x user manual

Logistic

EAN / GTIN: 4026397687408

Weight: 6,00 kg

Length: 1.20 m

Width: 0.60 m

Height: 0.60 m

Bulky product

OMNITRONIC Speaker Stand BOB System

Speaker stand for BOB speakers, extendable up to 170 cm

- Tube diameter: Ø 30 mm
- Adjustable height
- Scratchproof and shockproof

Package contents

- 1 x stand, 1 x user manual

Technical specifications:

Weight: 4,39 kg

EUROLITE LED THA-20PC TRC Theater-Spot bk

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	22 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Fuse:	5 x 20 mm, T 1 A Fuse replaceable
LED:	1 x 17 W COB (chip-on-board) Dim to warm (homogenous color mix)
Color temperature:	3000K
Cooling:	Passive convection cooling
Control:	Stand-alone
Projection:	Flicker-free
Beam angle:	17°
Beam angle (1/2 peak):	17° Frost filter 19° Frost filter 26°
Beam angle (1/10 peak):	36° Frost filter 40° Frost filter 53°
Color rendering index (CRI):	92 Ra
Illuminance in Lux (lx):	Warm white (WW) 3m: 727 lx, 6m: 188 lx
Housing color:	Black
Attachment system:	Mounting bracket
Transport aid:	Rubber feet
Material:	Aluminum casting
Slot for spot length:	10 cm x 10 cm
Dimensions:	Length: 21,5 cm Width: 14,5 cm Depth: 21 cm
Weight:	2,23 kg
Noise classification:	Class 0 (no noise at all)
Power cord	
Cable construction:	3 x 0,75 mm ² H05VV-F
Cable length:	Approx. 1 m

Mounting bracket

Diameter mounting holes: 1 x Ø10mm

Material: Metal, 3 mm

Diffusor cover

Material: Plastic

Color: Frost

Dimensions: Width: 2 mm
Diameter: Ø 8 cm

Ring

Material: Aluminum, 1 mm

Color: Gold

Dimensions: Depth: 1,3 cm
Diameter: Ø 8,2 cm

Barndoor

Material: Aluminum, 1 mm; metal

Ring diameter: Outside: 99 mm
Inside: 80 mm

Filter frame

Diameter mounting holes: 1 x Ø4mm

Material: Aluminum, 0,8 mm

Color: Black

Dimensions: Width: 9,9 cm
Height: 9,9 cm
Diameter: Ø 8 cm

Lamp clamping ring

Material: Metal, 2 mm

Color: Black

Legal specifications

Special product: Not designed for household room illumination

Intended use: Show effect lighting

OMNITRONIC Speaker Stand BOB System

Maximum carrying capacity: 14 kg

Height: Maximum: 195 cm
Minimum: 107 cm
Adjustable in 6 steps with locking pin

Attachment system: M10 thread

Type (general stands): Speaker stand/manual

Material: Steel

Color: Black, painted; , scratchproof and shockproof

Main pipe diameter: Ø 3 cm

Extension tube diameter: Ø 2,5 cm

Weight: 2,15 kg
