

## EUROLITE Set LED PLL-360 3200K + Stand

Surface light with 360 warm white LEDs and DMX incl. lighting stand and adapter

Art. No.: 20000798

GTIN: 4026397687415



**List price: 534.31 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED PLL-360 3200K Panel

Surface light with 360 warm white (WW)LEDs and DMX

- 360 powerful LEDs 0,5 W SMD 2835 warm white (WW)
- Energy-saving, durable and environmentally friendly
- Frost filter provides a soft, homogeneous light
- 4 barn doors to avoid blinding the audience and for protection during transport
- Silent operation
- Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by passive convection cooling
- Control via quick select potentiometer for brightness; DMX; master/slave function
- Flicker-free
- With a beam angle of 120°
- Very high color rendering index (CRI)
- With mounting bracket
- LCD display
- Slim, rugged metal housing
- For application areas such as: Video and photography; stage; Trade fair and shop fitting; theater
- Various versions available
- Dimmable
- Mains input and output for power linking up to 8 units
- Rugged carrying handle
- Application possibility: Suspended; on stand
- Preprogrammed in Light´J; Light Captain; Colorchief

#### Package contents

### Logistic

EAN / GTIN: 4026397687415

Weight: 14,00 kg

Length: 1.20 m

Width: 0.60 m

Height: 0.60 m

Bulky product

- 1 x spotlight, 1 x user manual, 1 x power cord

### EUROLITE LS-1 EU Steel Stand

Lighting stand made in EU, without crossbeam, maximum load 30 kg, height 145-315 cm

- Stable lighting stand for mobile use
- Adjustable height
- Made in Europe

#### Package contents

- 1 x stand, 1 x user manual

### EUROLITE LS-1A1 Adapter for LS-1

Universal adapter for lighting stands LS-1 and LS-1T

- Universal adapter allowing to mount a single spotlight
- Made in Europe

## Technical specifications:

Weight:	11,66 kg
---------	----------

### EUROLITE LED PLL-360 3200K Panel

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	130 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Lamp type:	LED lamp
Lamp specification:	Dimmable
LED type:	360 x 0,5 W SMD 2835 warm white (WW)
DMX channels:	3
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Quick select potentiometer for brightness; DMX; master/slave function
Preprogrammed in:	Light`J; Light Captain; Colorchief
Projection:	Flicker-free
Beam angle:	120°
Beam angle (1/2 peak):	120°
Color temperature:	3200K
Color rendering index (CRI):	94 Ra
Illuminance in Lux (lx):	Warm white (WW) 3m: 403 lx, 6m: 118 lx
Luminous flux:	9367 lm
Housing color:	Black

Attachment system:	Mounting bracket
Display type:	LCD display
Carrying handle:	1 pc/pcs
Dimensions:	Width: 57 cm Depth: 12 cm Height: 31 cm
Weight:	6,10 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	F
EPREL-Nr:	1056205

#### **EUROLITE LS-1 EU Steel Stand**

Maximum carrying capacity:	30 kg
Height:	Maximum: 315 cm Minimum: 145 cm
Attachment system:	Ø 28mm
Type (general stands):	Light stand/manual
Material:	Steel/magnesium
Color:	Black
Transport dimensions:	120 cm x 16 cm x 14 cm
Base area:	Ø 108 cm
Weight:	5,30 kg

#### **EUROLITE LS-1A1 Adapter for LS-1**

Maximum carrying capacity:	30 kg
Attachment system:	Ø 29mm M8 thread
Type (general stands):	Accessory
Material:	Steel
Color:	Black, powder-coated
Dimensions:	Width: 11 cm Depth: 9 cm Height: 10 cm
Weight:	0,26 kg