

EUROLITE Set LED THA-40PC TRC + Stand

Fanless PC spot with 57 W white light LED including speaker stand

Art. No.: 2000799

GTIN: 4026397687422



Features:

- Rugged metal housing
- 1 LED 57 W COB (chip-on-board) warm white (WW)
- Dimmer electronic
- The device is cooled by passive convection cooling
- Control via stand-alone; rotary dial for brightness; Dimmer
- Flicker-free
- With a beam angle of 12° - 47°
- Very high color rendering index (CRI)
- With mounting bracket
- Rubber feet
- Silent operation
- For application areas such as: Decoration; Trade fair and shop fitting; restaurants, bars and hotels; video and photography; advertisement/Shop window
- <p>OMNITRONIC Speaker Stand BOB System
- <h2 class="featureSatz">Speaker stand for BOB speakers, extendable up to 170 cm</h2>Tube diameter: Ø 30 mm
- Adjustable height
- Scratchproof and shockproof

Logistic

EAN / GTIN: 4026397687422

Weight: 7,00 kg

Length: 1.20 m

Width: 0.60 m

Height: 0.60 m

Bulky product

Technical specifications:

Weight:

5.98 kg

EUROLITE LED THA-40PC TRC Theater Spot bk

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	40 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 57 W COB (chip-on-board) warm white (WW)
Cooling:	Passive convection cooling
Control:	Stand-alone; rotary dial for brightness; Dimmer
Projection:	Flicker-free
Beam angle:	12° - 47°
Beam angle (1/2 peak):	12 - 36°
Beam angle (1/10 peak):	18 - 47°
Color temperature:	3100K
Color rendering index (CRI):	92 Ra
Illuminance in Lux (lx):	Narrow 3m: 2008 lx, 6m: 514 lx Wide 3m: 482 lx, 6m: 141 lx
Housing color:	Black
Attachment system:	Mounting bracket
Transport aid:	Rubber feet
Material:	Aluminum casting
Slot for spot length:	13.1 cm x 13.1 cm
Dimensions:	Length: 26 cm Width: 20 cm Depth: 25 cm
Weight:	3.82 kg
Noise classification:	Class 0 (no noise at all)
Diameter mounting holes:	1 x Ø10mm; 2 x Ø6mm
Material:	Metal, 3 mm
Cable construction:	3 x 0.75 mm ² H05VV-F
Cable length:	Approx. 1 m
Material:	Aluminum, 1.5 mm; metal
Ring diameter:	Outside: 12.9 mm Inside: 10.9 mm
Diameter mounting holes:	1 x Ø4mm
Shape:	Octagonal
Material:	Aluminum, 0.8 mm
Dimensions:	Width: 13 cm Height: 13 cm Diameter: Ø 10.5 cm
Special product:	Not designed for household room illumination

Intended use: Show effect lighting

OMNITRONIC Speaker Stand BOB System

Maximum carrying capacity:	14 kg
Height:	Maximum: 195 cm Minimum: 107 cm Adjustable in 6 steps with locking pin
Attachment system:	M10 thread
Type (general stands):	Speaker stand/manual
Material:	Steel
Color:	Black, painted; , scratchproof and shockproof
Main pipe diameter:	Ø 3 cm
Extension tube diameter:	Ø 2.5 cm
Weight:	2.15 kg

Scope of delivery:

1 x EUROLITE LED THA-40PC TRC Theater Spot bk

- 1 x spotlight
- 1 x barndoor
- 1 x filter frame
- 1 x user manual

1 x OMNITRONIC Speaker Stand BOB System

- 1 x stand
- 1 x user manual