

EUROLITE Set LED PLL-480 CW/WW + Stand

DMX-controlled surface light with 240 cold white and 240 warm white LEDs incl. steel stand

Art. No.: 2000800

GTIN: 4026397687439



List price: 724.71 €

incl. 19% VAT.

Features:

EUROLITE LED PLL-480 CW/WW Panel

DMX controlled surface light with 240 cold white and 240 warm white LEDs

- Energy-saving, durable and environmentally friendly
- Milky diffuser provides a soft, homogeneous light
- 4 barn doors to avoid blinding the audience and for protection during transport
- Electronic dimmer (0-100%)
- 4 dimmer speeds selectable
- Slim, rugged metal housing
- Stand or truss installation
- Mains input and output for power linking up to 8 units
- 480 powerful LEDs 0,5 W SMD CW/WW (homogenous color mix)
- Variable color temperature 3200 K - 5600 K
- Can be operated in 5 CH mode
- The device is cooled by passive convection
- Controlling by DMX; Master/slave function
- Preprogrammed in Light´J; Light Captain
- Flicker-free
- Effect: Strobe effect
- With a beam angle of 120°
- Very high color rendering index (CRI)
- With Mounting bracket
- LCD display for easy controlling
- 1 hinged, chromium plated case handle
- For application areas such as: Video- and Photographic; Stage

Package contents

- 1 x Spotlight, 1 x User manual, 1 x Power cord, 1 x Plug (male)

Logistic

EAN / GTIN: 4026397687439

Weight: 20,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

EUROLITE LS-1 EU Steel stand

Lighting stand made in EU, without crossbeam, maximum load 30 kg, height 145-315 cm

- Stable lighting stand for mobile use
- T bar, adapter and carry bag available as accessories
- Made in Europe

Package contents

- 1 x Stand, 1 x User manual

EUROLITE LS-1A1 Adapter for LS-1

Universal adapter for lighting stands LS-1 and LS-1T

- Universal adapter allowing to mount a single spotlight
- M8 thread
- Made in Europe

Technical specifications:

Weight: 18,16 kg

EUROLITE LED PLL-480 CW/WW Panel

| | |
|--|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 217 W |
| IP classification: | IP20 |
| Power connection: | Via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | P-Con (gray), mounting version |
| Lamp type: | LED lamp |
| LED: | 480 x 0,5 W SMD CW/WW (homogenous color mix) |
| Color temperature: | 3200K - 5600K adjustable |
| DMX channels: | 5 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Passive convection |
| Control: | DMX; Light 'J; Light Captain; Master/slave function |
| Beam angle: | 120° |
| Beam angle (1/2 peak): | 120° |
| Color rendering index (CRI) more than: | 96 Ra |
| Illuminance in Lux (lx): | Cold white (CW) 3m: 398 lx, 6m: 119 lx Warm white (WW) 3m: 391 lx, 6m: 117 lx All 3m: 787 lx, 6m: 234 lx |
| Lamp life: | 50000 h |
| Luminous flux: | 17470 lm |
| Housing color: | Black |

| | |
|----------------------------------|---|
| Attachment system: | Mounting bracket |
| Display type: | LCD display |
| Case handles: | 1 pc/pcs |
| Dimensions: | Width: 64 cm Depth: 12,5 cm Height: 33 cm |
| Weight: | 12,60 kg |
| Noise classification: | Class 0 (no noise at all) |
| Energy efficiency class (A - G): | F |

EUROLITE LS-1 EU Steel stand

| | |
|----------------------------|------------------------------------|
| Maximum carrying capacity: | 30 kg |
| Height: | Maximum: 315 cm Minimum: 145 cm |
| Attachment system: | Ø 28 mm |
| Type (general stands): | Light stand/manual |
| Material: | Steel/magnesium |
| Color: | Black |
| Transport dimensions: | 1,2 m x 16 cm x 14 cm |
| Base area: | Ø 1,08 m |
| Weight: | 5,30 kg |

EUROLITE LS-1A1 Adapter for LS-1

| | |
|----------------------------|--|
| Maximum carrying capacity: | 30 kg |
| Attachment system: | Ø 29 mm |
| Type (general stands): | Accessory |
| Material: | Steel |
| Color: | Black, powder-coated |
| Thread: | M8 thread |
| Dimensions: | Width: 11 cm Depth: 9 cm Height: 10 cm |
| Weight: | 260 g |