

EUROLITE Set 4x AKKU IP PAR 14 HCL QuickDMX + Case

Art. No.: 20000822 GTIN: 4026397689235







The article is no longer in our assortment.

Features:

EUROLITE AKKU IP PAR 14 HCL QuickDMX

IP65 battery-powered spotlight with RGBWA+UV LEDs, QuickDMX, frost filter and IR remote control

- Integrated QuickDMX transceiver for wireless DMX control
- Cordless, flexible and versatile
- Battery operation up to 26h depending on program used
- 14 powerful LEDs 10 W 6in1 HCL RGBWA/UV (homogenous color mix)
- Frost filter
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic;
 Dimmer speed (step response) adjustable
- Strobe effect
- Integrated show programs
- Direct color selection for 27 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; IR remote control; master/slave function; QuickDMX
- Preprogrammed in LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light'J; Colorchief
- Flicker-free
- With a beam angle of 15°
- Variable color temperature 2700 K 8000 K
- With double bracket
- LCD display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use
- For application areas such as: Mobile use; stage; rental
- Silent operation
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397689235

Weight: 60,00 kg Length: 1.20 m Width: 0.80 m Heigth: 0.60 m Bulky product

Package contents

1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 1 x XLR cable, 3 x frost filter, 2 x screw

ROADINGER Flightcase 4x TMH-30/TMH-40/TMH-60 with wheels

Trunk case with castors, PRO version

- For optimal security
- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 51,60 kg

EUROLITE AKKU IP PAR 14 HCL QuickDMX

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Battery/battery pack built-in Via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Cable length:	Approx. 1,1 m
Power output:	IP T-Con (F) mounting version
Fuse:	5 x 20 mm, T 3 A fuse replaceable
Battery pack type:	1 x lithium ion 22,2 V, 4400 mAh, 97,68 Wh
Battery pack:	Battery operation up to 26h depending on program used
	Recharging time 3h
LED type:	14 x 10 W 6in1 HCL RGBWA/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
Equipment:	Frost filter
DMX channels:	2; 3; 6-1; 6-2; 12
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; IR remote control; master/slave function; QuickDMX

Preprogrammed in:	LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light'J; Colorchief
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle:	15°
Beam angle (1/2 peak):	15°
	27°
	30°
	60°
Color temperature:	2700K - 8000K adjustable
Housing color:	Black
Attachment system:	Double bracket
Display type:	LCD display
Dimensions:	Width: 31,7 cm
	Depth: 22,7 cm
	Height: 37,0 cm
Weight:	7,85 kg
Noise classification:	Class 0 (no noise at all)

built-in

Show effect lighting

ROADINGER Flightcase 4x TMH-30/TMH-40/TMH-60 with wheels

Remote control

Legal specifications
Special product:

Intended use:

Battery:

100 kg
30 mm
4 pc/pcs
2 pc/pcs
Butterfly lock: 2 pc/pcs
4 x castors with 2 locking brakes4 x built-in stacking trays in the cover
Branded hardware
Birch multiplex, 7 mm
Dark brown, laminated
27 cm x 27 cm x 28 cm
10 cm x 56 cm x 28 cm
65 cm x 55 cm x 30,5 cm
Length: 71 cm Width: 60 cm Height: 53 cm
20,20 kg

1 x button cell 3.0 V CR2032 lithium manganese

Not designed for household room illumination