

EUROLITE Set 2x AKKU IP PAR 14 HCL QuickDMX + Case

Art. No.: 20000823

GTIN: 4026397689242













The article is no longer in our assortment.

Features:

EUROLITE AKKU IP PAR 14 HCL QuickDMX

IP65 battery-powered spotlight with RGBWA+UV LEDs, QuickDMX, frost filter and IR remote control

- Integrated QuickDMX transceiver for wireless DMX control
- Cordless, flexible and versatile
- Battery operation up to 26h depending on program used
- 14 powerful LEDs 10 W 6in1 HCL RGBWA/UV (homogenous color mix)
- Frost filter
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic;
 Dimmer speed (step response) adjustable
- Strobe effect
- Integrated show programs
- Direct color selection for 27 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; IR remote control; master/slave function; QuickDMX
- Preprogrammed in LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light'J; Colorchief
- Flicker-free
- With a beam angle of 15°
- Variable color temperature 2700 K 8000 K
- With double bracket
- LCD display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use
- For application areas such as: Mobile use; stage; rental
- Silent operation
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397689242

Weight: 30,00 kg Length: 1.20 m Width: 0.80 m Heigth: 0.60 m Bulky product

Package contents

1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 1 x XLR cable, 3 x frost filter, 2 x screw

ROADINGER Flightcase 2x TMH-30/40/60

PRO flightcase for 2 x EUROLITE LED TMH-30/TMH-40/TMH-60 moving head

- For optimal security
- With 2 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 24,90 kg

EUROLITE AKKU IP PAR 14 HCL QuickDMX

| Power supply: | 100-240 V AC, 50/60 Hz |
|--------------------|---|
| IP classification: | IP65 |
| Protection class: | Protection class I |
| Power connection: | Battery/battery pack built-in |
| | Via IP T-Con (M) mounting version power supply cord with safety plug (provided) |
| Cable length: | Approx. 1,1 m |
| Power output: | IP T-Con (F) mounting version |
| Fuse: | 5 x 20 mm, T 3 A fuse replaceable |
| Battery pack type: | 1 x lithium ion 22,2 V, 4400 mAh, 97,68 Wh |
| Battery pack: | Battery operation up to 26h depending on program used |
| | Recharging time 3h |
| LED type: | $14 \times 10 \text{ W}$ 6in1 HCL RGBWA/UV (homogenous color mix) |
| Flash rate: | 0 - 20 Hz |
| Equipment: | Frost filter |
| DMX channels: | 2; 3; 6-1; 6-2; 12 |
| DMX input: | 3-pin XLR (M) mounting version IP |
| DMX output: | 3-pin XLR (F) mounting version IP |
| Cooling: | Passive convection cooling |
| Control: | DMX; stand-alone; IR remote control; master/slave function; QuickDMX |
| | |

| Preprogrammed in: | LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light'J; Colorchief |
|------------------------|---|
| Projection: | Flicker-free |
| Carrier frequency: | 2,4 GHz |
| Beam angle: | 15° |
| Beam angle (1/2 peak): | 15° |
| | 27° |
| | 30° |
| | 60° |
| Color temperature: | 2700K - 8000K adjustable |
| Housing color: | Black |
| Attachment system: | Double bracket |
| Display type: | LCD display |
| Dimensions: | Width: 31,7 cm |
| | Depth: 22,7 cm |
| | Height: 37,0 cm |
| Weight: | 7,85 kg |
| Noise classification: | Class 0 (no noise at all) |
| Remote control | |
| Battery: | 1 x button cell 3.0 V CR2032 lithium manganese built-in |
| Legal specifications | |
| Special product: | Not designed for household room illumination |

ROADINGER Flightcase 2x TMH-30/40/60

Intended use:

| Maximum load: | 50 kg |
|--------------------------|---------------------------|
| Aluminum profile frames: | 30 mm |
| Case handle: | 2 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |
| Use of brands: | Branded hardware |
| Material: | Birch multiplex, 7 mm |
| Color: | Dark brown, laminated |
| Device compartment: | 26,5 cm x 31 cm x 30,5 cm |
| Middle compartment: | 10,5 cm x 31 cm x 30,5 cm |
| Inside dimensions: | 63,5 cm x 31 cm x 30,5 cm |
| Dimensions: | Width: 71 cm |
| | Depth: 35 cm |
| | Height: 40,5 cm |
| Weight: | 9,20 kg |
| | |

Show effect lighting