

EUROLITE Set DIY LED THA-20PC TRC + Multi adapter, 3 phases, black

DIY set for connection to 3-phase track systems

Art. No.: 20000830

GTIN: 4026397689310



The article is no longer in our assortment.

Features:

EUROLITE LED THA-20PC TRC Theater-Spot bk

Fanless PC spot with 17 W white light LED, color rendering index (CRI) >90

- New LED technology that simulates the color temperature curve of a halogen lamp when dimming
- Two additional frost filters provide a soft, homogeneous light
- 1 powerful LED 17 W COB (chip-on-board) Dim to warm (homogenous color mix)
- The device is cooled by passive convection cooling
- Control via stand-alone
- Flicker-free
- With a beam angle of 17°
- Very high color rendering index (CRI)
- With Mounting bracket
- Silent operation
- For application areas such as: Trade fair and shop fitting; Wedding/gala/events; video and photography; mobile use
- Dimmer electronic
- Rubber feet
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x barndoor, 1 x filter frame, 2 x diffusor cover, 1 x ring, 2 x lamp clamping ring, 1 x user manual

Logistic

EAN / GTIN: 4026397689310

Weight: 3,50 kg

Length: 0.41 m

Width: 0.31 m

Height: 0.28 m

EUTRAC Multi adapter, 3 phases, black

Multi adapter with data bus option

- For 3~ circuit track
- Prepared for data bus contacts (data bus contact with SELV safety chip, part no. 99-698-0)
- Screw termination, approved for 6 A inductive / 6 A ohmic up to 250 V
- With earth contact, circuit selection by turnkey switch and optional neutral position during operation
- Due to double mechanical locking perfect track fixing even when using heavy spotlights
- Maximum load up to 5 kg, or 10 kg when using retaining collar 99-066-x
- Made in Germany

EUTRAC Retaining collar for multi adapter Ø10,5mm/ Ø13,5mm black

- 1 x screwing

Technical specifications:

Weight: 2,29 kg

EUROLITE LED THA-20PC TRC Theater-Spot bk

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	22 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Fuse:	5 x 20 mm, T 1 A Fuse replaceable
LED:	1 x 17 W COB (chip-on-board) Dim to warm (homogenous color mix)
Color temperature:	3000K
Cooling:	Passive convection cooling
Control:	Stand-alone
Projection:	Flicker-free
Beam angle:	17°
Beam angle (1/2 peak):	17° Frost filter 19° Frost filter 26°
Beam angle (1/10 peak):	36° Frost filter 40° Frost filter 53°
Color rendering index (CRI):	92 Ra
Illuminance in Lux (lx):	Warm white (WW) 3m: 727 lx, 6m: 188 lx
Housing color:	Black
Attachment system:	Mounting bracket
Transport aid:	Rubber feet
Material:	Aluminum casting
Slot for spot length:	10 cm x 10 cm
Dimensions:	Length: 21,5 cm Width: 14,5 cm

	Depth: 21 cm
Weight:	2,23 kg
Noise classification:	Class 0 (no noise at all)
Power cord	
Cable construction:	3 x 0,75 mm ² H05VV-F
Cable length:	Approx. 1 m
Mounting bracket	
Diameter mounting holes:	1 x Ø10mm
Material:	Metal, 3 mm
Diffusor cover	
Material:	Plastic
Color:	Frost
Dimensions:	Width: 2 mm Diameter: Ø 8 cm
Ring	
Material:	Aluminum, 1 mm
Color:	Gold
Dimensions:	Depth: 1,3 cm Diameter: Ø 8,2 cm
Barndoor	
Material:	Aluminum, 1 mm; metal
Ring diameter:	Outside: 99 mm Inside: 80 mm
Filter frame	
Diameter mounting holes:	1 x Ø4mm
Material:	Aluminum, 0,8 mm
Color:	Black
Dimensions:	Width: 9,9 cm Height: 9,9 cm Diameter: Ø 8 cm
Lamp clamping ring	
Material:	Metal, 2 mm
Color:	Black
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUTRAC Multi adapter, 3 phases, black

Power connection:	Mains input via Special connector recessed mounting
Power output:	Screw terminal
Weight:	50 g

EUTRAC Retaining collar for multi adapter Ø10,5mm/ Ø13,5mm black

Weight:

10 g
