



Features:

- New LED technology that simulates the color temperature curve of a halogen lamp when dimming
- Two additional frost filters provide a soft, homogeneous light
- 1 LED 17 W COB (chip-on-board) Dim to warm (homogenous color mix)
- Dimmer electronic
- The device is cooled by passive convection cooling
- Control via stand-alone
- Flicker-free
- With a beam angle of 17°
- Very high color rendering index (CRI)
- With mounting bracket
- Rubber feet
- For application areas such as: Decoration; Trade fair and shop fitting; wedding/gala/events; video and photography; advertisement/Shop window; restaurants, bars and hotels
- Silent operation
- Application possibility: Suspended; on stand
- <p>EUTRAC Multi adapter, 3 phases, black
- <h2 class="featureSatz">Multi adapter with data bus option</h2>For 3~ circuit track
- Prepared for data bus contacts (data bus contact with SELV safety chip, part no. 99-698-0)
- Screw termination, approved for 6 A inductive / 6 A ohmic up to 250 V
- With earth contact, circuit selection by turnkey switch and optional neutral position during operation
- Due to double mechanical locking perfect track fixing even when using heavy spotlights
- Maximum load up to 5 kg, or 10 kg when using retaining collar 99-066-x
- Made in Germany

Logistic

EAN / GTIN: 4026397689310

Weight: 3,50 kg

Length: 0.41 m

Width: 0.31 m

Heigh: 0.28 m

Technical specifications:

Weight: 2.29 kg

EUROLITE LED THA-20PC TRC Theater Spot bk

| | |
|------------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 22 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Fixed power supply cord with safety plug |
| Fuse: | 5 x 20 mm, T 1 A fuse replaceable |
| Lamp type: | LED lamp |
| LED type: | 1 x 17 W COB (chip-on-board) Dim to warm (homogenous color mix) |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone |
| Projection: | Flicker-free |
| Beam angle: | 17° |
| Beam angle (1/2 peak): | 17° Frost filter 19° Frost filter 26° |
| Beam angle (1/10 peak): | 36° Frost filter 40° Frost filter 53° |
| Color temperature: | 3000K |
| Color rendering index (CRI): | 92 Ra |
| Illuminance in Lux (lx): | Warm white (WW) 3m: 727 lx, 6m: 188 lx |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Transport aid: | Rubber feet |
| Material: | Aluminum casting |
| Slot for spot length: | 10 cm x 10 cm |
| Dimensions: | Length: 21.5 cm Width: 14.5 cm Depth: 21 cm |
| Weight: | 2.23 kg |
| Noise classification: | Class 0 (no noise at all) |
| Diameter mounting holes: | 1 x Ø10mm |
| Material: | Metal, 3 mm |
| Cable construction: | 3 x 0.75 mm ² H05VV-F |
| Cable length: | Approx. 1 m |
| Material: | Aluminum, 1 mm; metal |

| | |
|--------------------------|---|
| Ring diameter: | Outside: 99 mm Inside: 80 mm |
| Diameter mounting holes: | 1 x Ø4mm |
| Material: | Aluminum, 0.8 mm |
| Color: | Black |
| Dimensions: | Width: 9.9 cm Height: 9.9 cm Diameter: Ø 8 cm |
| Material: | Plastic |
| Color: | Semi-transparent |
| Dimensions: | Width: 0.2 cm Diameter: Ø 8 cm |
| Material: | Aluminum, 1 mm |
| Color: | Gold |
| Dimensions: | Depth: 1.3 cm Diameter: Ø 8.2 cm |
| Material: | Metal, 2 mm |
| Color: | Black |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

EUTRAC Multi adapter, 3 phases, black

| | |
|-------------------|---|
| Power connection: | Mains input via special connector recessed mounting |
| Power output: | Screw terminal |
| Weight: | 0.05 kg |

EUTRAC Retaining collar for multi adapter Ø10,5mm/ Ø13,5mm black

| | |
|---------|---------|
| Weight: | 0.01 kg |
|---------|---------|

Scope of delivery:

1 x EUROLITE LED THA-20PC TRC Theater Spot bk

- 1 x spotlight
- 1 x barndoor
- 1 x filter frame
- 2 x frost filter
- 1 x ring
- 2 x lamp clamping ring
- 1 x user manual

1 x EUTRAC Retaining collar for multi adapter Ø10,5mm/ Ø13,5mm black

- 1 x screwing