

## EUROLITE Set 2x LED SLS-6 TCL Spot + LED QDF-Bar RGBAW Light set

Art. No.: 2000832

2x flat spotlight with 6 x 8 W 3in1 LED with RGB incl. spotlight bar with 4 LED heads

GTIN: 4026397689334



**The article is no longer in our assortment.**

### Features:

#### EUROLITE LED SLS-6 TCL Spot

Flat spotlight with 6 x 8 W 3in1 LED with RGB color mixing

- Slim design for space-saving applications
- DMX and power terminals intelligently designed for easy wiring
- 6 powerful LEDs 8 W high-power 3in1 TCL RGB (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- 2 integrated show programs
- Direct color selection for 16 preset colors
- The device is cooled by cooling fan
- Control via stand-alone; DMX; Sound to light via Microphone; Master/slave function
- Flicker-free
- With a beam angle of 16°
- With Mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- Preprogrammed in EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3
- Rubber feet
- For application areas such as: Clubs/dancing school; Party room; small rental
- Application possibility: Standing; suspended; on stand

#### Package contents

- 1 x spotlight, 1 x power cord, 1 x user manual

### Logistic

EAN / GTIN: 4026397689334

Weight: 10,00 kg

Length: 1.30 m

Width: 0.50 m

Height: 0.30 m

Bulky product

## EUROLITE LED QDF-Bar RGBAW Light Set

LED bar with 4 LED heads, LEDs in RGBWA and DMX

- Crossbar with integrated DMX control unit and stand sleeve
  - Ultra-light ideally suited for mobile use
  - Ideal for bands, stages or solo entertainers
  - Suited for installation on a speaker stand (not included) or truss
  - Comes pre-assembled with practical transport bag
  - Equipped with 240 LEDs (5 mm) in the colors red, green, blue, amber and white
  - Movable and tiltable spotlights
  - Via DMX, each spot can be individually controlled
  - DMX-controlled operation or stand-alone operation
  - DMX512 control via any commercial DMX controller (occupies 23 channels)
  - Functions: Effect/color presets, built-in programs, strobe effect with variable speed, Master/Slave operation
  - Addressing and setting via control panel with 4-digit LED display
  - Additional controlling possibility via the EUROLITE IR-7 remote control, included in delivery
  - Black lacquered metal version
  - IEC terminals for power linking up to 8 units
  - Switch-mode power supply for operation between 100 and 240 volts
  - 240 powerful LEDs 5 mm R/G/B/W/A<BR> LEDs controlled separately
  - The device is cooled by passive convection cooling
  - Control via stand-alone; DMX; Sound to light via Microphone
  - Preprogrammed in Light J; LED PC-Control 512
  - Flicker-free
  - Silent operation
- Package contents**
- 1 x spotlight, 1 x remote control

## Technical specifications:

---

Weight: 7,67 kg

---

## EUROLITE LED SLS-6 TCL Spot

|                    |  |
|--------------------|--|
| Power supply:      | 100-240 V AC, 50/60 Hz   |
| Power consumption: | 15 W   |
| IP classification: | IP20   |
| Power connection:  | Mains input via IEC connector (M) mounting version power supply cord with safety plug included |
| Power output:      | 1 x IEC connector (F) mounting version   |
| Lamp type:         | LED lamp   |
| LED:               | 6 x 8 W high-power 3in1 TCL RGB (homogenous color mix)   |
| Flash rate:        | 0 - 20 Hz  |
| DMX channels:      | 2; 3; 4; 5; 7  |
| DMX input:         | 1 x 3-pin XLR (M) mounting version   |
| DMX output:        | 1 x 3-pin XLR (F) mounting version   |
| Cooling:           | 1 x cooling fan  |
| Control:           | Stand-alone; DMX; Sound to light via Microphone; Master/slave function                         |

---

Preprogrammed in: EASY SHOW 1; LED EASY OPERATOR 4x4;  
LED EASY OPERATOR 4x6; LED EASY  
OPERATOR DELUXE; LED PC-Control 512;  
Light Captain; EASY SHOW 2; EASY SHOW 3

|                          |   |
|--------------------------|---|
| Projection:              | Flicker-free                                  |
| Beam angle:              | 16°   |
| Beam angle (1/2 peak):   | 16°   |
| Beam angle (1/10 peak):  | 30°   |
| Housing color:           | Black   |
| Attachment system:       | Mounting bracket                              |
| Display type:            | 4 digit 7-segment LED display                 |
| Transport aid:           | Rubber feet                                   |
| Material:                | Plastic; ABS Acrylonitrile butadiene styrene  |
| Dimensions:              | Width: 22 cm<br>Depth: 11 cm<br>Height: 21 cm |
| Weight:                  | 1,16 kg                                       |
| Noise classification:    | Class 2 (slight noise)                        |
| Photobiological safety:  | Risk Group 0                                  |
| Power cord               |   |
| Cable construction:      | 3 x 0,75 mm <sup>2</sup> H05VV-F              |
| Cable length:            | Approx. 1,2 m                                 |
| Mounting bracket         |   |
| Diameter mounting holes: | 5 x Ø11mm                                     |
| Material:                | Metal, 2 mm                                   |
| Legal specifications     |   |
| Special product:         | Not designed for household room illumination  |
| Intended use:            | Show effect lighting                          |

#### **EUROLITE LED QDF-Bar RGBAW Light Set**

|                    |  |
|--------------------|--|
| Power supply:      | 100-240 V AC, 50/60 Hz   |
| Power consumption: | 20 W   |
| IP classification: | IP20   |
| Power connection:  | Mains input via IEC connector (M) mounting<br>version power supply cord with safety plug<br>(provided) |
| Power output:      | 1 x IEC connector (F) mounting version   |
| Fuse:              | F 1 A Fuse replaceable   |
| Lamp type:         | LED lamp   |
| LED:               | 240 x 5 mm R/G/B/W/A   |
| Flash rate:        | 0 - 20 Hz  |
| DMX channels:      | 4; 7; 23   |
| DMX input:         | 1 x 3-pin XLR (M) mounting version   |
| DMX output:        | 1 x 3-pin XLR (F) mounting version   |
| Cooling:           | Passive convection cooling   |

|                       |   |
|-----------------------|---|
| Control:              | Stand-alone; DMX; Sound to light via Microphone         |
| Preprogrammed in:     | Light J; LED PC-Control 512                             |
| Projection:           | Flicker-free  |
| Housing color:        | Black   |
| Dimensions:           | Width: 85 cm<br>Depth: 11 cm<br>Height: 36 cm           |
| Weight:               | 4,5 kg  |
| Noise classification: | Class 0 (no noise at all)                               |
| Remote control        |   |
| Battery:              | 1 x Button cell 3.0 V CR2025 lithium manganese built-in |
| Legal specifications  |   |
| Special product:      | Not designed for household room illumination            |
| Intended use:         | Show effect lighting                                    |