

EUROLITE Set 2x LED SLS-6 TCL Spot + LED QDF-Bar RGBAW Light set

Art. No.: 2000832

2x flat spotlight with 6 x 8 W 3in1 LED with RGB incl. spotlight bar with 4 LED heads

GTIN: 4026397689334



Features:

- Slim design for space-saving applications
- DMX and power terminals intelligently designed for easy wiring
- 6 LEDs 8 W high-power 3in1 R/G/B (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- 2 integrated show programs
- Direct color selection for 16 preset colors
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function
- Flicker-free
- With a beam angle of 16°
- With mounting bracket
- 4 digit 7-segment LED display
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels
- Application possibility: Standing; suspended; on stand
- <p>EUROLITE LED QDF-Bar RGBAW Light Set
- <h2 class="featureSatz">LED bar with 4 LED heads, LEDs in RGBWA and DMX</h2>Crossbar with integrated DMX control unit and stand sleeve
- Ultra-light ideally suited for mobile use
- Ideal for bands, stages or solo entertainers
- Suited for installation on a speaker stand (not included) or truss
- Comes pre-assembled with practical transport bag
- Equipped with 240 LEDs (5 mm) in the colors red, green, blue, amber and white

Logistic

EAN / GTIN: 4026397689334

Weight: 10,00 kg

Length: 1.30 m

Width: 0.50 m

Height: 0.30 m

Bulky product

- Movable and tiltable spotlights
- Via DMX, each spot can be individually controlled
- DMX-controlled operation or stand-alone operation
- DMX512 control via any commercial DMX controller (occupies 23 channels)
- Functions: Effect/color presets, built-in programs, strobe effect with variable speed, Master/Slave operation
- Addressing and setting via control panel with 4-digit LED display
- Additional controlling possibility via the EUROLITE IR-7 remote control, included in delivery
- Black lacquered metal version
- IEC terminals for power linking up to 8 units
- Switch-mode power supply for operation between 100 and 240 volts
- 240 LEDs 5 mm R/G/B/W/A
 LEDs controlled separately
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone
- Flicker-free
- Silent operation

Technical specifications:

Weight: 7.67 kg

EUROLITE LED SLS-6 TCL Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	15 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug included
Power output:	1 x IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 0.5 A fuse replaceable
Lamp type:	LED lamp
LED type:	6 x 8 W high-power 3in1 R/G/B (homogenous color mix)
Flash rate:	0.5 - 23 Hz
DMX channels:	2; 3; 4; 5; 7
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	1 x cooling fan
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function
Fixtures available for:	EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	30°
Housing color:	Black matte

Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Transport aid:	Rubber feet
Material:	Plastic; ABS Acrylonitrile butadiene styrene
Dimensions:	Width: 22 cm Depth: 11 cm Height: 21 cm
Weight:	1.16 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0
Cable construction:	3 x 0.75 mm ² H05VV-F
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE LED QDF-Bar RGBAW Light Set

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	20 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	F 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	240 x 5 mm R/G/B/W/A
Flash rate:	0 - 20 Hz
DMX channels:	4; 7; 23
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; sound to light via microphone
Fixtures available for:	Light J; LED PC-Control 512
Projection:	Flicker-free
Housing color:	Black
Dimensions:	Width: 85 cm Depth: 11 cm Height: 36 cm
Weight:	4.5 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

2 x EUROLITE LED SLS-6 TCL Spot

- 1 x spotlight
- 1 x power cord
- 1 x user manual

1 x EUROLITE LED QDF-Bar RGBAW Light Set

- 1 x spotlight
- 1 x remote control