



**List price: 653.31 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED B-40 Laser Beam Effect wh

LED beam effect with RGBW color mixing and RG laser

- 2 laser diodes project hundreds of red and green laser beams
- 5 powerful LEDs 8 W high-power 4in1 QCL RGBW<BR>3 segments controlled separately
- For application areas such as: Clubs/dancing school; Wedding/gala/events; mobile djs / entertainer; Rental
- Laser; multi beam effect; Strobe effect
- Laser class 2M <BR> does not require additional protective measures or appointment of a laser safety officer
- Rotation speed stepless; color blend stepless; Dimmer electronic
- 7 integrated show programs
- The device is cooled by cooling fan at the Head; cooling fan at the Base
- Control via IR remote control; stand-alone; Sound to light via Microphone; DMX; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- With Mounting bracket
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3; Light J
- Mains input and output for power linking up to 8 units
- Application possibility: Standing; suspended; on stand

#### Package contents

- 1 x light effect, 1 x user manual, 1 x power cord, 1 x remote control, 1 x mounting bracket, 4 x screw, 4 x washer

### Logistic

EAN / GTIN: 4026397690606

Weight: 12,00 kg

Length: 0.82 m

Width: 0.41 m

Height: 0.52 m

## ROADINGER Flightcase 1x B-40 HCL/Laser

Trunk case, PRO version

- High-quality workmanship with birch multiplex 6,5 mm, dark brown
- Interior with foam padding
- Aluminum profile frames 20mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 2 high-quality spring locks
- Branded hardware
- European engineering
- For further information about this product, please refer to the Data Sheet under "Downloads"

### Technical specifications:

---

Weight: 11,20 kg

---

### EUROLITE LED B-40 Laser Beam Effect wh

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	65 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 1 A Fuse replaceable
Lamp type:	LED lamp
LED:	5 x 8 W high-power 4in1 QCL RGBW
Flash rate:	0 - 20 Hz
Laser class:	2M
Laser color:	R/G
Laser module:	Green (G) 40 mW 532nm Red (R) 100 mW 650nm
DMX channels:	3; 10; 22
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan at the Head Cooling fan at the Base
Control:	IR remote control; stand-alone; Sound to light via Microphone; DMX; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3; Light J
Housing color:	White
Attachment system:	Mounting bracket

Dimensions:	Width: 31 cm Depth: 31 cm Height: 39 cm
Weight:	4,30 kg
Noise classification:	Class 2 (slight noise)

#### **ROADINGER Flightcase 1x B-40 HCL/Laser**

Maximum load:	25 kg
Aluminum profile frames:	20 mm
Case handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Spring lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 6,5 mm, laminated
Color:	Dark brown
Device compartment:	32,5 cm x 32,5 cm x 39 cm
Dimensions:	Length: 40 cm Width: 40 cm Height: 48 cm
Weight:	6,90 kg