

EUROLITE Set LED KLS Scan Next FX Compact Light Set + Controller + Steel stand 00851

GTIN: 4026397690859



List price: 1248.31 €

incl. 19% VAT.

Features:

EUROLITE LED KLS Scan Next FX Compact Light Set

Compact bar with derby, spots, scanners, UV effect, QuickDMX port and bag

- DMX light effect bar with 1 rotating LED derby, 4 LED spots, 2 scanners and UV LEDs
- Ultra-light ideally suited for mobile use
- Crossbar with integrated DMX control unit and TV spigot for stand installation
- Swivel mounting brackets for truss mounting
- Comes pre-assembled with practical transport bag
- Convenient control via included IR remote control or optional wireless foot switch
- Sound-control via built-in microphone with sensitivity control
- Several diverse DMX modes for various consoles and requirements
- LED derby and LED spots individually tiltable and controllable
- Spots with 15° beam angle
- Mirror movement can be inverted separately for both scanners (e.g. for common, counter-rotating control)
- Brand-new software design with smart programs
- 20 built-in auto and music show programs that include all 4 effect units
- Addressing and setting via control panel with 4-digit OLED display
- Supports QuickDMX - the wireless DMX system by Eurolite
- Built-in phantom-powered USB port for QuickDMX receivers (accessories)
- When fog is used, this effect becomes especially attractive
- P-Con terminals for power linking up to 8 units
- Switch-mode power supply for operation between 100 and 240 volts
- Can be operated in 3; 7; 13; 14; 15; 18; 19; 30; 32; 39 CH mode
- The device is cooled by cooling fan
- Controlling by DMX; QuickDMX via USB (optional); IR remote control (provided); Sound to light via Microphone; Stand-alone; Wireless footswitch (optional); Master/slave function

Logistic

EAN / GTIN: 4026397690859

Weight: 23,22 kg

Length: 1.20 m

Width: 0.80 m

Height: 1.35 m

Bulky product

- For application areas such as: Wedding/gala; Lender; Small lender
- spotlight**
- LED: Spot each 3 x high-power 7 W 4in1 QCL RGB/WW (homogenous color mix)
- light effect**
- LED: Multi beam effect each 1 x 3 W R/G/B
- moving light**
- LED: Scanner each 1 x 15 W cold white (CW)
- bar**
- LED: 4 x high-power 1 W ultra violett (UV)

EUROLITE QuickDMX USB Wireless Transmitter/Receiver

Wireless miniature DMX transceiver 2.4 GHz, phantom powered

- User-friendly USB plug with swivel antenna
- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to GFSK modulation with 78 channels, interference-free operation also alongside other QuickDMX receivers and wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- Operating range up to 400 m (with line-of-sight)
- Simultaneous operation of up to 6 transmitters, thus control of 6 DMX universes (3072 DMX channels) possible
- Plug & Play: quick and easy setup with one operating button for connecting/disconnecting QuickDMX receivers
- LED indication for functions
- Transceiver to be used as transmitter or receiver
- Requires 5 V phantom power for operation
- 2.4 GHz ISM band - license-free worldwide
- Can receive and process up to 512 DMX channels
- Can transmit up to 512 DMX channels
- Controlling by DMX; QuickDMX built-in

EUROLITE QuickDMX Wireless Transmitter

Compact wireless DMX transmitter 2.4 GHz

- User-friendly 3-pin XLR plug (male) with swivel antenna
- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to GFSK modulation with 78 channels, interference-free operation also alongside other QuickDMX transmitters and wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- Simultaneous operation of up to 6 transmitters, thus control of 3072 DMX channels (6 DMX universes) possible
- 1 to 512 QuickDMX receivers can be controlled by each transmitter
- Plug & Play: quick and easy setup with one operating button for connecting/disconnecting QuickDMX receivers
- LED indication for functions
- Transceiver, to be used as transmitter or receiver
- Powered via included PSU
- 2.4 GHz ISM band - license-free worldwide
- Can transmit up to 512 DMX channels
- Controlling by QuickDMX built-in; DMX
- Use a operating range up to 400m

EUROLITE DMX LED Color Chief Controller

DMX lighting desk with innovative control concept for LED spotlights

- Easy control of LED spotlights with up to 6 colors, light bars as well as simple lighting effects
- For 8 devices or device groups, each with up to 4 segments
- Each device can occupy up to 30 channels
- Quick and easy programming
- Eurolite KLS systems and LED spotlights already in the library
- Additional fixtures can be configured manually
- 8 color effects directly selectable
- 3 additional channels available per fixture (e.g. for rotations)
- Color wheel selection and simulation

- 24 memory spaces for scenes and chases
- Several chases can be run simultaneously
- USB port for data storage of lighting programs
- Sound control via audio signal or TAP button
- Master dimming, fade time and run time easily adjustable
- 3-pin XLR connector
- Firmware update via USB
- Desktop console
- Programmable 24 sequencens
- Can transmit up to 240 DMX channels
- Controlling by DMX; Sound to light via RCA (F) mounting version; Sound to light via Microphone
- (19") 48.3 cm rack installation 3 U

EUROLITE STV-60-WOT EU Steel Stand black

Lighting stand, made in EU, maximum load 30 kg, height 150-315 cm

- Stable lighting stand (without T bar)
- For mobile use
- Steel/magnesium version
- Ø 29 mm attachment fits standard TV pins
- Carry bag available as accessory
- Available in black and white
- Made in Europe

Technical specifications:

Weight: 20,86 kg

EUROLITE LED KLS Scan Next FX Compact Light Set

| | |
|-------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 115 W |
| IP classification: | IP20 |
| Protection class: | Class I |
| Power connection: | Mains input P-Con (blue), mounting version Power supply cord with safety plug (provided) |
| Power output: | P-Con (gray), mounting version |
| Fuse: | 5 x 20 mm, T 2 A Fuse replaceable |
| Lamp type: | LED lamp |
| Equipment: | Color wheel; gobo wheel with static gobos |
| DMX channels: | 3; 7; 13; 14; 15; 18; 19; 30; 32; 39 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Cooling fan |
| Control: | DMX; QuickDMX via USB (optional); IR remote control (provided); Sound to light via Microphone; Stand-alone; Wireless footswitch (optional); Master/slave function |
| Beam angle: | 15° |
| Beam angle (1/2 peak): | Spot 15° |
| Beam angle (1/10 peak): | Spot 28° |

| | |
|---------------------------------|---|
| <p>Illuminance in Lux (lx):</p> | <p>Red (R) 1m: 1022 lx, 3m: 125 lx, 6m: 33 lx Green (G) 1m: 2448 lx, 3m: 285 lx, 6m: 75 lx Blue (B) 1m: 395 lx, 3m: 47 lx, 6m: 13 lx Warm white (WW) 1m: 1892 lx, 3m: 219 lx, 6m: 58 lx All 1m: 4853 lx, 3m: 676 lx, 6m: 175 lx</p> |
| Housing color: | Black |
| Attachment system: | TV spigot Ø 28mm |
| Display type: | OLED display |
| Dimensions: | Width: 1,1 m Depth: 15,5 cm Height: 43 cm |
| Weight: | 12,80 kg |
| Spotlight | |
| LED: | Spot each 3 x high-power 7 W 4in1 QCL RGB/WW (homogenous color mix) |
| Light effect | |
| LED: | Multi beam effect each 1 x 3 W R/G/B |
| Moving light | |
| LED: | Scanner each 1 x 15 W cold white (CW) |
| Bar | |
| LED: | 4 x high-power 1 W ultra violett (UV) |
| Remote control | |
| Battery: | 1 x Button cell 3.0 V CR2025 lithium manganese |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| intended use: | show effect lighting |

EUROLITE QuickDMX USB Wireless Transmitter/Receiver

| | |
|--------------------|--|
| Power supply: | 5 V DC |
| IP classification: | IP20 |
| Power connection: | Mains input USB A (M) connectable version |
| DMX channels: | Input 512 Output 512 |
| DMX output: | 1 x USB, type A |
| Control: | DMX; QuickDMX built-in |
| Carrier frequency: | 2,4 GHz |
| Modulation: | GFSK |
| Parallel mode: | Max. 6 transmitter |
| Color: | Black |
| Dimensions: | Width: 8,6 cm Depth: 4 cm Height: 1,1 cm |
| Weight: | 10 g |

EUROLITE QuickDMX Wireless Transmitter

| | |
|--------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz 5 V DC 1 A |
| IP classification: | IP20 |
| Power connection: | Mains input Coaxial power connector (M) Power supply cord with AC adapter (provided) |
| DMX channels: | Output 512 |
| DMX input: | 1 x 3-pin XLR (M) |
| Control: | QuickDMX built-in; DMX |
| Carrier frequency: | 2,4 GHz |
| Modulation: | GFSK |
| Parallel mode: | Max. 6 transmitter |
| Range: | 400 m |
| Color: | Silver |
| Dimensions: | Length: 21,2 cm Diameter: Ø 1,8 cm |
| Weight: | 150 g |

EUROLITE DMX LED Color Chief Controller

| | |
|--------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz 9 V DC 800 mA |
| Power consumption: | 10 W |
| IP classification: | IP20 |
| Power connection: | Mains input Coaxial power connector (M) Power supply cord with AC adapter (provided) |
| Programs: | Programmable 24 Sequences |
| DMX channels: | Output 240 |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Control: | DMX; Sound to light via RCA (F) mounting version; Sound to light via Microphone |
| Housing color: | Black |
| Available storage media: | USB devices (FAT 32) |
| USB port: | Typ A |
| Color: | Black |
| Housing design: | (19") 48.3 cm rack installation 3 U |
| Dimensions: | Width: 48,3 cm Depth: 13,35 cm Height: 8,5 cm |
| Weight: | 2,25 kg |

EUROLITE STV-60-WOT EU Steel Stand black

| | |
|----------------------------|------------------------------------|
| Maximum carrying capacity: | 30 kg |
| Height: | Maximum: 315 cm Minimum: 150 cm |
| Attachment system: | TV spigot Ø 28mm |
| Type (general stands): | Light stand/manual |
| Material: | Steel/magnesium |
| Color: | Black |
| Transport dimensions: | 1,26 m x 12 cm x 15 cm |
| Weight: | 5,65 kg |