



The article is no longer in our assortment.

Features:

EUROLITE LED TL-3 RGB+UV Trusslight

Variable truss light and uplight with bright 3 x 7 W RGB+UV LED

- Compact and bright
- Perfect for ALUTRUSS 3-POINT SYSTEM DECOLOCK DQ3
- Color change adjustable; Dimmer electronic; color blend stepless
- UV effect; Strobe effect
- 2 integrated show programs
- Direct color selection for 17 preset colors
- Control via IR remote control; stand-alone; DMX; Master/slave function; Sound to light via Microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 16°
- 4 digit 7-segment LED display
- For application areas such as: Clubs/dancing school; Wedding/gala/events; Stage; mobile djs / entertainer
- The device is cooled by passive convection cooling
- Preprogrammed in LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
- Rubber feet
- Mains input and output for power linking up to 8 units
- Very quiet working noise
- Application possibility: Standing; suspended

Package contents

- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

Logistic

EAN / GTIN: 4026397690989

Weight: 10,00 kg

Length: 0.54 m

Width: 0.53 m

Height: 0.45 m

ROADINGER Flightcase 4x TL-3 TCL

Trunk case, PRO version

- With accessory compartment
- High-quality workmanship with birch multiplex 7 mm, black, laminated
- Interior with foam padding
- Rugged carrying handle
- 2 chrome tip-over locks
- Made in Germany
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	8,36 kg
---------	---------

EUROLITE LED TL-3 RGB+UV Trusslight

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	15 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	F 1 A Fuse replaceable
Lamp type:	LED lamp
Flash rate:	1 - 20 Hz
DMX channels:	3; 4; 4; 8
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	IR remote control; stand-alone; DMX; Master/slave function; Sound to light via Microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	16°
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	33°
Housing color:	Black
Attachment system:	M10 thread
Display type:	4 digit 7-segment LED display

Transport aid:	Rubber feet
Material:	Metal
Dimensions:	Width: 12,2 cm Depth: 10,8 cm Height: 11,7 cm
Weight:	890 g
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Photobiological safety:	Risk Group 0
Power cord	
Cable construction:	3 x 0,75 mm² H05VV-F
Cable length:	Approx. 1,1 m
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x TL-3 TCL

Maximum load:	25 kg
Carrying handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Material:	Birch multiplex, 7 mm
Color:	Black, laminated
Compartment dimensions:	12,5 cm x 11,5 cm x 9,5 cm
Accessory compartment:	12,5 cm x 28 cm x 10,5 cm
Inside dimensions:	37,5 cm x 28 cm x 10,5 cm
Dimensions:	Width: 47 cm Depth: 31 cm Height: 18 cm
Weight:	4,80 kg