



**List price: 1248.31 €**

incl. 19% VAT.

### Features:

#### EUROLITE AKKU IP Flat Light 3 bk

Flat IP65 spotlight in black with 3 x 8 W 4in1 QCL RGBW LED, QuickDMX transceiver

- Integrated QuickDMX transceiver for wireless DMX control
- Battery operation up to 16h depending on program used
- 3 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- The device is cooled by passive convection cooling
- Control via master/slave function; IR remote control; QuickDMX; stand-alone; sound to light via microphone
- Flicker-free
- With a beam angle of 15°
- With mounting bracket
- LCD display
- Suitable for outdoor use IP65
- For application areas such as: Small rental; rental; wedding/gala/events; mobile djs / entertainer
- Dimmer electronic; Dimmer speed (step response) adjustable; color blend stepless; color change adjustable; colors preset
- Strobe effect
- Cordless, flexible and versatile
- Integrated automatic charging of the battery and status indicator
- Preprogrammed in Light´J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
- Silent operation
- Application possibility: Standing

#### Package contents

- 1 x device, 1 x external mains adapter, 1 x power cord, 1 x remote control, 1 x battery, 1 x declaration of conformity, 1 x user manual

### Logistic

EAN / GTIN: 4026397626629

Weight: 9,50 kg

Length: 0.46 m

Width: 0.36 m

Height: 0.27 m

### EUROLITE Charger 4x Akku Flat Light Series

Power supply with cable for simultaneous charging of 4 x AKKU Flat Light 1/3

- Package contents
- 1 x charger, 1 x power cord, 1 x adapter cable

### EUROLITE SB-14 Soft Bag

Practical black soft bag, divided into 4 compartments, for 4 AKKU Flat Lights

- With 2 Outside pockets
- With 4 compartments
- High-quality workmanship with nylon , black, water repellent
- Interior with foam padding
- 2 carrying straps

### Technical specifications:

Weight: 7,27 kg

### EUROLITE AKKU IP Flat Light 3 bk

|                         |  |
|-------------------------|--|
| Power supply:           | 100-240 V AC, 50/60 Hz<br>12,6V DC 2500 mA   |
| IP classification:      | IP65   |
| Protection class:       | Protection class III   |
| Power connection:       | Mains input via coaxial power connector (M)<br>mounting version power supply cord with Euro<br>plug (provided)<br>Battery/battery pack |
| Battery pack type:      | 2 x lithium ion 11,1 V, 2600 mAh, 28,86 Wh   |
| Battery pack:           | Battery operation up to 16h depending on<br>program used<br>Recharging time 4h   |
| Lamp type:              | LED lamp   |
| LED type:               | 3 x 8 W high-power 4in1 QCL RGBW<br>(homogenous color mix)   |
| Flash rate:             | 1 - 23 Hz  |
| DMX channels:           | 3; 4; 6; 8; 10   |
| Cooling:                | Passive convection cooling   |
| Control:                | Master/slave function; IR remote control;<br>QuickDMX; stand-alone; sound to light via<br>microphone                                   |
| Preprogrammed in:       | Light´J; Light Captain; EASY SHOW 1; EASY<br>SHOW 2; EASY SHOW 3; Colorchief   |
| Projection:             | Flicker-free   |
| Carrier frequency:      | 2,4 GHz  |
| Beam angle:             | 15°  |
| Beam angle (1/2 peak):  | 15°  |
| Beam angle (1/10 peak): | 33°  |

|                       |   |
|-----------------------|---|
| Housing color:        | Black   |
| Attachment system:    | Mounting bracket  |
| Display type:         | LCD display   |
| Dimensions:           | Width: 17,2 cm<br>Depth: 13,8 cm<br>Height: 6,2 cm      |
| Weight:               | 1,61 kg   |
| Noise classification: | Class 0 (no noise at all)                               |
| Remote control        |   |
| Battery:              | 1 x button cell 3.0 V CR2032 lithium manganese built-in |
| Legal specifications  |   |
| Special product:      | Not designed for household room illumination            |
| Intended use:         | Show effect lighting                                    |

#### **EUROLITE Charger 4x Akku Flat Light Series**

|                   |  |
|-------------------|--|
| Power supply:     | 100-240 V AC, 50/60 Hz<br>12,6V DC 6000 mA   |
| Power connection: | Mains input via C8 (M) "figure 8" mounting version power supply cord with Euro plug (provided) |
| Power output:     | 4 x coaxial power connector (F)  |
| Weight:           | 0,49 kg  |

#### **EUROLITE SB-14 Soft Bag**

|                 |   |
|-----------------|---|
| Carrying strap: | 2 pc/pcs                                      |
| Material:       | Nylon   |
| Color:          | Black, water repellent                        |
| Dimensions:     | Width: 28 cm<br>Depth: 22 cm<br>Height: 18 cm |
| Weight:         | 0,34 kg                                       |