



### Features:

#### EUROLITE AKKU IP Flat Light 3 bk

Flat IP65 spotlight in black with 3 x 8 W 4in1 QCL RGBW LED, QuickDMX transceiver

- Integrated QuickDMX transceiver for wireless DMX control
- Cordless, flexible and versatile
- Battery operation up to 16h depending on program used
- Integrated automatic charging of the battery and status indicator
- 3 LEDs 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
- Dimmer electronic; Dimmer speed (step response) adjustable; color blend stepless; color change adjustable; colors preset
- Strobe effect
- The device is cooled by passive convection cooling
- Control via master/slave function; IR remote control; QuickDMX; stand-alone; sound to light via microphone
- Fixtures available for Light´J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 15°
- With mounting bracket
- LCD display
- Suitable for outdoor use IP65
- For application areas such as: Decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels
- Silent operation
- Application possibility: Standing

### Logistic

EAN / GTIN: 4026397626629

Weight: 9,50 kg

Length: 0.46 m

Width: 0.36 m

Height: 0.27 m

## EUROLITE SB-14 Soft Bag

Practical black soft bag, divided into 4 compartments, for 4 AKKU Flat Lights

- With 2 Outside pockets
- With 4 compartments
- High-quality workmanship with nylon , black, water repellent
- Interior with foam padding
- 2 carrying straps

## Technical specifications:

---

Weight: 7.27 kg

---

## EUROLITE AKKU IP Flat Light 3 bk

Power supply:	100-240 V AC, 50/60 Hz 12.6V DC 2500 mA
IP classification:	IP65
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with Euro plug (provided) Battery/battery pack
Battery pack type:	2 x lithium ion 11.1 V, 2600 mAh, 28.86 Wh
Battery pack:	Battery operation up to 16h depending on program used Recharging time 4h
Lamp type:	LED lamp
LED type:	3 x 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 10
Cooling:	Passive convection cooling
Control:	Master/slave function; IR remote control; QuickDMX; stand-alone; sound to light via microphone
Fixtures available for:	Light J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Carrier frequency:	2.4 GHz
Beam angle:	15°
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	33°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Dimensions:	Width: 17.2 cm

	Depth: 13.8 cm
	Height: 6.2 cm
Weight:	1.61 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **EUROLITE Charger 4x Akku Flat Light Series**

Power supply:	100-240 V AC, 50/60 Hz 12.6V DC 6000 mA
Power connection:	Mains input via C8 (M) "figure 8" mounting version power supply cord with Euro plug (provided)
Power output:	4 x coaxial power connector (F)
Weight:	0.49 kg

#### **EUROLITE SB-14 Soft Bag**

Carrying strap:	2 pc/pcs
Material:	Nylon
Color:	Black, water repellent
Dimensions:	Width: 28 cm Depth: 22 cm Height: 18 cm
Weight:	0.34 kg

#### **Scope of delivery:**

##### **4 x EUROLITE AKKU IP Flat Light 3 bk**

- 1 x device
- 1 x external mains adapter
- 1 x power cord
- 1 x remote control
- 1 x battery
- 1 x declaration of conformity
- 1 x user manual

##### **1 x EUROLITE Charger 4x Akku Flat Light Series**

- 1 x charger
- 1 x power cord
- 1 x adapter cable