

EUROLITE Set LED KLS-180 wh + LED B-40 wh + USB QuickDMX + Easy Show No.: 2000866

GTIN: 4026397693799



List price: 1129.31 €

incl. 19% VAT.

Features:

EUROLITE LED KLS-180 Compact Light Set wh

Bar with 4 RGBW spots and 4 white strobe LEDs, with QuickDMX connector (XLR)

- Crossbar with integrated DMX control unit and stand sleeve
- Ultra-light, ideally suited for mobile use
- Ideal for bands, mobile DJs and stages
- Suited for installation on a speaker stand (not included) or truss
- Comes pre-assembled with practical transport bag
- Movable and tiltable spotlights
- Each spot can be individually controlled via DMX
- Supports QuickDMX - the wireless DMX system from Eurolite
- Built-in phantom-powered socket for QuickDMX receivers (optional)
- Stepless color blend, color change, preset colors, dimmer and strobe effect
- Mains input and output for power linking up to 8 units
- 4 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- 4 powerful LEDs 1 W high-power cold white (CW)
- Can be operated in 3; 4; 8; 21 CH mode
- The device is cooled by passive convection
- Controlling by IR remote control (provided); stand-alone; DMX; Sound to light via Microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); IR remote control
- Preprogrammed in EASY SHOW; LED PC-Control 512; Light Captain
- Flicker-free projection
- With a beam angle of 9°
- With Mounting bracket
- For application areas such as: Wedding/gala

Logistic

EAN / GTIN: 4026397693799

Weight: 14,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.60 m

Bulky product

EUROLITE LED B-40 Laser Beam Effect wh

LED beam effect with RGBW color mixing and RG laser

- 2 laser diodes project hundreds of red and green laser beams
- Laser class 2M: does not require additional protective measures or appointment of a laser safety officer
- Stepless color blend, dimmer and strobe effect
- Rotation speed variably adjustable
- LEDs are distributed in 3 groups which can be controlled individually via DMX
- Supports QuickDMX - the wireless DMX system from Eurolite
- Mains input and output for power linking up to 8 units
- 5 powerful LEDs 8 W high-power 4in1 QCL RGBW
- 7 integrated Showprograms
- Can be operated in 3; 10; 22 CH mode
- The device is cooled by cooling fan at the Head; cooling fan at the Base
- Controlling by IR remote control; stand-alone; Sound to light via Microphone; DMX; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMx by LumenRadio via USB (optional); Sound to light
- Preprogrammed in LED PC-Control 512; EASY SHOW; Light Captain
- Effect: Laser; multi beam effect
- With Mounting bracket
- For application areas such as: Wedding/gala

EUROLITE EASY Show

Programmed DMX controller for over 200 spotlights from EUROLITE

- Easy-to-use DMX controller and DMX recorder
- Designed for DMX beginners with 200 programmed fixtures
- DMX recording function for your own projects, ideal for installations or rental companies
- Ideal for colored LED spotlights, KLS systems, moving lights and lighting effects
- No programming required, simply connect your spotlights and get started
- All spotlights can be freely combined to a show
- 12 color schemes and 24 chases directly available
- Controls for overall brightness, running speed, fade time and strobe effect
- Data storage on USB flash drives
- QuickDMX connector for wireless DMX connection
- Backlit LC display
- Compact desktop console
- Includes USB flash drive, USB plug-in power adapter and mounting brackets
- A list of all preset devices is available at www.steinigke.de
- Controlling by DMX; Sound to light via Microphone

EUROLITE QuickDMX USB Wireless Transmitter/Receiver

Wireless miniature DMX transceiver 2.4 GHz, phantom powered

- User-friendly USB plug with swivel antenna
- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to GFSK modulation with 78 channels, interference-free operation also alongside other QuickDMX receivers and wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- Simultaneous operation of up to 6 transmitters, thus control of 3072 DMX channels (6 DMX universes) possible
- LED indication for functions
- Transceiver, to be used as transmitter or receiver
- Requires 5 V phantom power for operation
- 2.4 GHz - license-free worldwide
- Can receive and process up to 512 DMX channels
- Can transmit up to 512 DMX channels
- Controlling by DMX; QuickDMX built-in; plug and play
- Use a operating range up to 400m with line of sight

Technical specifications:

Weight: 10,79 kg

EUROLITE LED KLS-180 Compact Light Set wh

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	80 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Fuse:	T 1 A
Lamp type:	LED lamp
LED:	Spot 4 x 8 W high-power 4in1 QCL RGBW (homogenous color mix) Strobe effect 4 x 1 W high-power cold white (CW)
Flash rate:	1 - 20 Hz
DMX channels:	3; 4; 8; 21
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection
Control:	IR remote control (provided); stand-alone; DMX; Sound to light via Microphone; EASY SHOW; LED PC-Control 512; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); Light Captain; IR remote control
Beam angle:	9°
Beam angle (1/2 peak):	9°
Housing color:	White
Attachment system:	Mounting bracket
Dimensions:	Width: 60,5 cm Depth: 14 cm Height: 23 cm
Weight:	5,10 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE LED B-40 Laser Beam Effect wh

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	65 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 1 A Fuse replaceable
Lamp type:	LED lamp
LED:	5 x 8 W high-power 4in1 QCL RGBW
Flash rate:	0 - 20 Hz
Laser class:	Class 2M
Laser color:	R/G
Laser module:	Green (G) 40 mW 532nm Red (R) 100 mW 650nm
DMX channels:	3; 10; 22
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan at the Head Cooling fan at the Base
Control:	IR remote control; stand-alone; Sound to light via Microphone; DMX; Master/slave function; LED PC-Control 512; EASY SHOW; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); Light Captain; Sound to light
Housing color:	White
Attachment system:	Mounting bracket
Dimensions:	Width: 31 cm Depth: 31 cm Height: 39 cm
Weight:	4,30 kg
Noise classification:	Class 2 (slight noise)

EUROLITE EASY Show

Power supply:	100-240 V AC, 50/60 Hz 5 V DC 250 mA
Power consumption:	1,25 W
IP classification:	IP20
Power connection:	Mains input via USB C (F) mounting version power supply cord with AC adapter
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Control:	DMX; Sound to light via Microphone

Housing color:	Black
Available storage media:	USB devices
Dimensions:	Width: 28,0 cm Depth: 14,5 cm Height: 6,0 cm
Weight:	1,35 kg

EUROLITE QuickDMX USB Wireless Transmitter/Receiver

Power supply:	5 V DC
IP classification:	IP20
Power connection:	Mains input via USB A (M) connectable version
DMX channels:	Input 512 Output 512
DMX output:	1 x USB, type A
Control:	DMX; QuickDMX built-in; plug and play
Carrier frequency:	2,4 GHz
Modulation:	GFSK
Parallel mode:	Max. 6 transmitter
Range:	400 m with line of sight
Color:	Black
Dimensions:	Width: 8,6 cm Depth: 4 cm Height: 1,1 cm
Weight:	10 g