



Features:

EUROLITE LED KLS-180 Compact Light Set wh

Bar with 4 RGBW spots and 4 white strobe LEDs, with QuickDMX connector (XLR)

- Crossbar with integrated DMX control unit and stand sleeve
- Compact lightweight
- Movable and tiltable spotlights
- Dimmer electronic; color blend stepless; color change adjustable; colors preset
- Strobe effect
- The device is cooled by passive convection cooling
- Control via IR remote control; stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for EASY SHOW 1; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Light J; Colorchief
- Flicker-free
- With a beam angle of 9°
- With mounting bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels
- Silent operation
- Application possibility: Suspended; on stand

spotlight

- 4 LEDs 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
4 spots controlled separately

bar

- 4 LEDs 1 W SMD 8072 cold white (CW)
 LEDs controlled separately

Logistic

EAN / GTIN: 4026397693799

Weight: 14,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.60 m

Bulky product

EUROLITE LED B-40 Laser Beam Effect wh

LED beam effect with RGBW color mixing and RG laser

- 2 laser diodes project hundreds of red and green laser beams
- 5 LEDs 8 W SMD 9080 4in1 QCL RGBW
3 segments controlled separately
- Rotation speed stepless; color blend stepless; Dimmer electronic
- Laser; multi beam effect; strobe effect
- Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer
- 7 integrated show programs
- The device is cooled by cooling fan at the head; cooling fan at the base
- Control via IR remote control; stand-alone; sound to light via microphone; DMX; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3; Light J; Colorchief
- With mounting bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; advertisement/Shop window
- Application possibility: Standing; suspended; on stand

EUROLITE EASY Show

Programmed DMX controller for over 200 spotlights from EUROLITE

- Easy-to-use DMX controller and DMX recorder
- Designed for DMX beginners with 200 programmed fixtures
- DMX recording function for your own projects, ideal for installations or rental companies
- Ideal for colored LED spotlights, KLS systems, moving lights and lighting effects
- No programming required, simply connect your spotlights and get started
- All spotlights can be freely combined to a show
- Data storage on USB flash drives
- A list of all preset devices is available at www.steinigke.de
- Program speed adjustable; color fade adjustable; Dimmer
- Strobe effect
- 24 integrated show programs
- Direct color selection for 12 preset colors
- Preprogrammed 24 scenes/chases and 12 cues
- Control via DMX; sound to light via microphone; QuickDMX via USB (optional)
- Monochrome LCD display
- Desktop console housing
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation

EUROLITE QuickDMX USB Wireless Transmitter/Receiver

Wireless miniature DMX transceiver 2.4 GHz, phantom powered

- User-friendly USB plug with swivel antenna
- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to GFSK modulation with 78 channels, interference-free operation also alongside other QuickDMX transceiver and wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- LED indication for functions
- Transceiver, to be used as transmitter or receiver
- Requires 5 V phantom power for operation
- Can receive and process up to 512 DMX channels
- Can transmit up to 512 DMX channels
- Control via DMX; QuickDMX; plug and play
- Operating range up to 400m with line-of-sight
- Up to 6 transmitters can be operated in parallel without interference

Technical specifications:

Weight: 10.79 kg

EUROLITE LED KLS-180 Compact Light Set wh

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	80 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Fuse:	T 1 A
Lamp type:	LED lamp
DMX channels:	3; 4; 8; 21
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	IR remote control; stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	EASY SHOW 1; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Light J; Colorchief
Projection:	Flicker-free
Beam angle:	9°
Beam angle (1/2 peak):	9°
Housing color:	White
Attachment system:	Ø 35mm Mounting bracket
Dimensions:	Width: 60.5 cm Depth: 14 cm Height: 23 cm
Weight:	5.10 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
LED type:	4 x 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
LED type:	4 x 1 W SMD 8072 cold white (CW)
Flash rate:	1 - 20 Hz

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE LED B-40 Laser Beam Effect wh

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	65 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	5 x 8 W SMD 9080 4in1 QCL RGBW
Flash rate:	0 - 20 Hz
Laser class:	2M
Laser color:	R/G
Laser module:	Green (G) 40 mW 532nm Red (R) 100 mW 650nm
DMX channels:	3; 10; 22
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan at the head Cooling fan at the base
Control:	IR remote control; stand-alone; sound to light via microphone; DMX; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3; Light J; Colorchief
Housing color:	White
Attachment system:	Mounting bracket
Dimensions:	Width: 31 cm Depth: 31 cm Height: 39 cm
Weight:	4.30 kg
Noise classification:	Class 2 (slight noise)

EUROLITE EASY Show

Power supply:	100-240 V AC, 50/60 Hz 5V DC 250 mA
Power consumption:	1.25 W
IP classification:	IP20

Power connection:	Mains input via USB C (W) mounting version power supply cord with AC adapter
Programs:	Preprogrammed 24 scenes/chases and 12 cues
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Control:	DMX; sound to light via microphone; QuickDMX via USB (optional)
Housing color:	Black
Display type:	Monochrome LCD display
Available storage media:	USB devices
Housing design:	Desktop console housing
Dimensions:	Width: 28.0 cm Depth: 14.5 cm Height: 6.0 cm
Weight:	1.35 kg
Noise classification:	Class 0 (no noise at all)

EUROLITE QuickDMX USB Wireless Transmitter/Receiver

Power supply:	5V DC
IP classification:	IP20
Power connection:	Mains input via USB A (M) connectable version
DMX channels:	Input 512 Output 512
DMX output:	1 x USB, type A
Control:	DMX; QuickDMX; plug and play
Range:	Range up to 400m with line-of-sight
Carrier frequency:	2.4 GHz
Parallel mode:	Max. 6 transmitter
RF power output:	19 dBm
Modulation:	GFSK
Color:	Black
Dimensions:	Width: 8.6 cm Depth: 4 cm Height: 1.1 cm
Weight:	0.01 kg

Scope of delivery:

1 x EUROLITE LED KLS-180 Compact Light Set wh

1 x device
1 x bag
1 x remote control
1 x battery
1 x power cord
1 x user manual

1 x EUROLITE LED B-40 Laser Beam Effect wh

1 x light effect
1 x user manual

1 x power cord
1 x remote control
1 x mounting bracket
4 x screw
4 x washer

1 x EUROLITE EASY Show

1 x controller
1 x user manual
1 x external mains adapter
2 x USB cable
2 x mounting bracket
4 x screw

3 x EUROLITE QuickDMX USB Wireless Transmitter/Receiver

1 x device
1 x user manual
1 x declaration of conformity