

EUROLITE Set 2x LED KLS Laser Bar PRO + Easy Show + 2x M-4 Speaker System Stand

GTIN: 4026397693812



List price: 1486.31 €

incl. 19% VAT.

Features:

EUROLITE LED KLS Laser Bar PRO FX Light Set

Bar with 2 strong derbies and spots, white/UV strobe LEDs, laser (RG, 2M)

- Enhanced version with very high brightness and additional UV LEDs
- Compact lightweight
- Crossbar with integrated DMX control unit and stand sleeve
- 2 laser diodes project hundreds of red and green laser beams
- 2 rotating derbies for mirror ball effects
- When fog is used, this effect becomes especially attractive
- For application areas such as: Wedding/gala/events; mobile use; clubs/dancing school; mobile djs / entertainer; rental
- 39 integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch; master/slave function
- With mounting bracket
- Mains input and output for power linking up to 8 units
- Laser; multi beam effect; flower effect; UV effect; strobe effect
- Preprogrammed in EASY SHOW 1; Light'J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Application possibility: On stand

lase

- Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer

spotlight

 6 powerful LEDs 6 W high-power 3in1 TCL RGB (homogenous color mix)
 spots controlled separately

Logistic

EAN / GTIN: 4026397693812

Weight: 36,00 kg Length: 1.20 m Width: 0.80 m Heigth: 1.50 m Bulky product - With a beam angle of 13°

light effect

- 6 powerful LEDs 2 W high-power R/G/B
 spots controlled separately

hai

 4 powerful LEDs 2 W high-power 2in1 BCL CW/UV (homogenous color mix)
 LEDs controlled separately

Package contents

1 x device, 1 x power cord, 1 x user manual, 1 x declaration of conformity, 1 x remote control, 1 x foot control, 2 x knurled screw, 2 x washer, 2 x mounting bracket, 2 x battery, 1 x bag

EUROLITE EASY Show

Programmed DMX controller for over 200 spotlights from EUROLITE

- Easy-to-use DMX controller and DMX recorder
- Designed for DMX beginners with 200 programmed fixtures
- DMX recording function for your own projects, ideal for installations or rental companies
- Ideal for colored LED spotlights, KLS systems, moving lights and lighting effects
- No programming required, simply connect your spotlights and get started
- All spotlights can be freely combined to a show
- Data storage on USB flash drives
- A list of all preset devices is available at www.steinigke.de
- Program speed adjustable; color fade adjustable; Dimmer
- Strobe effect
- 24 integrated show programs
- Direct color selection for 12 preset colors
- Control via DMX; sound to light via microphone; QuickDMX via USB (optional)
- Desktop console housing
- Monochrome LCD display
- Preprogrammed 24 scenes/chases and 12 cues
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer; restaurants, bars and hotels; installation
- Silent operation

Package contents

 1 x controller, 1 x user manual, 1 x external mains adapter, 2 x USB cable, 2 x mounting bracket, 4 x screw

OMNITRONIC M-4 Speaker-System Stand

Aluminum speaker stand, height adjustable 140-345 cm, maximum load 18 kg

- Durable aluminum version
- Tube diameter: Ø 35 mm
- Adjustable height

Package contents

- 1 x user manual

Technical specifications:		
Weight:	27,95 kg	

EUROLITE LED KLS Laser Bar PRO FX Light Set

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	150 W
IP classification:	IP20
Protection class:	Protection class I

Power output: 1 x IEC connector (F) mounting version Fuse: 5 x 20 mm, T 3,15 A Lamp type: LED lamp DMX channels: 3; 5; 10; 28 DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Cooling fan Control: Stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch; master/slave function Preprogrammed in: EASY SHOW 1; Light J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchiel Housing color: Black Attachment system: 2x mounting bracket Dimensions: Width: 1,030 cm Depth: 6,1 cm Helight: 38,7 cm Weight: 10,00 kg Noise classification: Class 2 (slight noise) Power cord Class 2 (slight noise) Cable length: 3 m Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Foot control Battery: 1 x 9.0 V E block 6F22 zinc carbon included Laser Laser color: R/G Laser of ass: 2M	Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type: LED lamp DMX channels: 3; 5; 10; 28 DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Cooling fan Control: Stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch; master/slave function Preprogrammed in: LSAY SHOW 1; Light*, LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Housing color: Black Attachment system: 2x mounting bracket Dimensions: Width: 1,030 cm Depth: 6.1 cm Height: 38,7 cm Weight: 10,00 kg Noise classification: Class 2 (slight noise) Power cord Cable length: 3 m Remote control Battery: 1 x button cell 3.0 V CR2026 lithium manganese built-in Foot control Battery: 1 x 9.0 V E block 6F22 zinc carbon included Laser Laser class: 2M Laser module: Red (R) 100 mW 650nm Green (G) 30 mW 532nm Light effect LED type: 6 x 2 W high-power R/G/B Flash rate: 0 - 30 Hz Spottlight LED typ	Power output:	1 x IEC connector (F) mounting version
DMX channels: 3; 5; 10; 28 DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Cooling fan Control: Stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch; master/size function Preprogrammed in: EASY SHOW 1; Light U; LED PC-Control 512; Light Capitain; EASY SHOW 2; EASY SHOW 3; Colorchief Housing color: Black Attachment system: 2x mounting bracket Dimensions: Width: 1,030 cm Depth: 6,1 cm Height: 38,7 cm Weight: 10,00 kg Noise classification: Class 2 (slight noise) Power cord Cable length: 3 m Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Foot control Battery: 1 x 9.0 V E block 6F22 zinc carbon included Laser Laser Laser color: R/G Laser module: Red (R) 100 mW 650nm Green (G) 30 mW 532nm Green (G) 30 mW 532nm Light effect LED type: 6 x 2 W high-power 3in1 TCL RGB (homogenous color mix)	Fuse:	5 x 20 mm, T 3,15 A
DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Cooling fan Control: Stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch; master/slave function Preprogrammed in: EASY SHOW 1; Light 'J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Housing color: Black Attachment system: 2x mounting bracket Dimensions: Width: 1,030 cm Depth: 6,1 cm Height: 38,7 cm Weight: 10,00 kg Noise classification: Class 2 (slight noise) Power cord Cable length: Cable length: 3 m Remote control Battery: Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Foot control Battery: Laser 1 x 9.0 V E block 6F22 zinc carbon included Laser Laser class: Laser module: Red (R) 100 mW 650mm Green (G) 30 mW 532nm Light effect LED type: 6 x 2 W high-power R/G/B LED type: 6 x 2 W high-power 3in1 TCL RGB (homogenous color mix) Beam angle: <	Lamp type:	LED lamp
DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Cooling fan Control: Stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch; master/slave function Preprogrammed in: EASY SHOW 1; Light 'J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Housing color: Black Attachment system: 2x mounting bracket Dimensions: Width: 1,030 cm Depth: 6,1 cm Height: 38,7 cm Weight: 10,00 kg Noise classification: Class 2 (slight noise) Power cord Class 2 (slight noise) Cable length: 3 m Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Foot control Battery: 1 x 9.0 V E block 6F22 zinc carbon included Laser Laser Laser color: R/G Laser module: Red (R) 100 mW 650nm Green (G) 30 mW 532nm Light effect LED type: 6 x 2 W high-power 3in1 TCL RGB (homogenous color mix) LED type: 6 x 6 W high-power 3in1 TCL RGB (homogenous color mix) Beam angle (1/10 peak): 20° Bar 4 x 2 W	DMX channels:	3; 5; 10; 28
Cooling: Control: Stand-alone: DMX; IR remote control; sound to light via microphone; wireless footswitch; master/slave function Preprogrammed in: EASY SHOW 1; Light 'J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Housing color: Black Attachment system: 2x mounting bracket Dimensions: Width: 1,030 cm Depth: 6,1 cm Height: 38,7 cm Weight: 10,00 kg Noise classification: Class 2 (slight noise) Power cord Cable length: 3 m Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Foot control Battery: 1 x 9.0 V E block 6F22 zinc carbon included Laser Laser color: R/G Laser module: Red (R) 100 mW 650nm Green (G) 30 mW 532nm Light effect LED type: 6 x 2 W high-power R/G/B Flash rate: 0 - 30 Hz Spotlight LED type: 6 x 6 W high-power 3in1 TCL RGB (homogenous color mix) Beam angle (1/10 peak): Beam angle (1/10 p	DMX input:	1 x 3-pin XLR (M) mounting version
Control: Stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch; master/slave function Preprogrammed in: EASY SHOW 1; Light 'J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Housing color: Black Attachment system: 2x mounting bracket Dimensions: Width: 1,030 cm	DMX output:	1 x 3-pin XLR (F) mounting version
light via microphone; wireless footswitch; master/slave function Preprogrammed in: EASY SHOW 1; Light 'J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Housing color: Black Attachment system: 2x mounting bracket Dimensions: Width: 1,030 cm	Cooling:	Cooling fan
Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief	Control:	light via microphone; wireless footswitch;
Attachment system: 2x mounting bracket	Preprogrammed in:	Light Captain; EASY SHOW 2; EASY SHOW 3;
Dimensions: Width: 1,030 cm Depth: 6,1 cm Height: 38,7 cm Weight: 10,00 kg Noise classification: Class 2 (slight noise) Power cord Cable length: Cable length: 3 m Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Foot control Foot control Battery: 1 x 9.0 V E block 6F22 zinc carbon included Laser Laser class: Laser class: 2M Laser module: Red (R) 100 mW 650nm Green (G) 30 mW 532nm Light effect LED type: LED type: 6 x 2 W high-power R/G/B Flash rate: 0 - 30 Hz Spotlight LED type: 6 x 6 W high-power 3in1 TCL RGB (homogenous color mix) Beam angle: 13° Beam angle (1/12 peak): 13° Beam angle (1/10 peak): 20° Bar LED type: 4 x 2 W high-power 2in1 BCL CW/UV (homogenous color mix)	Housing color:	Black
Depth: 6,1 cm	Attachment system:	2x mounting bracket
Height: 38,7 cm	Dimensions:	Width: 1,030 cm
Weight: 10,00 kg Noise classification: Class 2 (slight noise) Power cord Cable length: 3 m Remote control 1 x button cell 3.0 V CR2025 lithium manganese built-in Foot control Battery: 1 x 9.0 V E block 6F22 zinc carbon included Laser Laser class: 2M Laser color: R/G Laser module: Red (R) 100 mW 650nm Green (G) 30 mW 532nm Light effect LED type: 6 x 2 W high-power R/G/B Flash rate: 0 - 30 Hz Spotlight LED type: 6 x 6 W high-power 3in1 TCL RGB (homogenous color mix) Beam angle: 13° Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar LED type: 4 x 2 W high-power 2in1 BCL CW/UV (homogenous color mix)		
Noise classification: Class 2 (slight noise) Power cord 3 m Remote control 1 x button cell 3.0 V CR2025 lithium manganese built-in Foot control 1 x 9.0 V E block 6F22 zinc carbon included Battery: 1 x 9.0 V E block 6F22 zinc carbon included Laser 2M Laser color: R/G Laser module: Red (R) 100 mW 650nm Green (G) 30 mW 532nm Light effect LED type: LED type: 6 x 2 W high-power R/G/B Flash rate: 0 - 30 Hz Spotlight LED type: LED type: 6 x 6 W high-power 3in1 TCL RGB (homogenous color mix) Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar LED type: 4 x 2 W high-power 2in1 BCL CW/UV (homogenous color mix)		-
Power cord Cable length: 3 m Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Foot control Battery: 1 x 9.0 V E block 6F22 zinc carbon included Laser Laser class: 2M Laser color: R/G Laser module: Red (R) 100 mW 650nm Green (G) 30 mW 532nm Light effect LED type: 6 x 2 W high-power R/G/B Flash rate: 0 - 30 Hz Spotlight LED type: 6 x 6 W high-power 3in1 TCL RGB (homogenous color mix) Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar LED type: 4 x 2 W high-power 2in1 BCL CW/UV (homogenous color mix)		
Cable length: 3 m Remote control 1 x button cell 3.0 V CR2025 lithium manganese built-in Foot control 1 x 9.0 V E block 6F22 zinc carbon included Battery: 1 x 9.0 V E block 6F22 zinc carbon included Laser 2M Laser color: R/G Laser module: Red (R) 100 mW 650nm Green (G) 30 mW 532nm Light effect LED type: LED type: 6 x 2 W high-power R/G/B Flash rate: 0 - 30 Hz Spotlight LED type: LED type: 6 x 6 W high-power 3in1 TCL RGB (homogenous color mix) Beam angle: 13° Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar LED type: 4 x 2 W high-power 2in1 BCL CW/UV (homogenous color mix)		Class 2 (slight noise)
Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Foot control Battery: 1 x 9.0 V E block 6F22 zinc carbon included Laser Laser class: 2M Laser color: R/G Laser module: Red (R) 100 mW 650nm Green (G) 30 mW 532nm Light effect LED type: 6 x 2 W high-power R/G/B Flash rate: 0 - 30 Hz Spotlight LED type: 6 x 6 W high-power 3in1 TCL RGB (homogenous color mix) Beam angle: 13° Beam angle (1/12 peak): 13° Beam angle (1/10 peak): 20° Bar LED type: 4 x 2 W high-power 2in1 BCL CW/UV (homogenous color mix)		
Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Foot control Battery: 1 x 9.0 V E block 6F22 zinc carbon included Laser Laser class: 2M Laser color: R/G Laser module: Red (R) 100 mW 650nm Green (G) 30 mW 532nm Light effect LED type: 6 x 2 W high-power R/G/B Flash rate: 0 - 30 Hz Spotlight LED type: 6 x 6 W high-power 3in1 TCL RGB (homogenous color mix) Beam angle: 13° Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar LED type: 4 x 2 W high-power 2in1 BCL CW/UV (homogenous color mix)		3 m
built-in		
Battery: 1 x 9.0 V E block 6F22 zinc carbon included Laser Laser class: 2M Laser color: R/G Laser module: Red (R) 100 mW 650nm Green (G) 30 mW 532nm Light effect LED type: 6 x 2 W high-power R/G/B Flash rate: 0 - 30 Hz Spotlight LED type: 6 x 6 W high-power 3in1 TCL RGB (homogenous color mix) Beam angle: 13° Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar LED type: 4 x 2 W high-power 2in1 BCL CW/UV (homogenous color mix)	Battery:	
Laser Laser class: 2M Laser color: R/G Laser module: Red (R) 100 mW 650nm Green (G) 30 mW 532nm Light effect ED type: LED type: 6 x 2 W high-power R/G/B Flash rate: 0 - 30 Hz Spotlight EED type: LED type: 6 x 6 W high-power 3in1 TCL RGB (homogenous color mix) Beam angle: 13° Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar 4 x 2 W high-power 2in1 BCL CW/UV (homogenous color mix)	Foot control	
Laser class: 2M Laser color: R/G Laser module: Red (R) 100 mW 650nm Green (G) 30 mW 532nm Light effect ED type: LED type: 6 x 2 W high-power R/G/B Flash rate: 0 - 30 Hz Spotlight ED type: LED type: 6 x 6 W high-power 3in1 TCL RGB (homogenous color mix) Beam angle: 13° Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar 4 x 2 W high-power 2in1 BCL CW/UV (homogenous color mix)	Battery:	1 x 9.0 V E block 6F22 zinc carbon included
Laser color: Red (R) 100 mW 650nm Green (G) 30 mW 532nm Light effect LED type: 6 x 2 W high-power R/G/B Flash rate: 0 - 30 Hz Spotlight LED type: 6 x 6 W high-power 3in1 TCL RGB (homogenous color mix) Beam angle: 13° Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar LED type: 4 x 2 W high-power 2in1 BCL CW/UV (homogenous color mix)	Laser	
Laser module: Red (R) 100 mW 650nm Green (G) 30 mW 532nm Light effect LED type: 6 x 2 W high-power R/G/B Flash rate: 0 - 30 Hz Spotlight LED type: 6 x 6 W high-power 3in1 TCL RGB (homogenous color mix) Beam angle: 13° Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar LED type: 4 x 2 W high-power 2in1 BCL CW/UV (homogenous color mix)	Laser class:	2M
Light effect LED type: 6 x 2 W high-power R/G/B Flash rate: 0 - 30 Hz Spotlight LED type: 6 x 6 W high-power 3in1 TCL RGB (homogenous color mix) Beam angle: 13° Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar LED type: 4 x 2 W high-power 2in1 BCL CW/UV (homogenous color mix)	Laser color:	R/G
LED type: 6 x 2 W high-power R/G/B Flash rate: 0 - 30 Hz Spotlight LED type: 6 x 6 W high-power 3in1 TCL RGB (homogenous color mix) Beam angle: 13° Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar LED type: 4 x 2 W high-power 2in1 BCL CW/UV (homogenous color mix)	Laser module:	
Flash rate: 0 - 30 Hz Spotlight LED type: 6 x 6 W high-power 3in1 TCL RGB (homogenous color mix) Beam angle: 13° Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar LED type: 4 x 2 W high-power 2in1 BCL CW/UV (homogenous color mix)	Light effect	
Spotlight LED type: 6 x 6 W high-power 3in1 TCL RGB (homogenous color mix) Beam angle: 13° Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar LED type: 4 x 2 W high-power 2in1 BCL CW/UV (homogenous color mix)	LED type:	6 x 2 W high-power R/G/B
LED type: 6 x 6 W high-power 3in1 TCL RGB (homogenous color mix) Beam angle: 13° Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar LED type: 4 x 2 W high-power 2in1 BCL CW/UV (homogenous color mix)	Flash rate:	0 - 30 Hz
color mix) Beam angle: 13° Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar LED type: 4 x 2 W high-power 2in1 BCL CW/UV (homogenous color mix)	Spotlight	
Beam angle (1/2 peak): Beam angle (1/10 peak): Bar LED type: 4 x 2 W high-power 2in1 BCL CW/UV (homogenous color mix)	LED type:	
Beam angle (1/10 peak): 20° Bar LED type: 4 x 2 W high-power 2in1 BCL CW/UV (homogenous color mix)	Beam angle:	13°
Bar LED type: 4 x 2 W high-power 2in1 BCL CW/UV (homogenous color mix)	Beam angle (1/2 peak):	13°
LED type: 4 x 2 W high-power 2in1 BCL CW/UV (homogenous color mix)	Beam angle (1/10 peak):	20°
(homogenous color mix)	Bar	
Flash rate: 0 - 30 Hz	LED type:	
	Flash rate:	0 - 30 Hz

EUROLITE EASY Show

Power supply:	100-240 V AC, 50/60 Hz
	5V DC 250 mA
Power consumption:	1,25 W
IP classification:	IP20
Power connection:	Mains input via USB C (W) mounting version power supply cord with AC adapter
Programs:	Preprogrammed 24 scenes/chases and 12 cues
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Control:	DMX; sound to light via microphone; QuickDMX via USB (optional)
Housing color:	Black
Display type:	Monochrome LCD display
Available storage media:	USB devices
Housing design:	Desktop console housing
Dimensions:	Width: 28,0 cm
	Depth: 14,5 cm
	Height: 6,0 cm
Weight:	1,35 kg
Noise classification:	Class 0 (no noise at all)

OMNITRONIC M-4 Speaker-System Stand

Maximum carrying capacity:	18 kg
Tube diameter sector:	38 - 35 mm
Height:	Maximum: 345 cm Minimum: 140 cm Adjustable in 10 steps with locking pin
Attachment system:	Ø 35mm
Type (general stands):	Speaker stand/manual
Material:	Aluminum
Color:	Black
Transport dimensions:	140 cm x 13,5 cm
Weight:	3,30 kg