

## EUROLITE Set 2x LED KLS Laser Bar PRO + Easy Show + 2x M-4 Speaker System Stand

GTIN: 4026397693812



### Features:

#### EUROLITE LED KLS Laser Bar PRO FX Light Set

Bar with 2 strong derbies and spots, white/UV strobe LEDs, laser (RG, 2M)

- Enhanced version with very high brightness and additional UV LEDs
  - Compact lightweight
  - Crossbar with integrated DMX control unit and stand sleeve
  - 2 laser diodes project hundreds of red and green laser beams
  - 2 rotating derbies for mirror ball effects
  - When fog is used, this effect becomes especially attractive
  - Laser; multi beam effect; flower effect; UV effect; strobe effect
  - 39 integrated show programs
  - The device is cooled by cooling fan
  - Control via stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch; master/slave function
  - Fixtures available for EASY SHOW 1; Light´J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
  - With mounting bracket
  - Mains input and output for power linking up to 8 units
  - For application areas such as: Clubs/dancing school; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels
  - Application possibility: Suspended; on stand
- laser**
- Laser class 2M <BR> does not require additional protective measures or appointment of a laser safety officer
- spotlight**
- 6 LEDs 6 W SMD 8072 3in1 TCL RGB (homogenous color mix)<BR> spots controlled separately

### Logistic

EAN / GTIN: 4026397693812

Weight: 36,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 1.50 m

Bulky product

- With a beam angle of 13°  
**light effect**
- 6 LEDs 2 W SMD 8072 R/G/B<BR> spots controlled separately  
**bar**
- 4 LEDs 2 W SMD 8072 2in1 BCL CW/UV (homogenous color mix)<BR> LEDs controlled separately

### EUROLITE EASY Show

Programmed DMX controller for over 200 spotlights from EUROLITE

- Easy-to-use DMX controller and DMX recorder
- Designed for DMX beginners with 200 programmed fixtures
- DMX recording function for your own projects, ideal for installations or rental companies
- Ideal for colored LED spotlights, KLS systems, moving lights and lighting effects
- No programming required, simply connect your spotlights and get started
- All spotlights can be freely combined to a show
- Data storage on USB flash drives
- A list of all preset devices is available at [www.steinigke.de](http://www.steinigke.de)
- Program speed adjustable; color fade adjustable; Dimmer
- Strobe effect
- 24 integrated show programs
- Direct color selection for 12 preset colors
- Preprogrammed 24 scenes/chases and 12 cues
- Control via DMX; sound to light via microphone; QuickDMX via USB (optional)
- Monochrome LCD display
- Desktop console housing
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation

### OMNITRONIC M-4 Speaker-System Stand

Aluminum speaker stand, height adjustable 140-345 cm, maximum load 18 kg

- Durable aluminum version
- Tube diameter: Ø 35 mm
- Adjustable height

### Technical specifications:

---

|         |          |
|---------|----------|
| Weight: | 27.95 kg |
|---------|----------|

---

### EUROLITE LED KLS Laser Bar PRO FX Light Set

|                    |                                                                                                  |
|--------------------|--------------------------------------------------------------------------------------------------|
| Power supply:      | 100-240 V AC, 50/60 Hz                                                                           |
| Power consumption: | 150 W                                                                                            |
| IP classification: | IP20                                                                                             |
| Protection class:  | Protection class I                                                                               |
| Power connection:  | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output:      | 1 x IEC connector (F) mounting version                                                           |
| Fuse:              | 5 x 20 mm, T 3.15 A                                                                              |
| Lamp type:         | LED lamp                                                                                         |
| DMX channels:      | 3; 5; 10; 28                                                                                     |

|                         |                                                                                                                |
|-------------------------|----------------------------------------------------------------------------------------------------------------|
| DMX input:              | 1 x 3-pin XLR (M) mounting version                                                                             |
| DMX output:             | 1 x 3-pin XLR (F) mounting version                                                                             |
| Cooling:                | Cooling fan                                                                                                    |
| Control:                | Stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch; master/slave function |
| Fixtures available for: | EASY SHOW 1; Light´J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief                  |
| Housing color:          | Black                                                                                                          |
| Attachment system:      | Tube: 1x Ø 35mm<br>2x mounting bracket                                                                         |
| Dimensions:             | Width: 1.030 cm<br>Depth: 6.1 cm<br>Height: 38.7 cm                                                            |
| Weight:                 | 10.00 kg                                                                                                       |
| Noise classification:   | Class 2 (slight noise)                                                                                         |
| Cable length:           | 3 m                                                                                                            |
| Battery:                | 1 x button cell 3.0 V CR2025 lithium manganese built-in                                                        |
| Battery:                | 1 x 9.0 V E block 6F22 zinc carbon included                                                                    |
| Laser class:            | 2M                                                                                                             |
| Laser color:            | R/G                                                                                                            |
| Laser module:           | Red (R) 100 mW 650nm<br>Green (G) 30 mW 532nm                                                                  |
| LED type:               | 6 x 2 W SMD 8072 R/G/B                                                                                         |
| Flash rate:             | 0 - 30 Hz                                                                                                      |
| LED type:               | 6 x 6 W SMD 8072 3in1 TCL RGB (homogenous color mix)                                                           |
| Beam angle:             | 13°                                                                                                            |
| Beam angle (1/2 peak):  | 13°                                                                                                            |
| Beam angle (1/10 peak): | 20°                                                                                                            |
| LED type:               | 4 x 2 W SMD 8072 2in1 BCL CW/UV (homogenous color mix)                                                         |
| Flash rate:             | 0 - 30 Hz                                                                                                      |

#### **EUROLITE EASY Show**

|                    |                                                                                 |
|--------------------|---------------------------------------------------------------------------------|
| Power supply:      | 100-240 V AC, 50/60 Hz<br>5V DC 250 mA                                          |
| Power consumption: | 1.25 W                                                                          |
| IP classification: | IP20                                                                            |
| Power connection:  | Mains input via USB C (W) mounting version<br>power supply cord with AC adapter |
| Programs:          | Preprogrammed 24 scenes/chases and 12 cues                                      |
| DMX input:         | 3-pin XLR (M) mounting version                                                  |
| DMX output:        | 3-pin XLR (F) mounting version                                                  |

|                          |                                                                 |
|--------------------------|-----------------------------------------------------------------|
| Control:                 | DMX; sound to light via microphone; QuickDMX via USB (optional) |
| Housing color:           | Black                                                           |
| Display type:            | Monochrome LCD display                                          |
| Available storage media: | USB devices                                                     |
| Housing design:          | Desktop console housing                                         |
| Dimensions:              | Width: 28.0 cm<br>Depth: 14.5 cm<br>Height: 6.0 cm              |
| Weight:                  | 1.35 kg                                                         |
| Noise classification:    | Class 0 (no noise at all)                                       |

#### **OMNITRONIC M-4 Speaker-System Stand**

|                            |                                                                               |
|----------------------------|-------------------------------------------------------------------------------|
| Maximum carrying capacity: | 18 kg                                                                         |
| Tube diameter sector:      | 38 - 35 mm                                                                    |
| Height:                    | Maximum: 345 cm<br>Minimum: 140 cm<br>Adjustable in 10 steps with locking pin |
| Attachment system:         | Ø 35mm                                                                        |
| Type (general stands):     | Speaker stand/manual                                                          |
| Material:                  | Aluminum                                                                      |
| Color:                     | Black                                                                         |
| Transport dimensions:      | 140 cm x 13.5 cm                                                              |
| Weight:                    | 3.30 kg                                                                       |

#### **Scope of delivery:**

##### **2 x EUROLITE LED KLS Laser Bar PRO FX Light Set**

1 x device  
 1 x power cord  
 1 x user manual  
 1 x declaration of conformity  
 1 x remote control  
 1 x foot control  
 2 x knurled screw  
 2 x washer  
 2 x mounting bracket  
 2 x battery  
 1 x bag

##### **1 x EUROLITE EASY Show**

1 x controller  
 1 x user manual  
 1 x external mains adapter  
 2 x USB cable  
 2 x mounting bracket  
 4 x screw

##### **2 x OMNITRONIC M-4 Speaker-System Stand**

1 x user manual