



**The article is no longer in our assortment.**

### Features:

#### EUROLITE LED 7C-7 Silent Slim Spot

Silent 7in1 LED PAR spotlight in a space-saving design

- Flat version requires minimal space when mounting
- 7 powerful LEDs 9 W high-power 7in1 SCL RGB/CW/WW/A/UV (homogenous color mix)
- Strobe effect
- Integrated show programs
- Direct color selection for 27 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 15°
- Very high color rendering index (CRI)
- With double bracket
- 4 digit 7-segment LED display
- Color blend stepless; Dimmer electronic
- Silent operation
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Wedding/gala/events; Stage; theater; mobile djs / entertainer
- Application possibility: Standing; suspended; on stand

#### Package contents

- 1 x light effect, 1 x power cord, 1 x remote control, 1 x user manual

### Logistic

EAN / GTIN: 4026397693829

Weight: 25,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.60 m

Bulky product

## EUROLITE LED B-40 HCL Beam Effect

LED beam effect with RGBAW+UV color mixing

- Precision lenses fill the room with countless rotating beams
- 5 powerful LEDs 12 W high-power 6in1 HCL RGBWA/UV
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Rotation speed stepless
- Multi beam effect; Strobe effect; UV effect
- 4 integrated show programs
- Direct color selection for 25 preset colors
- The device is cooled by low-noise cooling fan
- Control via DMX; Sound to light via Microphone; Master/slave function; stand-alone
- With Mounting bracket
- 4 digit 7-segment LED display
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- Very quiet working noise
- Mains input and output for power linking up to 8 units

### Package contents

- 1 x light effect, 1 x user manual, 1 x power cord, 1 x omega bracket, 2 x screw, 2 x washer

## EUROLITE EASY Show

Programmed DMX controller for over 200 spotlights from EUROLITE

- Easy-to-use DMX controller and DMX recorder
- Designed for DMX beginners with 200 programmed fixtures
- DMX recording function for your own projects, ideal for installations or rental companies
- Ideal for colored LED spotlights, KLS systems, moving lights and lighting effects
- No programming required, simply connect your spotlights and get started
- All spotlights can be freely combined to a show
- Data storage on USB flash drives
- A list of all preset devices is available at [www.steinigke.de](http://www.steinigke.de)
- Program speed adjustable; color fade adjustable; Dimmer
- Strobe effect
- 24 integrated show programs
- Direct color selection for 12 preset colors
- Control via DMX; Sound to light via Microphone; QuickDMX via USB (optional)
- Desktop console housing
- Monochrome LCD display
- Preprogrammed 24 scenes/chases and 12 cues )
- For application areas such as: Clubs/dancing school; Party room; mobile djs / entertainer; restaurants, bars and hotels; Installation
- Silent operation

### Package contents

- 1 x controller, 1 x user manual, 1 x external mains adapter, 2 x uSB cable, 2 x mounting bracket, 4 x screw

## Technical specifications:

---

Weight: 20,05 kg

---

## EUROLITE LED 7C-7 Silent Slim Spot

Power supply: 100-240 V AC, 50/60 Hz

---

Power consumption: 45 W

---

IP classification: IP20

---

Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 1 A Fuse replaceable
Lamp type:	LED lamp
LED:	7 x 9 W high-power 7in1 SCL RGB/CW/WW/A/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 4-1; 4-2; 4-3; 4-4; 5; 6; 7; 9; 12
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	15°
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	33°
Color rendering index (CRI):	92 Ra
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
USB port:	Typ A
Material:	Aluminum casting; metal
Dimensions:	Width: 22 cm Depth: 11 cm Height: 25,5 cm
Weight:	2,60 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Power cord	
Cable construction:	3 x 1,0 mm <sup>2</sup> H05VV-F
Cable length:	Approx. 1,2 m
Mounting bracket	
Diameter mounting holes:	1 x Ø11mm
Material:	Metal, 2,5 mm
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

## EUROLITE LED B-40 HCL Beam Effect

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Lamp type:	LED lamp
LED:	5 x 12 W high-power 6in1 HCL RGBWA/UV
Flash rate:	0 - 20 Hz
DMX channels:	5; 11
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Low-noise cooling fan
Control:	DMX; Sound to light via Microphone; Master/slave function; stand-alone
Preprogrammed in:	Light J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 32 cm Depth: 32 cm Height: 38 cm
Weight:	4,15 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

## EUROLITE EASY Show

Power supply:	100-240 V AC, 50/60 Hz 5 V DC 250 mA
Power consumption:	1,25 W
IP classification:	IP20
Power connection:	Mains input via USB C (W) mounting version power supply cord with AC adapter
Programs:	Preprogrammed 24 scenes/chases and 12 cues )
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version

Control:	DMX; Sound to light via Microphone; QuickDMX via USB (optional)
Housing color:	Black
Display type:	Monochrome LCD display
Available storage media:	USB devices
Housing design:	Desktop console housing
Dimensions:	Width: 28,0 cm Depth: 14,5 cm Height: 6,0 cm
Weight:	1,35 kg
Noise classification:	Class 0 (no noise at all)