

EUROLITE Set 4x LED THA-20PC TRC Theater Spot bk + Case

Art. No.: 20000871

GTIN: 4026397694116



List price: 1093.61 €

incl. 19% VAT.

Features:

EUROLITE LED THA-20PC TRC Theater Spot bk

Fanless PC spot with 17 W white light LED, color rendering index (CRI) >90

- New LED technology that simulates the color temperature curve of a halogen lamp when dimming
 - Two additional frost filters provide a soft, homogeneous light
 - 1 powerful LED 17 W COB (chip-on-board) Dim to warm (homogenous color mix)
 - The device is cooled by passive convection cooling
 - Control via stand-alone
 - Flicker-free
 - With a beam angle of 17°
 - Very high color rendering index (CRI)
 - With mounting bracket
 - Silent operation
 - For application areas such as: Trade fair and shop fitting; wedding/gala/events; video and photography; mobile use
 - Dimmer electronic
 - Rubber feet
 - Application possibility: Suspended; on stand
- Package contents**
- 1 x spotlight, 1 x barn door, 1 x filter frame, 2 x frost filter, 1 x ring, 2 x lamp clamping ring, 1 x user manual

Logistic

EAN / GTIN: 4026397694116

Weight: 20,20 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.35 m

Bulky product

ROADINGER Flightcase 4x THA-20PC

- 6,5 mm,
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	17,02 kg
---------	----------

EUROLITE LED THA-20PC TRC Theater Spot bk

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	22 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Fuse:	5 x 20 mm, T 1 A fuse replaceable
LED type:	1 x 17 W COB (chip-on-board) Dim to warm (homogenous color mix)
Cooling:	Passive convection cooling
Control:	Stand-alone
Projection:	Flicker-free
Beam angle:	17°
Beam angle (1/2 peak):	17°
	Frost filter 19°
	Frost filter 26°
Beam angle (1/10 peak):	36°
	Frost filter 40°
	Frost filter 53°
Color temperature:	3000K
Color rendering index (CRI):	92 Ra
Illuminance in Lux (lx):	Warm white (WW) 3m: 727 lx, 6m: 188 lx
Housing color:	Black
Attachment system:	Mounting bracket
Transport aid:	Rubber feet
Material:	Aluminum casting
Slot for spot length:	10 cm x 10 cm
Dimensions:	Length: 21,5 cm
	Width: 14,5 cm
	Depth: 21 cm
Weight:	2,23 kg
Noise classification:	Class 0 (no noise at all)
Mounting bracket	
Diameter mounting holes:	1 x Ø10mm
Material:	Metal, 3 mm

Power cord	
Cable construction:	3 x 0,75 mm² H05VV-F
Cable length:	Approx. 1 m
Barndoor	
Material:	Aluminum, 1 mm; metal
Ring diameter:	Outside: 99 mm Inside: 80 mm
Filter frame	
Diameter mounting holes:	1 x Ø4mm
Material:	Aluminum, 0,8 mm
Color:	Black
Dimensions:	Width: 9,9 cm Height: 9,9 cm Diameter: Ø 8 cm
Frost filter	
Material:	Plastic
Color:	Semi-transparent
Dimensions:	Width: 0,2 cm Diameter: Ø 8 cm
Ring	
Material:	Aluminum, 1 mm
Color:	Gold
Dimensions:	Depth: 1,3 cm Diameter: Ø 8,2 cm
Lamp clamping ring	
Material:	Metal, 2 mm
Color:	Black
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x THA-20PC

Maximum load:	50 kg
Use of brands:	Branded hardware
Device compartment:	16 cm x 19 cm x 13,5 cm
Inside dimensions:	42,5 cm x 43 cm x 18 cm
Accessory compartment:	10,5 cm x 43 cm x 18 cm
Material thickness:	6,5 mm
Dimensions:	Width: 51 cm Depth: 46 cm Height: 27 cm
Weight:	8,10 kg