



**List price: 1426.81 €**

incl. 19% VAT.

### Features:

#### EUROLITE AKKU THA-20PC TRC Theater Spot bk

Battery powered LED theater spotlight with manual brightness regulation

- Two additional frost filters provide a soft, homogeneous light
  - New LED technology that simulates the color temperature curve of a halogen lamp when dimming
  - Rugged metal housing
  - Battery operation up to 2h
  - 1 powerful LED 17 W COB (chip-on-board) Dim to warm (homogenous color mix)
  - Dimmer electronic
  - The device is cooled by passive convection cooling
  - Control via stand-alone
  - Flicker-free
  - With a beam angle of 17°
  - Very high color rendering index (CRI)
  - With mounting bracket
  - Silent operation
  - For application areas such as: Trade fair and shop fitting; wedding/gala/events; video and photography; restaurants, bars and hotels
  - Cordless, flexible and versatile
  - Integrated automatic charging of the battery and status indicator
  - Rubber feet
  - Application possibility: Suspended; on stand
- Package contents**
- 1 x spotlight, 1 x user manual, 1 x external mains adapter, 1 x filter frame, 1 x barndoor, 2 x frost filter

### Logistic

EAN / GTIN: 4026397694130

Weight: 20,60 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.50 m

Bulky product

## ROADINGER Flightcase 4x THA-20PC

- 6,5 mm,
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

### Technical specifications:

---

Weight:	17,62 kg
---------	----------

---

### EUROLITE AKKU THA-20PC TRC Theater Spot bk

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP20
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Battery pack type:	1 x lithium ion 11,1 V, 2600 mAh, 28,86 Wh
Battery pack:	Battery operation up to 2h Recharging time 3h
LED type:	1 x 17 W COB (chip-on-board) Dim to warm (homogenous color mix)
Cooling:	Passive convection cooling
Control:	Stand-alone
Projection:	Flicker-free
Beam angle:	17°
Beam angle (1/2 peak):	17° Frost filter 19° Frost filter 26°
Color temperature:	3000K
Color rendering index (CRI):	92 Ra
Housing color:	Black
Attachment system:	Mounting bracket
Transport aid:	Rubber feet
Dimensions:	Length: 21 cm Width: 14,5 cm Height: 21 cm
Weight:	2,38 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

**ROADINGER Flightcase 4x THA-20PC**

Maximum load:	50 kg
Use of brands:	Branded hardware
Device compartment:	16 cm x 19 cm x 13,5 cm
Inside dimensions:	42,5 cm x 43 cm x 18 cm
Accessory compartment:	10,5 cm x 43 cm x 18 cm
Material thickness:	6,5 mm
Dimensions:	Width: 51 cm Depth: 46 cm Height: 27 cm
Weight:	8,10 kg