



List price: 2200.31 €

incl. 19% VAT.

Features:

EUROLITE LED Theatre COB 200 WW

LED theatre spot with warm white (WW) 200 W COB (chip-on-board) LED

- 1 powerful LED 200 W COB (chip-on-board) warm white (WW)
- Dimmer electronic
- Strobe effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 17°
- Very high color rendering index (CRI)
- With double bracket
- LCD display
- Very quiet working noise
- For application areas such as: Theater; Trade fair and shop fitting; mobile use; stage
- Preprogrammed in Light´J; Light Captain; Colorchief
- Mains input and output for power linking up to 8 units
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

Logistic

EAN / GTIN: 4026397694147

Weight: 41,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.75 m

Bulky product

ROADINGER Flightcase 4x LED Theatre COB 200 series, with wheels

Trunk case with castors, PRO version

- High-quality workmanship with birch multiplex 6,5 mm,
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes
- 4 built-in stacking trays in the cover
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Package contents

- 1 x case

Technical specifications:

Weight:	36,84 kg
---------	----------

EUROLITE LED Theatre COB 200 WW

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	150 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	1 x 200 W COB (chip-on-board) warm white (WW)
Flash rate:	0 - 20 Hz
DMX channels:	1; 2; 4
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light´J; Light Captain; Colorchief
Projection:	Flicker-free
Beam angle:	17°
Beam angle (1/2 peak):	17°
Beam angle (1/10 peak):	35°
Color temperature:	3200K
Color rendering index (CRI):	98 Ra
Housing color:	Black
Attachment system:	Double bracket

Display type:	LCD display
Dimensions:	Width: 25,95 cm Depth: 20,00 cm Height: 37,65 cm
Weight:	4,11 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Photobiological safety:	Risk Group 0
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x LED Theatre COB 200 series, with wheels

Maximum load:	100 kg
Aluminum profile frames:	30 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Use of brands:	Branded hardware
Material:	Birch multiplex, 6,5 mm
Accessory compartment:	10,5 cm x 47 cm x 35,5 cm
Device compartment:	28 cm x 22 cm x 35,5 cm
Inside dimensions:	66,5 cm x 47 cm x 35,5 cm
Dimensions:	Length: 73,5 cm Depth: 51 cm Height: 57 cm
Weight:	20,40 kg