



Features:

EUROLITE LED IP PAR 7x9W SCL Spot

Weather-proof (IP65) spotlight with 7 x 9 W LED and 7in1 SCL RGB/CW/WW/A/UV color mixing

- 7 LEDs 9 W high-power 7in1 SCL RGB/CW/WW/A/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 28 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; IR remote control
- Fixtures available for LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- Flicker-free
- With a beam angle of 15°
- With double bracket
- LCD display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- For application areas such as: Architecture; stage; clubs/dancing school; wedding/gala/events; theater; rental; video and photography
- Silent operation
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397694185

Weight: 380,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.50 m

Bulky product

ROADINGER Flightcase 4x LED IP PAR 7x8W QCL/7x9W SCL with wheels

Trunk case with castors, PRO version

- With 4 device compartments

- With 1 accessory compartment
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 34.03 kg

EUROLITE LED IP PAR 7x9W SCL Spot

| | |
|-------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 55 W |
| IP classification: | IP65 |
| Power connection: | Mains input via IP T-Con (M) mounting version power supply cord with safety plug |
| Power output: | IP T-Con (F) mounting version |
| Lamp type: | LED lamp |
| LED type: | 7 x 9 W high-power 7in1 SCL RGB/CW/WW/A/UV (homogenous color mix) |
| Flash rate: | 0 - 20 Hz |
| DMX channels: | 3; 5; 7; 9; 13 |
| DMX input: | 1 x 3-pin XLR (M) mounting version IP |
| DMX output: | 1 x 3-pin XLR (F) mounting version IP |
| Cooling: | Passive convection cooling |
| Control: | DMX; stand-alone; IR remote control |
| Fixtures available for: | LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3 |
| Projection: | Flicker-free |
| Beam angle: | 15° |
| Beam angle (1/2 peak): | 15° |
| Housing color: | Black matte |
| Attachment system: | Double bracket |
| Display type: | LCD display |
| Material: | Aluminum casting |
| Dimensions: | Width: 25.5 cm Depth: 15.3 cm Height: 28.1 cm |
| Weight: | 4.07 kg |
| Noise classification: | Class 0 (no noise at all) |

| | |
|--------------------------|---|
| Photobiological safety: | Risk Group 0 |
| Diameter mounting holes: | 3 x Ø11mm |
| Material: | Metal, 2.5 mm |
| Cable construction: | 3 x 1.0 mm ² H05RN-F |
| Cable length: | Approx. 1.2 m |
| Battery: | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase 4x LED IP PAR 7x8W QCL/7x9W SCL with wheels

| | |
|--------------------------|---|
| Maximum load: | 100 kg |
| Aluminum profile frames: | 25 mm |
| Case handle: | 4 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |
| Transport aid: | 4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover |
| Use of brands: | Branded hardware |
| Material: | Birch multiplex |
| Color: | Dark brown, laminated |
| Device compartment: | 21.5 cm x 22.5 cm x 29 cm |
| Accessory compartment: | 10 cm x 50 cm x 29 cm |
| Inside dimensions: | 53 cm x 50 cm x 29 cm |
| Material thickness: | 6.5 mm |
| Dimensions: | Width: 62.50 cm Depth: 53.50 cm Height: 51.50 cm |
| Weight: | 17.75 kg |

Scope of delivery:

1 x spotlight
1 x power cord
1 x remote control
1 x user manual