



The article is no longer in our assortment.

Features:

EUROLITE LED TSL-1000 Scan

Scanner with 100 W LED, rotating gobos, 3-facet prism, color wheel and motorized focus

- One high-power 100 W COB LED in cold white
- Positioning within 160° PAN and 50° TILT
- Exact positioning via 16-bit PAN/TILT movement resolution
- Auto, music, master/slave and DMX mode
- Built-in auto and music show programs
- 3-facet prism
- Gobos interchangeable
- Strobe effect with adjustable speed
- Motorized focus
- Electronic dimmer (0-100%) (0-100%) (0-100%) (0-100%) (0-100%)
- Narrow beam angle of 20°
- Control panel with OLED display for easy configuration
- Mains input and output for power linking up to 8 units
- Additional rubber feet protect the device when positioned on the floor
- 1 powerful LED 100 W COB (chip-on-board) cold white (CW)
- Exact positioning (16 bit resolution)
- Focus motor-driven; color wheel; gobo wheel with rotating gobos; prism 3-fold
- Gobo effect
- Color wheel with 8 dichroic filters plus open
rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 7 gobos and open
shake effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; master/slave function; sound to light via microphone
- Preprogrammed in Light Captain; EASY SHOW 2; EASY SHOW 3

Logistic

EAN / GTIN: 4026397694857

Weight: 25,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.50 m

Bulky product

- Flicker-free
- With a beam angle of 20°
- OLED display

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x safety eyelet

ROADINGER Flightcase 2x LED TSL-1000 with trolley function

Trolley case, PRO version

- High-quality workmanship with birch multiplex 6,5 mm,
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 3 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Trolley
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	21,70 kg
---------	----------

EUROLITE LED TSL-1000 Scan

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	110 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Fuse:	T 2 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 100 W COB (chip-on-board) cold white (CW)
Max. TILT movement:	50° exact positioning (16 bit resolution)
Max. PAN movement:	160° exact positioning (16 bit resolution)
Flash rate:	1 - 25 Hz
Equipment:	Focus motor-driven; color wheel; gobo wheel with rotating gobos; prism 3-fold
Color generation:	Color wheel with 8 dichroic filters plus open Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with rotating gobos, 7 gobos and open Shake effect
DMX channels:	10; 15
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version

Cooling:	Cooling fan
Control:	Stand-alone; DMX; master/slave function; sound to light via microphone
Preprogrammed in:	Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	20°
Beam angle (1/2 peak):	20°
Color temperature:	8000K
Illuminance in Lux (lx):	Cold white (CW) 1m: 35679 lx, 3m: 4265 lx, 6m: 1055 lx
Housing color:	Black
Display type:	OLED display
Dimensions:	Width: 25,1 cm Depth: 14,1 cm Height: 37,7 cm
Weight:	5,80 kg
Noise classification:	Class 2 (slight noise)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 2x LED TSL-1000 with trolley function

Maximum load:	25 kg
Aluminum profile frames:	25 mm
Case handle:	3 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	Trolley
Use of brands:	Branded hardware
Material:	Birch multiplex, 6,5 mm
Accessory compartment:	44 cm x 7 cm x 13 cm
Device compartment:	36 cm x 25,5 cm x 13 cm
Inside dimensions:	86,5 cm x 32,5 cm x 13 cm
Weight:	10,10 kg