

## EUROLITE Set 8x LED IP PAR 7x9W SCL Spot + Case with wheels

Art. No.: 20000883

GTIN: 4026397694895



**List price: 3152.31 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED IP PAR 7x9W SCL Spot

Weather-proof (IP65) spotlight with 7 x 9 W LED and 7in1 SCL RGB/CW/WW/A/UV color mixing

- 7 powerful LEDs 9 W high-power 7in1 SCL RGB/CW/WW/A/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 28 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; IR remote control
- Flicker-free
- With a beam angle of 15°
- With double bracket
- LCD display
- Suitable for outdoor use IP65
- Silent operation
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- Mains input and output for power linking up to 8 units
- For application areas such as: Installation; stage; rental; architecture
- Application possibility: Standing; suspended; on stand

#### Package contents

- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

### Logistic

EAN / GTIN: 4026397694895

Weight: 65,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.75 m

Bulky product

#### ROADINGER Flightcase 8x LED IP PAR 7x8W QCL/7x9W SCL with wheels

Trunk case with castors, PRO version

- With 8 device compartments
- With 1 accessory compartment
- High-quality workmanship with birch multiplex 6,50 mm, black, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes
- 4 built-in stacking trays in the cover
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

|         |          |
|---------|----------|
| Weight: | 58,96 kg |
|---------|----------|

### EUROLITE LED IP PAR 7x9W SCL Spot

|                        |   |
|------------------------|---|
| Power supply:          | 100-240 V AC, 50/60 Hz  |
| Power consumption:     | 55 W  |
| IP classification:     | IP65  |
| Power connection:      | Mains input via IP T-Con (M) mounting version<br>power supply cord with safety plug |
| Power output:          | IP T-Con (F) mounting version   |
| Lamp type:             | LED lamp  |
| LED type:              | 7 x 9 W high-power 7in1 SCL<br>RGB/CW/WW/A/UV (homogenous color mix)                |
| Flash rate:            | 0 - 20 Hz   |
| DMX channels:          | 3; 5; 7; 9; 13  |
| DMX input:             | 1 x 3-pin XLR (M) mounting version IP   |
| DMX output:            | 1 x 3-pin XLR (F) mounting version IP   |
| Cooling:               | Passive convection cooling  |
| Control:               | DMX; stand-alone; IR remote control   |
| Preprogrammed in:      | LED PC-Control 512; EASY SHOW 1; Light<br>Captain; EASY SHOW 2; EASY SHOW 3         |
| Projection:            | Flicker-free  |
| Beam angle:            | 15°   |
| Beam angle (1/2 peak): | 15°   |
| Housing color:         | Black matte   |
| Attachment system:     | Double bracket  |
| Display type:          | LCD display   |
| Material:              | Aluminum casting  |
| Dimensions:            | Width: 25,5 cm<br>Depth: 15,3 cm<br>Height: 28,1 cm                                 |
| Weight:                | 4,07 kg   |

|                          |   |
|--------------------------|---|
| Noise classification:    | Class 0 (no noise at all)                               |
| Photobiological safety:  | Risk Group 0  |
| Mounting bracket         |   |
| Diameter mounting holes: | 3 x Ø11mm   |
| Material:                | Metal, 2,5 mm   |
| Power cord               |   |
| Cable construction:      | 3 x 1,0 mm² H05RN-F                                     |
| Cable length:            | Approx. 1,2 m   |
| Remote control           |   |
| Battery:                 | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| Legal specifications     |   |
| Special product:         | Not designed for household room illumination            |
| Intended use:            | Show effect lighting                                    |

#### **ROADINGER Flightcase 8x LED IP PAR 7x8W QCL/7x9W SCL with wheels**

|                          |   |
|--------------------------|---|
| Maximum load:            | 100 kg  |
| Aluminum profile frames: | 25 mm   |
| Case handle:             | 4 pc/pcs  |
| Stop hinge:              | 3 pc/pcs  |
| Lock:                    | Butterfly lock: 2 pc/pcs  |
| Transport aid:           | 4 x castors with 2 locking brakes<br>4 x built-in stacking trays in the cover |
| Use of brands:           | Branded hardware  |
| Material:                | Birch multiplex, 6,50 mm, laminated   |
| Color:                   | Black, laminated  |
| Device compartment:      | 22,5 cm x 24 cm x 30 cm   |
| Accessory compartment:   | 101 cm x 10,5 cm x 28 cm  |
| Dimensions:              | Length: 105 cm<br>Depth: 63 cm<br>Height: 51 cm                               |
| Weight:                  | 26,40 kg  |