



**List price: 2378.81 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED IP PAR 12x9W SCL Spot

Weather-proof (IP65) spotlight with 12 x 9 W LED and 7in1 SCL RGB/CW/WW/A/UV color mixing

- 12 powerful LEDs 9 W COB (chip-on-board) 7in1 SCL RGB/CW/WW/A/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 28 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; IR remote control; stand-alone
- Flicker-free
- With a beam angle of 15°
- With double bracket
- LCD display
- Suitable for outdoor use IP65
- Silent operation
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- Mains input and output for power linking up to 8 units
- With pressure compensation membrane
- For application areas such as: Installation; Stage; Rental; architecture
- Application possibility: Standing; suspended; on stand

#### Package contents

- 1 x device, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

### Logistic

EAN / GTIN: 4026397694901

Weight: 40,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.50 m

Bulky product

## ROADINGER Flightcase 4x LED IP PAR 12x8W QCL/12x9 SQL Spot

Trunk case, PRO version

- High-quality workmanship with birch multiplex 6,5 mm,
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

### Technical specifications:

---

Weight: 35,00 kg

---

## EUROLITE LED IP PAR 12x9W SCL Spot

|                         |  |
|-------------------------|--|
| Power supply:           | 100-240 V AC, 50/60 Hz   |
| Power consumption:      | 75 W   |
| IP classification:      | IP65   |
| Protection class:       | Protection class I   |
| Power connection:       | Mains input via IP T-Con (M) mounting version power supply cord with safety plug |
| Power output:           | IP T-Con (F) mounting version  |
| Lamp type:              | LED lamp   |
| LED:                    | 12 x 9 W COB (chip-on-board) 7in1 SCL RGB/CW/WW/A/UV (homogenous color mix)      |
| Flash rate:             | 0 - 20 Hz  |
| DMX channels:           | 3; 5; 7; 9; 13   |
| DMX input:              | 3-pin XLR (M) mounting version IP  |
| DMX output:             | 3-pin XLR (F) mounting version IP  |
| Cooling:                | Passive convection cooling   |
| Control:                | DMX; IR remote control; stand-alone  |
| Preprogrammed in:       | LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3         |
| Projection:             | Flicker-free   |
| Beam angle:             | 15°  |
| Beam angle (1/2 peak):  | 15°  |
| Beam angle (1/10 peak): | 29°  |
| Housing color:          | Black  |
| Attachment system:      | Double bracket   |
| Display type:           | LCD display  |
| Material:               | Aluminum casting   |
| Dimensions:             | Width: 28,5 cm<br>Depth: 15,3 cm   |

|                          |   |
|--------------------------|---|
|                          | Height: 31,35 cm  |
| Weight:                  | 5,20 kg   |
| Noise classification:    | Class 0 (no noise at all)                               |
| Photobiological safety:  | Risk Group 0  |
| Power cord               |   |
| Cable construction:      | 3 x 1,0 mm <sup>2</sup> H05RN-F                         |
| Cable length:            | Approx. 1,2 m   |
| Mounting bracket         |   |
| Diameter mounting holes: | 3 x Ø11mm   |
| Material:                | Metal, 2,5 mm   |
| Remote control           |   |
| Battery:                 | 1 x Button cell 3.0 V CR2025 lithium manganese built-in |
| Legal specifications     |   |
| Special product:         | Not designed for household room illumination            |
| Intended use:            | Show effect lighting                                    |

#### **ROADINGER Flightcase 4x LED IP PAR 12x8W QCL/12x9 SQL Spot**

|                          |  |
|--------------------------|--|
| Maximum load:            | 100 kg   |
| Aluminum profile frames: | 25 mm  |
| Case handle:             | 4 pc/pcs                                       |
| Stop hinge:              | 2 pc/pcs                                       |
| Lock:                    | Butterfly lock: 2 pc/pcs                       |
| Use of brands:           | Branded hardware                               |
| Material:                | Birch multiplex, 6,5 mm                        |
| Compartment dimensions:  | 30 cm x 15,5 cm x 35 cm                        |
| Accessory compartment:   | 63 cm x 95 cm x 35 cm                          |
| Inside dimensions:       | 63 cm x 40,5 cm x 35 cm                        |
| Dimensions:              | Length: 67 cm<br>Depth: 48 cm<br>Height: 45 cm |
| Weight:                  | 14,20 kg                                       |