



The article is no longer in our assortment.

Features:

EUROLITE AKKU UP-1 Glow QCL Flex Spot QuickDMX

LED Uplight with 15 W 4in1 LED, tiltable head, QuickDMX & mood light

- Integrated QuickDMX transceiver for wireless DMX control
- Milky front screen provides a pleasantly soft light with RGBW color mixing
- Interchangeable front lens for 9° or 15° beam angle
- Stepless color blend, color change, color fade, dimmer and strobe effect
- Dimmer speed (step response) adjustable
- Integrated automatic charging of the battery with indicator
- Cordless, flexible and versatile
- Battery operation up to 24h depending on program used
- 30 powerful LEDs 0,25 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
- 1 powerful LED 15 W high-power 4in1 QCL RGBW (homogenous color mix)
- Direct color selection for 30 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; QuickDMX; sound to light via microphone; IR remote control; master/slave function
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- Flicker-free
- With a beam angle of 9°
- With mounting bracket
- With a KENSINGTON LOCK theft protection
- Silent operation
- For application areas such as: Small rental; wedding/gala/events

Package contents

- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x lens, 1 x user manual

Logistic

EAN / GTIN: 4026397694987

Weight: 22,00 kg

Length: 0.54 m

Width: 0.53 m

Height: 0.45 m

ROADINGER Flightcase EC-AU4 4x AKKU UP 4 QCL Spot QuickDMX

Trunk case

- Cable bushing allows loading the devices inside
- With 4 device compartments
- High-quality workmanship with plywood multi-layer glued 6 mm, black, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

| | |
|---------|----------|
| Weight: | 18,20 kg |
|---------|----------|

EUROLITE AKKU UP-1 Glow QCL Flex Spot QuickDMX

| | |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 40 W |
| IP classification: | IP20 |
| Protection class: | Protection class III |
| Power connection: | Battery/battery pack Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Battery pack type: | 1 x lithium ion 11,1 V, 10400 mAh, 115,44 Wh |
| Battery pack: | Battery operation up to 24h depending on program used Recharging time 4h |
| Lamp type: | LED lamp |
| LED type: | 30 x 0,25 W SMD 5050 4in1 QCL RGBW (homogenous color mix) 1 x 15 W high-power 4in1 QCL RGBW (homogenous color mix) |
| DMX channels: | 3; 7; 8; 9; 11 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | DMX; stand-alone; QuickDMX; sound to light via microphone; IR remote control; master/slave function |
| Preprogrammed in: | Light'J; LED PC-Control 512; Light Captain |
| Projection: | Flicker-free |
| Carrier frequency: | 2,4 GHz |
| Beam angle: | 9° |
| Beam angle (1/2 peak): | 9° 15° |

| | |
|-------------------------|---------------------------------------------------------|
| Beam angle (1/10 peak): | 18° |
| | 30° |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Theft protection: | KENSINGTON LOCK |
| Dimensions: | Width: 13,8 cm |
| | Depth: 13,8 cm |
| | Height: 20 cm |
| Weight: | 2,90 kg |
| Noise classification: | Class 0 (no noise at all); Class 0 (no noise at all) |
| Remote control | |
| Battery: | 1 x button cell 3.0 V CR2032 lithium manganese built-in |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase EC-AU4 4x AKKU UP 4 QCL Spot QuickDMX

| | |
|--------------------------|------------------------------------------------------------|
| Maximum load: | 25 kg |
| Aluminum profile frames: | 30 mm |
| Case handle: | 1 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 1 pc/pcs |
| Material: | Plywood multi-layer glued, 6 mm; plywood multi-layer glued |
| Color: | Black, laminated |
| Inside dimensions: | 45 cm x 36 cm x 20 cm |
| Device compartment: | 16 cm x 14,5 cm x 18 cm |
| Dimensions: | Width: 49 cm |
| | Depth: 40 cm |
| | Height: 27 cm |
| Weight: | 6,60 kg |