



List price: 1902.81 €

incl. 19% VAT.

Features:

EUROLITE AKKU UP-7 QCL Spot QuickDMX

Uplight with 7 x 8 W 4in1 LED, QuickDMX transceiver, frost filter and IR remote control

- Integrated QuickDMX transceiver for wireless DMX control
- Additional frost filter provides a wide, soft and homogeneous light
- Sturdy metal housing with handle and folding foot for angled placement
- Battery operation up to 17h depending on program used
- 7 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable; white balance adjustable
- Strobe effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; IR remote control; master/slave function; sound to light via microphone; QuickDMX
- Flicker-free
- With a beam angle of 9°
- Monochrome OLED display
- With a KENSINGTON LOCK theft protection
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; rental
- Mains input and output for power linking up to 8 units
- Cordless, flexible and versatile
- Integrated automatic charging of the battery and status indicator
- Preprogrammed in EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief

Logistic

EAN / GTIN: 4026397694994

Weight: 25,00 kg

Length: 0.54 m

Width: 0.53 m

Height: 0.45 m

- Rubber feet
- Silent operation
- Application possibility: Standing

Package contents

- 1 x device, 1 x power cord, 1 x remote control, 1 x battery, 1 x frost filter, 2 x knurled screw, 1 x declaration of conformity, 1 x user manual

ROADINGER Flightcase EC-AU4 4x AKKU UP 4 QCL Spot QuickDMX

Trunk case

- Cable bushing allows loading the devices inside
- With 4 device compartments
- High-quality workmanship with plywood multi-layer glued 6 mm, black, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	21,00 kg
---------	----------

EUROLITE AKKU UP-7 QCL Spot QuickDMX

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	70 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) Battery/battery pack built-in
Cable length:	Approx. 1,2 m
Power output:	1 x P-Con (gray), mounting version
Battery pack type:	1 x lithium ion 25,9 V, 7800 mAh, 202,02 Wh
Battery pack:	Battery operation up to 17h depending on program used Recharging time 3,5h
Lamp type:	LED lamp
LED type:	7 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 11
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; IR remote control; master/slave function; sound to light via microphone; QuickDMX

Preprogrammed in:	EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light 'J; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle:	9°
Beam angle (1/2 peak):	9°
Beam angle (1/10 peak):	18°
Housing color:	Black
Display type:	Monochrome OLED display
Transport aid:	Rubber feet
Theft protection:	KENSINGTON LOCK
Dimensions:	Width: 13,8 cm Depth: 16,7 cm Height: 18,9 cm
Weight:	3,60 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase EC-AU4 4x AKKU UP 4 QCL Spot QuickDMX

Maximum load:	25 kg
Aluminum profile frames:	30 mm
Case handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Material:	Plywood multi-layer glued, 6 mm; plywood multi- layer glued
Color:	Black, laminated
Inside dimensions:	45 cm x 36 cm x 20 cm
Device compartment:	16 cm x 14,5 cm x 18 cm
Dimensions:	Width: 49 cm Depth: 40 cm Height: 27 cm
Weight:	6,60 kg