



**The article is no longer in our assortment.**

### Features:

#### EUROLITE LED Strip 300 5m RGBWW 24V

Flexible LED strip with RGB and warm white LEDs

- Flexible LED strip for decorative lighting
- High-grade components and a solid construction guarantee a long service life and excellent color rendering
- Can be cut into segments of variable size
- Self-adhesive rear side
- Supplied on a plastic reel
- Power cable, straight and flexible plug connectors available as accessories
- 300 powerful LEDs SMD 5050 4in1 QCL RGB/WW (homogenous color mix)
- Control via system controller
- Good color rendering index (CRI)
- For application areas such as: Trade fair and shop fitting; clubs/dancing school; installation; restaurants, bars and hotels
- Silent operation

#### Package contents

- 1 x illuminant, 1 x user manual

### Logistic

EAN / GTIN: 4026397695007

Weight: 1,50 kg

Length: 0.30 m

Width: 0.22 m

Heigh: 0.21 m

#### EUROLITE LED Strip 4in1 Zone RF Controller

4-channel wireless LED controller with remote control for RGB/W and dual white

- User-friendly LED controller with 4 zones (4 x 6A) and remote control
- Controls single- and multi-colored (CW+WW, RGB, RGBW) LED strips (12-24 V) as desired
- Innovative wireless technology allows multiple controllers to be controlled synchronously and asynchronously with just one remote control

- Synchronous color sequences even over several hours with multiple controllers and different LED types
- Excellent signal transmission with 2.4 GHz - no perceptible difference to a wired system
- All controllers communicate with each other and cover a large range
- No visible contact between remote control and controller required
- Any number of controllers possible in 4 zones
- Color selection via touch-sensitive color wheel
- Memory function saves last setting when switching off
- Program speed adjustable; Dimmer electronic
- 8 integrated show programs
- remote control**
- Operating range up to 20m
- Package contents**
- 1 x controller, 1 x remote control, 1 x user manual, 2 x battery, 1 x declaration of conformity, 1 x holder, 4 x screw

### **EUROLITE Electronic Transformer, 24V, 5A, IP67**

Stabilized LED power supply unit DC 24 V, 5 A

- Input voltage AC 100-240 V
- Noise filter
- Suitable for outdoor use IP67

#### **Package contents**

- 1 x external mains adapter

### **Technical specifications:**

---

Weight:	0,91 kg
---------	---------

---

### **EUROLITE LED Strip 300 5m RGBWW 24V**

Power supply:	24V DC
Power consumption:	67 W
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Fixed supply cord with open wires
Cable length:	Approx. 0,15 m
LED type:	300 x SMD 5050 4in1 QCL RGB/WW (homogenous color mix)
Control:	System controller
Standing/fixation:	Self adhesive
Color rendering index (CRI):	82 Ra
Lamps/meter:	60 pc/pcs
Power/meter:	13,4 W
Lamps/tube:	300 pc/pcs
Lamp distance:	16 mm
Cutting mark:	10 cm
Housing color:	White
Dimensions:	Length: 500 cm Width: 1,2 cm Height: 0,2 cm

Weight:	0,15 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	G

#### **EUROLITE LED Strip 4in1 Zone RF Controller**

Weight:	0,19 kg
Controller	
Power supply:	12/24V DC
Power consumption:	Max. 576 W 24 V DC 144 W 24 V DC per channel Max. 288 W 12 V DC 72 W 12 V DC per channel
Output current:	Max. 4 x 6 A per channel
Power connection:	Via screw terminal
Power output:	Screw terminal
Carrier frequency:	2,4 GHz
Dimensions:	Length: 16 cm Width: 4,6 cm Height: 2,5 cm
Weight:	0,19 kg
Remote control	
Battery:	2 x 1.5 V AAA Micro LR03 alkaline manganese included
Range:	Range up to 20m
Dimensions:	Length: 16,4 cm Width: 4,5 cm Height: 2,6 cm
Weight:	0,1 kg

#### **EUROLITE Electronic Transformer, 24V, 5A, IP67**

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP67
Protection class:	Protection class II
Power connection:	Fixed supply cord with open wires
Cable length:	Approx. 0,2 m
Power output:	No connector/cable only
Housing color:	White matte
Controls:	Overload; short-circuit; overheat
Output:	24 V DC, stabilized; 5 A;
Material:	Plastic
Dimensions:	Length: 20 cm Width: 5,2 cm Height: 3,7 cm
Weight:	0,58 kg