



**List price: 1069.81 €**

incl. 19% VAT.

## Features:

### OMNITRONIC TRM-422 4-Channel Rotary Mixer

4-channel rotary mixer with 3-band frequency isolator and filter section for DJs

- 3-band master frequency isolator with vintage ALPS potentiometers (Blue Velvet RK27)
- Kill cut feature allows DJs to completely remove low, mid and high frequencies for amazing mixing
- Filter section with resonance and sweep control for creative sound shaping
- 4 stereo input channels with gain control, clip LED, 3-way equalizer and phono/line switching
- 2 microphone input channels with gain control, 2-way equalizer on air switch
- High-grade components ensure long life and excellent sound quality
- 16-digit stereo LED level meter, switchable between master and booth outputs
- Booth output with separate 2-way equalizer and level control
- PFL section with 16-digit stereo LED level meter, level control, PFL/master mix control and cue mix/split option
- Fully assignable VCA crossfader with adjustable curve
- 2 effects send/return paths
- Direct outputs for Timecode applications
- Outputs: master and booth (XLR/RCA L/R), record (RCA L/R), master insert send/return (RCA L/R), FX in/out (stereo jack)
- Desktop console housing
- (19") 48.3 cm rack installation possible
- For application areas such as: Clubs/dancing school; mobile use; mobile djs / entertainer; homerecording and studios

### Package contents

- 1 x mixer, 1 x power cord, 2 x mounting bracket, 6 x screw, 8 x rCA cable, 1 x user manual

## Logistic

EAN / GTIN: 4026397695571

Weight: 11,20 kg

Length: 0.54 m

Width: 0.53 m

Height: 0.45 m

## ROADINGER Flightcase TRM-422

Carrying case, PRO version

- High-quality workmanship with birch multiplex 6,5 mm, dark brown, laminated
- Interior with foam padding<BR>cover with foam padding
- Removable cover
- Aluminum profile frames 22mm with rounded edges
- Rugged carrying handle
- 2 high-quality spring locks
- Rubber feet
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

---

Weight: 10,39 kg

---

## OMNITRONIC TRM-422 4-Channel Rotary Mixer

|                    |   |
|--------------------|---|
| Power supply:      | 100-240 V AC, 50/60 Hz  |
| Power consumption: | 24 W  |
| Protection class:  | Protection class I  |
| Power connection:  | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)                                    |
| Frequency range:   | 20 - 20000 Hz Microphone<br>20 - 20000 Hz line<br>40 - 18000 Hz phono   |
| S/N ratio:         | >97,2 dB line<br>>91,7 dB Microphone  |
| THD:               | Line <0,04 % at 1 kHz<br>Phono <0,13 % at 1 kHz<br>Microphone <0,008 % at 1 kHz   |
| Gain:              | Microphone 44 dB<br>Line -16,5 dB to +8,5 dB<br>Phono -48,5 dB to +23,5 dB  |
| DJ filter:         | Routable: LPF, BPF, HPF   |
| Isolators:         | Master Gain:- ? bis +9<br>Low/mid 300 Hz, 18db/oct , Butterworth<br>Mid/high 4000 Hz, 18db/oct , Butterworth                        |
| Crosstalk:         | >-68 dB   |
| Control elements:  | Power switch, source selector, Crossfader, Crossfader selector switch, Crossfade curve switch; Cue mix split function, tone control |
| Status LED:        | Power, master level meter, clip, CUE  |
| Connections:       | Input: line via 4 x stereo RCA<br>Input: line/phono via 4 x stereo RCA<br>Input: Microphone via 2 x 3-pin XLR                       |

Output: headphones via 1 x 6.3 mm jack socket (stereo) mounting version  
 Output: headphones via 1 x 3.5 mm jack (stereo) mounting version  
 Output: rec. via 1 x stereo RCA  
 Output: booth via 2 x 3-pin XLR  
 Output: booth via 1 x stereo RCA  
 Output: master via 2 x 3-pin XLR  
 Output: master via 1 x stereo RCA  
 Output: AUX sends via 1 x 6.3 mm jack socket (stereo) mounting version  
 Output: AUX returns via 1 x 6.3 mm jack socket (stereo) mounting version  
 Output: Timecode via 4 x stereo RCA

|                 |  |
|-----------------|--|
| Channels:       | <p>Input channel: 4 x stereo with Line-Line/Phono switch via RCA, channel control via Rotary, 3-band tone control EQ, source selector, gain control, CUE switch, FX routing switch, Crossfader selector switch</p> <p>Microphon channel: 2 x mono via XLR, channel control via Rotary dial, ON AIR switch</p> <p>Master output: 2 x stereo via XLR, channel control via Rotary, Cue mix split function</p> <p>Booth output: 2 x stereo via XLR, channel control via Rotary</p> <p>Rec. output: 1 x stereo via RCA</p> <p>Headphones output: 1 x stereo via Jack, channel control via Rotary dial</p> |
| Max. level:     | Output: +18 dBu  |
| Material:       | Metal  |
| Housing design: | Desktop console housing<br>(19") 48.3 cm rack installation possible  |
| Dimensions:     | Width: 41 cm<br>Depth: 28,5 cm<br>Height: 10,5 cm  |
| Weight:         | 5,74 kg  |

#### **ROADINGER Flightcase TRM-422**

|                          |   |
|--------------------------|---|
| Maximum load:            | 25 kg   |
| Removable covers:        | 1 pc/pcs  |
| Aluminum profile frames: | 22 mm   |
| Carrying handle:         | 1 pc/pcs  |
| Lock:                    | Spring lock: 2 pc/pcs                           |
| Transport aid:           | Rubber feet                                     |
| Use of brands:           | Branded hardware                                |
| Material:                | Birch multiplex, 6,5 mm                         |
| Color:                   | Dark brown, laminated                           |
| Device compartment:      | 41 cm x 27,5 cm x 10,5 cm                       |
| Dimensions:              | Width: 48 cm<br>Depth: 43 cm<br>Height: 17,5 cm |
| Weight:                  | 4,65 kg   |