

EUROLITE Set 4x LED PLL-480 QCL Panel + Case

Art. No.: 20000899

GTIN: 4026397696912



List price: 3866.31 €

incl. 19% VAT.

Features:

EUROLITE LED PLL-480 QCL Panel

DMX-controlled surface light with 480 4in1 RGBW LEDs

- 480 powerful LEDs SMD 5050 4in1 QCL RGBW (homogenous color mix)
- Frost filter provides a soft, homogeneous light
- 4 barn doors to avoid blinding the audience and for protection during transport
- Silent operation
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; pulse-width modulation variable
- Strobe effect
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; master/slave function
- Flicker-free
- With a beam angle of 120°
- With mounting bracket
- LCD display
- Slim, rugged metal housing
- Stand or truss installation
- For application areas such as: Video and photography; stage; theater; advertisement/Shop window
- Preprogrammed in Light´J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
- Rugged carrying handle
- Mains input and output for power linking up to 8 units
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x plug (male)

Logistic

EAN / GTIN: 4026397696912

Weight: 76,50 kg

Length: 1.20 m

Width: 0.80 m

Height: 1.00 m

Bulky product

ROADINGER Flightcase 4x LED PLL-480 with wheels

- 7 mm, dark brown, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes
- Branded hardware
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	72,20 kg
---------	----------

EUROLITE LED PLL-480 QCL Panel

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	205 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	480 x SMD 5050 4in1 QCL RGBW (homogenous color mix)
Flash rate:	1 - 19 Hz
DMX channels:	6; 4
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; master/slave function
Preprogrammed in:	Light´J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	120°
Beam angle (1/2 peak):	120°
Illuminance in Lux (lx):	Red (R) 1m: 438 lx, 3m: 61 lx, 6m: 18 lx Green (G) 1m: 633 lx, 3m: 88 lx, 6m: 25 lx Blue (B) 1m: 209 lx, 3m: 29 lx, 6m: 8 lx Cold white (CW) 1m: 2130 lx, 3m: 296 lx, 6m: 87 lx All 1m: 2696 lx, 3m: 380 lx, 6m: 112 lx
Lamp life:	50000 h
Luminous flux:	17103 lm

Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Carrying handle:	1 pc/pcs
Dimensions:	Width: 64 cm Depth: 13 cm Height: 33,5 cm
Weight:	12,60 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	F
EPREL-Nr:	1243720

ROADINGER Flightcase 4x LED PLL-480 with wheels

Maximum load:	100 kg
Aluminum profile frames:	25 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Use of brands:	Branded hardware
Color:	Dark brown, laminated
Inside dimensions:	70 cm x 66 cm x 35 cm
Accessory compartment:	8 cm x 66 cm x 35 cm
Device compartment:	14 cm x 65,5 cm x 35 cm
Material thickness:	7 mm
Dimensions:	Length: 74 cm Width: 71 cm Height: 52,5 cm
Weight:	21,80 kg