# EUROLITE Set LED KLS-902 + Laser Derby Mobile Bundle

**Art. No.: 20000911**
GTIN: 4026397700527

## List price: 1783.81 €

incl. 19% VAT.

## Features:

**EUROLITE LED KLS-902 Next Compact Light Set**

Bar with 4 powerful RGB/WW spots, QuickDMX support, IR remote control and carrying bag

- 5 powerful LEDs 7 W high-power 4in1 QCL RGB/WW (homogenous color mix)<BR> spots controlled separately
- Crossbar with integrated DMX control unit and TV spigot for tripod installation
- With a beam angle of 16°
- 20 integrated show programs
- Color blend stepless; Dimmer electronic; program selection
- Mounting points and power outlets for additional fixtures
- Control via DMX; stand-alone; Sound to light via Microphone; IR remote control; Wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- For application areas such as: Mobile use; Stage; mobile djs / entertainer; small rental; Rental
- Preprogrammed in EASY SHOW 1; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; Light´J; EASY SHOW 3
- Mains input and output for power linking up to 8 units
- Very quiet working noise
- Application possibility: Suspended; on stand

**Package contents**

- 1 x light effect, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 2 x omega bracket, 1 x declaration of conformity, 4 x knurled screw, 1 x bag

**EUROLITE LED Laser Derby MK2**

DMX light effect with RG laser (2M), rotating LED derby, stroboscope and IR remote control

## Logistic

EAN / GTIN: 4026397700527
Weight: 42,00 kg
Length: 0.00 m
Width: 0.00 m
Heigth: 0.00 m
Bulky product

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- 2 laser diodes project hundreds of red and green laser beams
- 7 integrated show programs
- Dimmer electronic; color macros adjustable
- Control via IR remote control; stand-alone; DMX; Master/slave function; Sound to light via Microphone; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
- The device is cooled by cooling fan
- With Mounting bracket
- 4 digit 7-segment LED display
- Laser; multi beam effect; Strobe effect
- Preprogrammed in Light Captain; EASY SHOW 2
- For application areas such as: Clubs/dancing school; Party room; mobile djs / entertainer; small rental
- Application possibility: Suspended; on stand

**laser**

- Laser class 2M <BR> does not require additional protective measures or appointment of a laser safety officer

**light effect**

- 4 powerful LEDs 10 W SMD 5050 R/G/B/W

**strobes**

- 16 powerful LEDs 0,6 W SMD 2835 cold white (CW)

**Package contents**

- 1 x device, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 1 x mounting bracket, 2 x knurled screw, 4 x washer

**EUROLITE DMX LED Color Chief Controller**

DMX lighting desk with innovative control concept for LED spotlights

- Easy control of LED spotlights with up to 6 colors, light bars as well as simple lighting effects
- For 8 devices or device groups, each with up to 4 segments
- Quick and easy programming
- Additional fixtures can be configured manually
- 8 color effects directly selectable
- 3 additional channels available per fixture (e.g. for rotations)
- Color wheel selection and simulation
- 24 memory spaces for scenes and chases
- Several chases and scenes can be run simultaneously
- USB port for storing program data
- Sound control via audio signal or TAP button
- Master dimming, fade time and run time easily adjustable
- Programmable 24 scenes/chases  distributed over 1 page/s
- Can transmit up to 240 DMX channels
- Control via DMX; Sound to light via RCA (F) mounting version; Sound to light via Microphone
- (19") 48.3 cm rack installation  3 U
- Desktop console housing
- For application areas such as: Clubs/dancing school; Party room; Trade fair and shop fitting; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation
- Firmware can be updated

**Package contents**

- 1 x controller, 1 x user manual, 1 x external mains adapter

**EUROLITE STV-60-WOT EU Steel Stand black**

Lighting stand, made in EU, maximum load 30 kg, height 150-315 cm

- Stable lighting stand for mobile use
- TV spigot
- Available in various colors
- Made in Europe
- For application areas such as: Mobile use
- Adjustable height

**Package contents**

- 1 x stand, 1 x user manual

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

**EUROLITE SB-4 Soft Bag L**

Black soft bag for up to 4 devices, 320 x 320 x 200 mm

- Practical transport bag offers enough space for several lighting effects and accessories
- With Dividers
- With 2 Outside pockets
- With 4 Device compartments
- High-quality workmanship with nylon , black, water repellent
- Interior with foam padding<BR>cover with foam padding
- 2 carrying straps

**Package contents**

- 1 x bag

**OMNITRONIC IEC Extension 3x0.75 0.6m bk<p class='attributgroup'>Package contents**

- 1 x network cable

**ROADINGER Mixer Case Pro MCA-19-N, 3U, black**

Rack case

- Upward tilted profile rails for top-operated units
- High-quality workmanship with plywood multi-layer glued 7 mm, black, laminated
- Interior with foam padding
- Removable cover
- Aluminum profile frames 30mm with rounded edges
- Rugged carrying handle
- 2 high-quality butterfly locks
- Rubber feet
- With profile rails suitable for 19" units
- 3 U

**Package contents**

- 1 x case

**EUROLITE QuickDMX Wireless Transmitter**

Compact wireless DMX transmitter 2.4 GHz

- User-friendly 3-pin XLR adapter (male) with swivel antenna
- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to GFSK modulation with 78 channels, interference-free operation also alongside other QuickDMX transceiver and wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- 1 to 512 QuickDMX receivers can be controlled by each transmitter
- LED indication for functions
- Transceiver, to be used as transmitter or receiver
- Can transmit up to 512 DMX channels
- Control via QuickDMX; DMX; plug and play
- Operating range up to 400m
- Up to 6 transmitters can be operated in parallel without interference

**Package contents**

- 1 x device, 1 x user manual, 1 x declaration of conformity, 1 x external mains adapter, 1 x uSB cable

**EUROLITE QuickDMX USB Wireless Transmitter/Receiver**

Wireless miniature DMX transceiver 2.4 GHz, phantom powered

- User-friendly USB plug with swivel antenna
- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to GFSK modulation with 78 channels, interference-free operation also alongside other QuickDMX transceiver and wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- LED indication for functions

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- Transceiver, to be used as transmitter or receiver
- Requires 5 V phantom power for operation
- Can receive and process up to 512 DMX channels
- Can transmit up to 512 DMX channels
- Control via DMX; QuickDMX; plug and play
- Operating range up to 400m with line-of-sight
- Up to 6 transmitters can be operated in parallel without interference

**Package contents**

- 1 x device, 1 x user manual, 1 x declaration of conformity

## Technical specifications:

| | |
|---|---|
| Weight: | 28,55 kg |

**EUROLITE LED KLS-902 Next Compact Light Set**

| | |
|---|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 125 W |
| IP classification: | IP20 |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Cable length: | 3 m |
| Power output: | 2 x IEC connector (F) mounting version<br>1 x P-Con (gray), mounting version |
| Device fuse: | 5 x 20 mm, T 2 A Fuse replaceable |
| Power output fuse per channel: | 5 x 20 mm, T 5 A Fuse replaceable |
| Battery: | 1 x  Button cell 3.0 V CR2025 lithium manganese built-in |
| Lamp type: | LED lamp |
| LED type: | 5 x 7 W high-power 4in1 QCL RGB/WW (homogenous color mix) |
| DMX channels: | 3; 4; 6; 8; 16; 20; 18 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | DMX; stand-alone; Sound to light via Microphone; IR remote control; Wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Preprogrammed in: | EASY SHOW 1; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; Light´J; EASY SHOW 3 |
| Beam angle: | 16° |
| Beam angle (1/2 peak): | 16° |
| Beam angle (1/10 peak): | 32° |
| Housing color: | Black |
| Attachment system: | TV spigot Ø 28mm<br>Omega bracket |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| | |
|---|---|
| Dimensions: | Width: 1,08 m<br>Depth: 6 cm<br>Height: 28 cm |
| Weight: | 9,80 kg |
| Noise classification: | Class 1 (very slight noise, suitable for noise-sensitive environments) |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

**EUROLITE LED Laser Derby MK2**

| | |
|---|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 60 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via IEC (M) power supply cord with safety plug |
| Power output: | IEC connector (F) mounting version Bypass |
| Fuse: | 5 x 20 mm, T 1,6 A Fuse replaceable |
| Lamp type: | LED lamp |
| DMX channels: | 2; 4; 5; 6; 8; 7; 9 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Cooling fan |
| Control: | IR remote control; stand-alone; DMX; Master/slave function; Sound to light via Microphone; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional) |
| Preprogrammed in: | Light Captain; EASY SHOW 2 |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Display type: | 4 digit 7-segment LED display |
| Control elements: | Navigation keys, sensitivity rotary dial |
| Status LED: | DMX, slave mode, auto mode, sound mode |
| Dimensions: | Width: 26 cm<br>Depth: 19 cm<br>Height: 19 cm |
| Weight: | 2,17 kg |
| Power cord | |
| Cable length: | 1,5 m |
| Remote control | |
| Battery: | 1 x  Button cell 3.0 V CR2025 lithium manganese built-in |
| Laser | |
| Laser class: | 2M |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| | |
|---|---|
| Laser color: | R/G |
| Laser module: | Green (G) 35 mW 515nm<br>Red (R) 100 mW 650nm |
| Light effect | |
| LED type: | 4 x 10 W SMD 5050 R/G/B/W |
| Strobes | |
| LED type: | 16 x 0,6 W SMD 2835 cold white (CW) |

**EUROLITE DMX LED Color Chief Controller**

| | |
|---|---|
| Power supply: | 100-240 V AC, 50/60 Hz<br>9 V DC 800 mA |
| Power consumption: | 10 W |
| IP classification: | IP20 |
| Power connection: | Mains input via Coaxial power connector (M) mounting version power supply cord with AC adapter (provided) |
| Programs: | Programmable 24 scenes/chases distributed over 1 page/s |
| DMX channels: | Output 240 |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Control: | DMX; Sound to light via RCA (F) mounting version; Sound to light via Microphone |
| Housing color: | Black |
| Available storage media: | USB devices (FAT 32) |
| USB port: | Typ A |
| Color: | Black |
| PC connect: | , firmware can be updated |
| Housing design: | (19") 48.3 cm rack installation 3 U<br>Desktop console housing |
| Dimensions: | Width: 48,3 cm<br>Depth: 13,35 cm<br>Height: 8,5 cm |
| Weight: | 2,25 kg |
| Noise classification: | Class 0 (no noise at all) |

**EUROLITE STV-60-WOT EU Steel Stand black**

| | |
|---|---|
| Maximum carrying capacity: | 30 kg |
| Height: | Maximum: 320 cm<br>Minimum: 150 cm |
| Attachment system: | TV spigot Ø 28mm |
| Type (general stands): | Light stand/manual |
| Material: | Steel/magnesium |
| Color: | Black |
| Transport dimensions: | 1,26 m x 12 cm x 15 cm |
| Weight: | 5,65 kg |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

**EUROLITE SB-4 Soft Bag L**

| | |
|---|---|
| Maximum load: | 25 kg |
| Carrying strap: | 2 pc/pcs |
| Material: | Nylon |
| Color: | Black, water repellent |
| Compartment dimensions: | 15 cm x 15 cm x 20 cm |
| Inside dimensions: | 31 cm x 34 cm x 20 cm |
| Dimensions: | Width: 32 cm<br>Depth: 41 cm<br>Height: 20 cm |
| Weight: | 520 g |

**OMNITRONIC IEC Extension 3x0.75 0.6m bk**

| | |
|---|---|
| Cable construction: | 3 x 0,75 mm² Power cable |
| Cable length: | 0,6 m |
| Plug A: | 1 x IEC (M) |
| Plug B: | 1 x IEC (F) |
| Color: | Black |
| Weight: | 80 g |

**ROADINGER Mixer Case Pro MCA-19-N, 3U, black**

| | |
|---|---|
| Maximum load: | 25 kg |
| Removable covers: | 1 pc/pcs |
| Aluminum profile frames: | 30 mm |
| Carrying handle: | 1 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |
| Transport aid: | Rubber feet |
| Material: | Plywood multi-layer glued, 7 mm |
| Color: | Black, laminated; dark brown, laminated |
| Inside dimensions: | 45 cm x 20 cm x 10,5 cm |
| Front panel width: | 19" |
| Mounting height: | Approx. 13.5 cm (3 U) |
| Mounting depth: | 105 mm |
| Housing design: | 3 U |
| Dimensions: | Width: 55 cm<br>Depth: 24 cm<br>Height: 23,5 cm |
| Weight: | 5,10 kg |

**EUROLITE QuickDMX Wireless Transmitter**

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| | |
|---|---|
| Power supply: | 100-240 V AC, 50/60 Hz<br>5 V DC 1 A |
| IP classification: | IP20 |
| Power connection: | Mains input via Coaxial power connector (M) mounting version power supply cord for USB A mains connection (provided) |
| DMX channels: | Output 512 |
| DMX input: | 1 x 3-pin XLR (M) |
| Control: | QuickDMX; DMX; plug and play |
| Range: | Range up to 400m |
| Carrier frequency: | 2,4 GHz |
| Parallel mode: | Max. 6 transmitter |
| RF power output: | 19 dBm |
| Modulation: | GFSK |
| Color: | Silver |
| Dimensions: | Length: 21,2 cm<br>Diameter: Ø 1,8 cm |
| Weight: | 150 g |

**EUROLITE QuickDMX USB Wireless Transmitter/Receiver**

| | |
|---|---|
| Power supply: | 5 V DC |
| IP classification: | IP20 |
| Power connection: | Mains input via USB A (M) connectable version |
| DMX channels: | Input 512<br>Output 512 |
| DMX output: | 1 x USB, type A |
| Control: | DMX; QuickDMX; plug and play |
| Range: | Range up to 400m with line-of-sight |
| Carrier frequency: | 2,4 GHz |
| Parallel mode: | Max. 6 transmitter |
| RF power output: | 23 dBm |
| Modulation: | GFSK |
| Color: | Black |
| Dimensions: | Width: 8,6 cm<br>Depth: 4 cm<br>Height: 1,1 cm |
| Weight: | 10 g |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.